

Painter's Plus

Painter's Plus is a premium grade caulk formulated for use on a variety of interior and exterior applications. Designed to prevent paint cracking, won't shine through paint, and is easily applied with consistent flow/without air pops. Paintable in 30 minutes, compatible with oil and water-based paints, as well as can be spray painted immediately.

FEATURES:

- Paintable in 30 Minutes
- Interior & Exterior Use
- No Air Pops
- Resists Paint Cracking
- Won't Shine Through Paint
- Excellent Flexibility
- Strong Adhesion
- Easy Application & Smooth Tooling
- VOC Compliant
- Water Clean-Up

USE ON:

- Windows & door frames
- Trim
- Baseboards
- Moldings
- Skirting
- Corner joints
- Stairs
- Vents
- Pipes

ADHERES TO:

- Painted and unpainted wood
- Aluminum
- Brick
- Metal
- Plaster/Drywall
- Glass



**PAINTABLE IN
30 MINUTES**



**EASY APPLICATION
& NO AIR POPS**



**WON'T SHINE
THROUGH PAINT**



**RESISTS
PAINT CRACKING**



**INTERIOR
& EXTERIOR**



TECHNICAL DATA SHEET

Painter's Plus

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0766	Pure White	10.1 fl. oz (300 mL) Cartridge	0-75339-03404-0	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 13.5

Specific Gravity: Approx. 1.60

Total Non-Volatile % Solids (Weight): > 85% +/- 2.5

Extrudability/Application: 802g/min

Consistency/Appearance: Smooth, White Paste

pH (initial): Approx. 8

Odor: Very Mild

Base Polymer: Proprietary Polymer

Filler/Pigment: Calcium Carbonate/TiO2

Flash Point: Non-Flammable; >200°F

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Expect 1 Year @ 72°F

Tack Free Time: 30 Minutes

Full Cure: 72 Hours

Storage Conditions: 40°F to 90°F (5°C to 32°C)

Application Temperature: 40°F to 90°F (5°C to 32°C)

Elongation: 113%

Service Temperature: -20°F to 180°F (-29°C to 82°C)

Paintability: 30 Minutes with Brush / Immediately with Sprayer

Clean-Up: Water

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size (Up to 3/8" bead size). Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife, or Damp Cloth for neat appearance. Remove excess caulk immediately with clean, damp cloth before surface skins over. Allow 30 minutes for caulk to skin before painting or use a paint sprayer immediately. Clean-up with mild soap and water.

LIMITATIONS:

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics.
- Not intended for sealing building envelope.
- Not recommended for below water line applications.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazzard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 0.5% by weight, < 5 g/L

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠️ WARNING: Cancer Risk From Titanium Dioxide Exposure - www.P65Warnings.ca.gov