

Painter's Caulk

Painter's Caulk is an acrylic latex caulk specifically formulated to offer exceptional paintability with all types of paint. This easy to apply and paintable caulk allows you to paint in two hours. Painter's caulk is mildew resistant when cured.

FEATURES:

- Easy Application and Tooling
- Water Clean-up
- Paintable in 2 Hours
- Interior & Exterior Use
- Mildew Resistant When Cured
- 25-year Limited Warranty

USE ON:

- Windows & Door Frames
- Trim
- Baseboards
- Molding
- Siding

ADHERES TO:

- Painted and Unpainted Wood
- Aluminum
- Brick
- Metal
- Plaster/Drywall
- Glass



**PAINTABLE
IN 2 HOURS**



**INTERIOR
& EXTERIOR**



FLEXIBLE



**WATER
CLEAN-UP**



**MOLD & MILDEW
RESISTANT
WHEN CURED**



TECHNICAL DATA SHEET

Painter's Caulk

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0746	White	10.1 fl. oz (300 mL) Cartridge	0-75339-00746-4	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 14.0 +/- 1

Specific Gravity: Approx. 1.55 to 1.80

Total Non-Volatile % Solids (Weight): > 80% +/- 2.5

Extrudability/Application: 12 Seconds +/- 5

Consistency/Appearance: Smooth, Colored Paste

pH (initial): Approx. 7.5 +/- 0.5

Odor: Mild

Base Polymer: Proprietary Polymer

Filler/Pigment: Calcium Carbonate/TiO₂

Flash Point: Non-Flammable; >200°F

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Expect 1 Year @ 72°F

Tack Free Time: <1 hour @ 40°F

Full Cure: 72 Hours

Storage Conditions: 40°F to 90°F (5°C to 32°C)

Application Temperature: 40°F to 90°F (5°C to 32°C)

Elongation: 200%

Service Temperature: -20°F to 180°F (-29°C to 82°C)

Paintability: 24 to 72 hours

Clean-Up: Water

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size (Up to 3/8" bead size). Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife, or Damp Cloth for neat appearance. Remove excess caulk immediately with clean, damp cloth before surface skins over. Wait 2 hours before painting with latex paint, or 24 hours with oil-based paint. Clean-up with mild soap and water.

LIMITATIONS:

- Application when surface and air temperatures are above 32°F/ 0°C and Below 90°F/ 32°C
- Joint size should not exceed 3/8". If joint depth exceeds 3/8", use backer rod. (3/8" is the Max)
- Protect from rain/water exposure for 72 hours. Painting is recommended.
- Not recommended for use on fishtanks/aquariums, marine applications, mirrors, or automobiles.
- Not recommended for below water line applications.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5% by weight, < 25 g/L

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Cancer Risk From Titanium Dioxide Exposure - www.P65Warnings.ca.gov