



Red Devil

QUICK[®]paint

Specially formulated for the professional paint contractor. This styrenated, siliconized acrylic caulk has the fastest paint over time in the industry - just 30 minutes with latex paint, 2 hours with oil-based paint, or immediately with spray paint. This premium caulk is designed with higher solids to reduce shrinkage and comes with a 40-year durability guarantee. It's easy to use, adheres to most construction surfaces indoors or outdoors, clean up easily with water, and is mildew resistant when cured.

FEATURES:

- Interior/Exterior Use
- Excellent Adhesion
- Excellent Flexibility
- Low VOC
- Brush ready in 30 minutes
- No Paint Film Cracking
- Easy Water Clean Up
- Mold & Mildew Resistant
- Multi Surface Application
- Easy Water Clean-Up

USES:

Formulated for use on Window & Door Frames, Baseboards, Moldings, Splashboards, Eaves, and most common construction surfaces.

ADHERES TO:

Painted & Unpainted Wood, Glass, Aluminum, Masonry, Brick, Metal, Concrete & More.



INTERIOR &
EXTERIOR USE



PAINTABLE IN
MINUTES



MOLD & MILDEW
RESISTANT
WHEN CURED



MULTI-SURFACE
APPLICATION



Meets or Exceeds Federal Specifications:

- ASTM C834-05 Performance
- Recommended Thrust Ratio: 6:1 & Up



www.reddevil.com

Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

QUICKpaint®

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0946	White	10.1 fl. oz (300 mL) Cartridge	0-75339-00994-9	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 14 +/- .50

Specific Gravity: Approx. 1.50 to 2.0

Total Non-Volatile % Solids (Weight): > 85% +/- 2.5

Extrudability/Application: 10 seconds +/- 3

Consistency/Appearance: Creamy, Viscous Paste

pH (initial): 7 to 9

Odor: Mild Acrylic

Base Polymer: Styrenated Acrylic Blend

Filler/Pigment: Calcium Carbonate, TiO₂

Flash Point: Non-Flammable; >200F

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Expect 1 Year @ 72°F

Tack Free Time: 30 Minutes - Pass (No Stick)

Full Cure: 72 Hours (cool & humid environments will extend)

Storage Conditions: 40°F to 90°F (5°C to 32°C)

Application Temperature: 40°F to 90°F (5°C to 32°C)

Tooling: Excellent

Elongation at Break/Ultimate Tensile: 350%

Service Temperature: 0°F to 200°F (-17°C to 28°C)

Coverage: 50 - 55 Linear Feet (3/16" Bead)

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5%/wt, < 25 g/L

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife or Damp Cloth. Remove excess with a damp cloth before surface skins over. Just 30 minutes with latex paint, 2 hours with oil-based paint, or immediately with spray paint.

FOR BEST RESULTS:

- Apply when surface and air temperatures are above freezing and below 90°F.
- Joints deeper than ½", use a backer rod.
- Prime bare surfaces before caulking.
- Store at temperatures above freezing and below 90°F.
- Do not overtool.

CLEAN-UP:

Mild Soap and Water.

LIMITATIONS:

- Not recommended for use on automobiles, fish tanks/aquariums, and mirrors.
- Apply only to clean, dry substrates.
- Protect from water until cured (72 Hours) - Cooler temperatures & higher humidity will extend cure time.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide and Carbon Black Exposure - www.P65Warnings.ca.gov