

**POLYURETHANE**  
**Fix-A-Floor®**  
**WOOD FLOORING REPAIR**

**TECHNICAL  
DATA SHEET**

[www.fixafloorworldwide.com](http://www.fixafloorworldwide.com)

[info@fixafloorworldwide.com](mailto:info@fixafloorworldwide.com)

Customer Service: 800-774-5981

Fix-A-Floor Polyurethane Wood Floor Repair Adhesive is an Extra Strength, Super Blend Formula! Created specifically for Re-Bonding those Loose & Hollow, Squeaky, Popping, Bouncy Wood Floors. No need to remove or replace, Just Drill & Fill! The narrow tip allows for the smallest holes to be drilled leaving an undetectable permanent repair.

**PHYSICAL & CHEMICAL PROPERTIES:**

**Base Polymer:** Polyurethane Prepolymer

**Weight Per Gallon:** 10 lb/gal

**Specific Gravity:** Approx. 1.2

**Viscosity:** 4800 cps

**Consistency/Appearance:** Slight haze, clear to yellow liquid

**Odor:** Slight isocyanate

**Flash Point:** Approx. 420°F

**Coverage:** 4 sq. ft.

**Freeze/Thaw Stability:** Pass 5 Cycles (ASTM C731)

**Shelf Life:** Expect 1 Year @ 72°F

**Full Cure:** 24 Hours

**Storage Conditions:** 32°F to 95°F (0°C to 35°C)

**Application Temperature:** 40°F to 90°F (4°C to 35°C)

**Service Temperature:** -40°F to 194°F (-40°C to 90°C)

**Shear Adhesion Strength to Wood:** 162 lbs.

**Lap Shear Adhesion Strength:** 330 psi

**Clean-Up:** Mineral Spirits

**FEATURES:**

- Provides extra strength, permanent adhesion to a wide range of wood flooring types.
- Low odor, non-toxic, non-flammable, & low VOC.
- Works for interior & exterior applications

**ADHERES TO:**

- Solid Hardwoods
- Engineered Hardwood
- Luxury Wood Plank
- Bamboo Flooring
- Laminate Flooring

**RECOMMENDATIONS/LIMITATIONS:**

- After initial application, place weight on the application area and let it remain in place for 24 hours
- Stress on planks due to improper installation will limit the success of the product. Properly installed movement joints should be used.
- If the plank has been completely removed, Fix-A-Floor® can be used as a general adhesive to reattach it.
- When using the product on underfloor heating elements, turn the heating elements off for 48 hours before, during, and after application.
- For outdoor applications, ensure rain is not anticipated for 24-48 hours before and after application.

**LIMITED WARRANTY:**

This product is warranted to be free of manufacturing defects. If a manufacturing defect is found within one year from the date of purchase, such defective product shall be replaced. No warranty either expressed or implied is made regarding the performance of this product since conditions under which these goods are transported, stored, used, or applied are beyond our control. This warranty is made in lieu of all other warranties either expressed or implied and the seller shall not be responsible for consequential, incidental, special or other damages no matter what the cause.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	No
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazzard	None
VOC Content	See MSDS

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)**