

# Material Safety Data Sheet

0788PM Paint Master – 45 Yr Elastomeric Adhesive Sealant - White

MSDS No. 0150 Rev. 5

Emergency Phone No.  
(918)825-5744

## SECTION 1 – PRODUCT NAME & MANUFACTURER INFORMATION

PRODUCT NAME	Paint Master 45 Yr Elastomeric Adhesive Sealant - White		
MANUFACTURER'S NAME & TELEPHONE NUMBER	Red Devil, Inc.	918-825-5744	
STREET ADDRESS	4175 Webb Street		
CITY / STATE / ZIP	Pryor, Oklahoma 74361		

## SECTION 2 – COMPOSITION / HAZARDOUS INGREDIENTS

	%	TLV	PEL	UNITS
<b>PRODUCT CONSISTS OF:</b>				
Calcium Carbonate ** (1317-65-3)	< 55	10	15	mg/m3
Acrylic Emulsion Blend (mixture)	< 30	NE	NE	
Benzoate Ester (proprietary)	< 8	NE	NE	
Petroleum Distillate (64742-48-9)	< 0.75	100	100	ppm
Titanium Dioxide ** (13463-67-7)	< 1.5	10	15	mg/m3
Propylene Glycol (57-55-6)	< 2	400***	NE	ppm
Non-hazardous ingredients*	< 5	NA	NA	

\*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). \*\*Inhalation not likely due to product's physical state. \*\*\*TWA. \*\*\*\*Formula contains no EG (HAPS). Calculated VOC: <1.5 %/wt, < 25 g/L. CARB Compliance: Yes. Prop 65 Ingredients: Yes (See Section 16)

## SECTION 3 – HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF ENTRY	<input checked="" type="checkbox"/> Skin Contact	<input checked="" type="checkbox"/> Skin Absorption	<input checked="" type="checkbox"/> Eye Contact	<input checked="" type="checkbox"/> Inhalation	<input checked="" type="checkbox"/> Ingestion
EMERGENCY OVERVIEW	White paste w/ slight odor. Warning. Harmful if swallowed or absorbed through skin. May cause eye, skin, nose, throat & respiratory tract irritation.				
EFFECTS OF OVEREXPOSURE	<u>Eye Contact:</u> May cause eye irritation. <u>Skin Contact:</u> Harmful if absorbed through skin. May cause allergic reaction or dermatitis. <u>Inhalation:</u> May cause irritation of respiratory tract. <u>Chronic Hazards:</u> Prolonged or repeated skin contact may cause irritation.				
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	None known.				

## SECTION 4 – FIRST AID MEASURES

SKIN CONTACT	Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.
EYE CONTACT	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.
INHALATION	Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.
INGESTION	DO NOT INDUCE VOMITING. Get immediate medical attention.

## SECTION 5 – FIRE FIGHTING MEASURES

<b>FLAMMABLE</b>	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
<b>EXTINGUISHING MEDIA</b>	Carbon Dioxide, Dry Chemical, Foam, Water Fog		
<b>FLASHPOINT (°F) &amp; METHOD</b>	> 200F (Closed Cup)	<b>UPPER EXPLOSIVE LIMIT (% BY VOLUME)</b>	NE
<b>LOWER EXPLOSIVE LIMIT (% BY VOLUME)</b>	NE	<b>AUTOIGNITION TEMPERATURE (°F)</b>	NE
<b>UNUSUAL FIRE &amp; EXPLOSION HAZARDS</b>	None known.		
<b>SPECIAL FIREFIGHTING PROCEDURES</b>	Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces.		

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

<b>PROCEDURES</b>	Wear proper protective equipment (Section 8). Use absorbent material or scrape up dried material & place in approved container.		
-------------------	---	--	--

## SECTION 7 – HANDLING & STORAGE

<b>HANDLING PROCEDURES &amp; EQUIPMENT</b>	Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing. Odor is not an adequate warning of hazardous conditions.		
<b>STORAGE REQUIREMENTS</b>	Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120F. Store away from caustics & oxidizers.		

## SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

<b>RESPIRATORY</b>	In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator w/ organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits. <b>Engineering Controls:</b> Good general ventilation should be sufficient for control of airborne levels. Ensure adequate ventilation, especially in confined areas. Local ventilation of emission sources may be necessary to maintain concentrations below recommended exposure limits.		
<b>EYEWEAR</b>	Goggles or safety glasses w/ side shields.		
<b>CLOTHING / GLOVES</b>	Rubber gloves.		
<b>HYGENIC PRACTICES</b>	Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of day.		

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

<b>PHYSICAL STATE</b>	Paste	<b>ODOR &amp; APPEARANCE</b>	Mild acrylic odor. Smooth paste.
<b>SPECIFIC GRAVITY</b>	Approximately 1.55 to 1.65	<b>VAPOR DENSITY (AIR=1)</b>	Heavier than air
<b>EVAPORATION RATE</b>	NE	<b>BOILING RANGE (°F)</b>	NE
<b>pH</b>	7.0 to 10.0	<b>SOLUBILITY IN WATER</b>	NE
<b>VAPOR PRESSURE (MM Hg)</b>	NE	<b>%/WT VOLATILE (TNV)</b>	Approximately 15 to 20%

## SECTION 10 – STABILITY AND REACTIVITY

<b>STABILITY</b>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Stable under normal conditions.	
<b>INCOMPATIBILITY</b>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Incompatible w/ strong bases & oxidizing agents.	
<b>CONDITIONS TO AVOID</b>	Excessive heat & freezing.		
<b>HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS</b>	Hazardous polymerization will not occur under normal conditions. Normal decomposition products, ie: COx, NOx.		

## SECTION 11 – TOXICOLOGICAL INFORMATION / CARCINOGENICITY

ACGIH	Small amount of Silica, crystalline present in Calcium Carbonate & trace residual Formaldehyde present in base emulsion blend are suspected human carcinogens.
OSHA	Trace residual Formaldehyde present in base emulsion viewed as a potential cancer hazard.
IARC	Trace residual Formaldehyde: Human carcinogen.
NTP	Silica, crystalline, present in small amount in Calcium Carbonate Filler: Known carcinogen. Trace residual Formaldehyde: Anticipated carcinogen.
DATA WITH POSSIBLE RELEVANCE TO HUMANS	Product contains trace amounts of residual Formaldehyde. OSHA & NTP identify Formaldehyde as a potential carcinogen. IARC identifies Formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, w/ human significance unknown. Rats have shown carcinogenic effects in respiratory system. Risk should be minimal when used w/ adequate ventilation. Maintain adequate ventilation to prevent exposure above OSHA exposure limits.

## SECTION 12 – ECOLOGICAL INFORMATION

AQUATIC TOXICITY	Not known or expected under normal use.
------------------	---

## SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL	Dispose of material in accordance w/ Federal, State & Local regulations.
EPA WASTE CODE IF DISCARDED (40CFR Sec.261)	This product does not meet the definition of a hazardous waste according to U. S. EPA Hazardous Waste Management Regulation, 40 CFR Sec 261.

## SECTION 14 – TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION	DOT Proper Shipping Name: Not Regulated by DOT. DOT Technical Name: NA. Packing Group: NA. Hazard Subclass: NA. DOT Hazard Class: NA. DOT UN/NA Number: NA. Shipping information is applicable for domestic ground transport only. Different categorization may apply if shipped via other modes of transportation &/or to non-domestic destinations.
------------------------------	---

## SECTION 15 – REGULATORY INFORMATION

CERCLA – SARA HAZARD CATEGORY	Immediate health hazard. Chronic health hazard. SARA 311/312: Yes. Acute & Chronic.	U.S. STATE REGS	See Section 16.
SARA 313	None.	TSCA	All ingredients either on TSCA Inventory or exempt.

## SECTION 16 – OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

NJ Right-to-Know: (Top 5 Ingredients): Calcium Carbonate (1317-65-3), Base Acrylic Emulsion Blend (mixture), Benzoate Ester (proprietary), Water (7732-18-5), Petroleum Distillate (64742-48-9). Pennsylvania Right-to-Know (Non-Haz @ >3%): Water (7732-18-5). Ingredients Known to State of California to cause cancer &/or developmental toxicity &/or reproductive toxicity: Formaldehyde (50-00-0), Silica, crystalline (14808-60-7). HMIS Ratings: Health: 1, Flammability: 1, Reactivity: 0, Personal Protection: X. Titanium Dioxide (13463-67-7) added to Massachusetts Right to Know List, Minnesota Hazardous Substance List, New Jersey Right to Know List, Pennsylvania Right to Know List & Rhode Island Hazardous Substance List. WHMIS Ingredient Disclosure List: Yes. IMDG Regulated: None. TDG-Canada Regulated: None. IATA Regulated: None. RoHS Ingredients: None. **WARNING**: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**LEGEND**: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act

Reviewed By: <u>Larry G. Brandon</u>	<u>VP Technology &amp; General Manager</u>	<u>February 4, 2010</u>
NAME	TITLE	DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.