

Material Safety Data Sheet

0531PM, 0532PM, 0534PM Series Paint Master
Vinyl Spackling Compound

MSDS No. 0160 Rev. 3

Emergency Phone No.
(918)825-5744

SECTION 1 – PRODUCT NAME & MANUFACTURER INFORMATION

PRODUCT NAME Paint Master Vinyl Spackling Compound

MANUFACTURER'S NAME & TELEPHONE NUMBER Red Devil, Inc. 918-825-5744

STREET ADDRESS 4175 Webb Street

CITY / STATE / ZIP Pryor, Oklahoma 74361

SECTION 2 – COMPOSITION / HAZARDOUS INGREDIENTS

PRODUCT CONSISTS OF:

	%	TLV	PEL	UNITS
Aqueous Vinyl Acrylic Emulsion (mixture)	< 20	NE	NE	
Soda Lime Borosilicate ** (65997-17-3)	< 4	NE	NE	
Calcium Carbonate ** (1317-65-3) (as nuisance particulate, total)	< 70	10	15	mg/m3
Amino Methyl Propanol (AMP-95) (124-68-5)	< 0.10	NE	NE	
Propylene Glycol (57-55-6) ****	< 1	400***	NE	ppm
Non-hazardous ingredients *	< 20	NA	NA	

*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). ** Inhalation not likely due to products physical state. *** TWA. **** Contains no EG.
Calculated VOC: < 0.5 %/wt, < 10 g/L. CARB Compliance: Yes. Prop 65 Ingredients: Yes (See Section 16)

SECTION 3 – HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF ENTRY Skin Contact Skin Absorption Eye Contact Inhalation Ingestion

EMERGENCY OVERVIEW White to slightly off-white paste w/ a slightly sweet odor. May cause eye, skin, nose, throat & respiratory tract irritation.

EFFECTS OF OVEREXPOSURE May cause eye, skin, nose, throat & respiratory tract irritation. Harmful if swallowed. Inhalation of dust may result in pulmonary & respiratory damages. Prolonged or repeated exposure to dust may cause lung damage. This product may contain small amounts of vinyl acetate, identified by IARC as a potential carcinogen; however there should be minimal risk when used w/ ventilation adequate to keep the atmospheric concentration of vinyl acetate below the recommended exposure limit.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE If dry sanded, asthma & asthma-like conditions may worsen from prolonged or repeated exposure to dust.

SECTION 4 – FIRST AID MEASURES

SKIN CONTACT Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.

EYE CONTACT Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.

INHALATION If inhaled, remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.

INGESTION DO NOT INDUCE VOMITING. Get immediate medical attention.

SECTION 5 – FIRE FIGHTING MEASURES

FLAMMABLE Yes No

EXTINGUISHING MEDIA Carbon Dioxide, Dry Chemical, Foam, Water Fog

FLASHPOINT (°F) & METHOD >200F (Seta Closed Cup)

UPPER EXPLOSIVE LIMIT (% BY VOLUME) NE

LOWER EXPLOSIVE LIMIT (% BY VOLUME) NE

AUTOIGNITION TEMPERATURE (°F) NE

UNUSUAL FIRE & EXPLOSION HAZARDS None known.

SPECIAL FIREFIGHTING PROCEDURES Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PROCEDURES Wear proper protective equipment (Section 8). Use absorbent material or scrape up dried material & place in approved container.

SECTION 7 – HANDLING & STORAGE

HANDLING PROCEDURES & EQUIPMENT Keep out of reach of children & pets. Do not take internally. Do not breathe vapors or inhale dusts of this product. Avoid contact w/ skin & eyes. Do not get on clothing. Use w/ adequate ventilation. Ensure fresh air during application & drying by opening windows & doors.

STORAGE REQUIREMENTS Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120F. Store away from caustics & oxidizers.

SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

RESPIRATORY In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator w/ organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits. Prevent build-up of dust & vapors by opening windows & doors. Wet sanding is recommended to avoid generation of dust.

EYEWEAR Goggles or safety glasses w/ side shields.

CLOTHING / GLOVES Gloves recommended for prolonged or repeated skin contact.

HYGENIC PRACTICES Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of workday.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE Paste ODOR & APPEARANCE Slight sweet. White/slightly off-white paste.

SPECIFIC GRAVITY Approximately 1.15 to 1.25 VAPOR DENSITY (AIR=1) NE

EVAPORATION RATE NE BOILING RANGE (°F) NE

pH Approximately 7 to 9 SOLUBILITY IN WATER NE

VAPOR PRESSURE (MM Hg) NE %/WT VOLATILE (TNV) < 30%

SECTION 10 – STABILITY AND REACTIVITY

STABILITY Yes No Stable under normal conditions.

INCOMPATIBILITY Yes No Incompatible w/ strong bases & strong oxidizing agents.

CONDITIONS TO AVOID Excessive heat & freezing.

HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS Hazardous polymerization will not occur under normal conditions. Normal decomposition products, ie: COx, NOx.

SECTION 11 – TOXICOLOGICAL INFORMATION / CARCINOGENICITY

ACGIH	Silica, crystalline (14808-60-7), present in Calcium Carbonate filler is a suspected human carcinogen. Vinyl acetate (108-05-4), present in base emulsion is a confirmed animal carcinogen w/ unknown relevance to humans.
OSHA	NE
IARC	Silica, crystalline (14808-60-7), present in Calcium Carbonate filler identified as a human carcinogen. Vinyl acetate (108-05-4), present in base emulsion identified as a possible carcinogen.
NTP	Silica, crystalline (14808-60-7), present in Calcium Carbonate filler identified as a Known carcinogen.
DATA WITH POSSIBLE RELEVANCE TO HUMANS	Product may contain trace amounts of vinyl acetate, identified by IARC as a potential carcinogen. There is presently no evidence that it has caused cancer in humans. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 12 – ECOLOGICAL INFORMATION

AQUATIC TOXICITY	Ecological injuries are not known or expected under normal use.
-------------------------	---

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL	Dispose of material in accordance w/ Federal, State & Local regulations.
EPA WASTE CODE IF DISCARDED (40CFR Sec.261)	None.

SECTION 14 – TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION	Product not regulated by DOT.
-------------------------------------	-------------------------------

SECTION 15 – REGULATORY INFORMATION

CERCLA – SARA HAZARD CATEGORY	SARA 311 & 312: Immediate health hazard, Chronic health hazard.	U.S. STATE REGS	See Section 16.
SARA 313	None.	TSCA	All ingredients either on TSCA Inventory or exempt.

SECTION 16 – OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

NJ Right-to-Know: (Top 5 Ingredients): Vinyl Acrylic Emulsion (mixture), Water (7732-18-5), Soda Lime Borosilicate (Glass Bubbles) (65997-17-3), Propylene Glycol (57-55-6), Calcium Carbonate (1317-65-3). **Pennsylvania Right-to-Know (Non-Haz @ >3%):** Water (7732-18-5). **Ingredients Known to State of California to cause cancer, birth defects or reproductive harm:** Vinyl acetate (108-05-4), Silica, crystalline (14808-60-7). **Canadian WHMIS Class:** Not regulated. **HMIS Ratings:** Health: 1, Flammability: 0, Reactivity: 0, Personal Protection: X. **WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

LEGEND: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act

Reviewed By: <u>Larry G. Brandon</u>	<u>VP Technology & General Manager</u>	<u>February 3, 2010</u>
NAME	TITLE	DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.