



Technical Data Sheet

Interior/Exterior Floor Leveler Powder – Product No. 0370

Description

Floor Leveler is a premium powder formula to be mixed with water prior to use. Product designed for use over concrete or wood.

Key Features

- Fast-setting – sets hard in 30 minutes
- Excellent shelf-life when stored as directed
- Easy to use
- Leaves a smooth finish
- Will not shrink or crack

Uses

Use to level rough, uneven concrete or wood subfloors. Leaves a smooth finish for the installation of linoleum, vinyl, tile, wood or carpeted floors. Can be used to patch cracks & fill low spots in concrete or wood.

Directions:

1. Remove all dirt, dust or loose materials. Wood substrates must be securely fastened.
2. For average consistency, use 3 ½ parts powder to 1 part water & stir until a smooth, creamy blend has been reached.
3. Mix only enough material that will be applied in a 10 to 15 minute period.
4. One pound of mixed Floor Leveler will cover approximately one square foot @ 1/8 inch thickness.
5. Do not use in temperatures below 40F.
6. Pour compound onto surface, then spread & level using a steel trowel. Compound must be given a steel trowel finish when moisture starts to leave. This usually occurs within 10-15 minutes.
7. After application, do not add additional water or mixing liquid once troweling has begun.
8. May be sanded when thoroughly dry.

<u>Physical/Performance Property</u>	<u>Test Method</u>	<u>Typical Result</u>
<i>Base Raw Material</i>	<i>Known</i>	<i>Portland Cement & Calcium Sulfate Powder</i>
<i>Consistency/Appearance</i>	<i>Visual Observation</i>	<i>Approximately 30 minutes</i>
<i>Hard Set</i>	<i>Test Lab</i>	<i>2 Years Minimum (stored as directed)</i>
<i>Shelf Life</i>	<i>Test Lab</i>	<i>Store in a cool, dry place in the original, sealed container</i>
<i>Storage Conditions</i>	<i>Lab 50 C Oven – Accelerated</i>	<i>Non-toxic when used as directed.</i>
<i>Toxicity</i>	<i>Test Lab @ 72F</i>	
	<i>Supplier Data Sheets</i>	
<i>Mixing Ratio (average consistency)</i>	<i>Supplier Data Sheets</i>	<i>3.5 Parts Powder to 1 Part Water</i>
<i>Color</i>	<i>Visual Observation</i>	<i>Light Gray</i>
<i>VOC Content</i>	<i>Supplier Data Sheets</i>	<i>0% by weight</i>
<i>Approximate Coverage</i>	<i>Test Lab</i>	<i>One pound of mixed Leveler will cover approximately one square foot @ 1/8 inch thickness</i>

Clean Up

Clean tools with water before product hardens & clean skin with soap & water.

For Best Results

- Gloves & eye protection should be worn for optimum protection.
- Wet concrete or wooden substrates prior to application to retard suction & improve adhesion.
- Smooth concrete surfaces should first be acid-etched & thoroughly flushed with clean water.
- Chalky concrete surfaces should be thoroughly cleaned, rinsed & dried.
- Always keep container tightly sealed & stored in a cool, dry place.

Environmental/Safety/Transportation

Color

Light Gray

Packaging

HDPE Tub

Limitations

- Use of clean water recommended.
- Store in cool dry place.
- Do not use on below ground surfaces which may contain moisture.
- Not recommended for use in high traffic areas.

<u>Criteria</u>	<u>Evaluation Method</u>	<u>Status</u>
<i>CARB Compliance</i>	<i>Documents Review</i>	<i>Yes</i>
<i>Prop 65 Ingredients</i>	<i>Documents Review</i>	<i>Yes (see MSDS)</i>
<i>UN Proper Shipping Name</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>UN Hazard Class</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>UN ID Number</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>UN Packing Group</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>VOC Content</i>	<i>Calculated</i>	<i>0% by weight</i>

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. (See MSDS for additional information)

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If not satisfied when used as directed, product will be replaced without charge upon presentation of proof of purchase and used container. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

TDS Number: 0370TD

Date of Issue: January 20, 2010

SEE MSDS FOR ADDITIONAL DATA/INFORMATION