



# Technical Data Sheet

## Water Stop Cement (Hydraulic Cement) – Product No. 0380

### Description

Water Stop Cement is quick-setting hydraulic cement that expands as it hardens to form a water-tight seal that stops leaks & seals cracks in concrete & masonry walls.

### Directions:

Use according to container label instructions.  
NOTE: Patched area should be kept damp for several hours after application.

### Key Features

- Quick-setting
- Excellent shelf-life when stored as directed
- Easy to Use
- Expands as it hardens
- Suitable for below-grade applications
- VOC Compliant

### Uses

Seal cracks in concrete & masonry walls; suitable for below-grade retaining walls & basement walls.

<u>Physical/Performance Property</u>	<u>Test Method</u>	<u>Typical Result</u>
<i>Base Raw Material</i>	<i>Known</i>	<i>Portland Cement &amp; Calcium Aluminate Cement</i>
<i>Consistency/Appearance</i>	<i>Visual Observation</i>	<i>Powder</i>
<i>Initial Set</i>	<i>Test Lab</i>	<i>3 to 5 minutes</i>
<i>Hard Set</i>	<i>Test Lab</i>	<i>5 to 6 minutes</i>
<i>Shelf Life</i>	<i>Lab 50 C Oven – Accelerated</i>	<i>2 Years Minimum (stored as directed)</i>
<i>Storage Conditions</i>	<i>Test Lab</i>	<i>Store in a cool, dry place in the original, sealed container</i>
<i>Toxicity</i>	<i>Supplier Data Sheets</i>	<i>Non-toxic when used as directed.</i>
<i>Mixing Ratio (average consistency)</i>	<i>Supplier Data Sheets</i>	<i>4 Parts Powder to 1 Part Water</i>
<i>Solubility in Water</i>	<i>Test Lab</i>	<i>Insoluble after cure</i>
<i>Color</i>	<i>Visual Observation</i>	<i>Light Gray</i>
<i>VOC Content</i>	<i>Supplier Data Sheets</i>	<i>0% by weight</i>

## Clean Up

Clean tools with water before product hardens & clean skin with soap & water.

## For Best Results

- Gloves & eye protection should be worn for optimum protection.
- Patched area should be kept damp for several hours following application for best results.

## Environmental/Safety/Transportation

## Color

Light Gray

## Packaging

HDPE Tubs

## Limitations

- Use of clean water recommended.
- Store in cool dry place.

<u>Criteria</u>	<u>Evaluation Method</u>	<u>Status</u>
<i>CARB Compliance</i>	<i>Documents Review</i>	<i>Yes</i>
<i>Prop 65 Ingredients</i>	<i>Documents Review</i>	<i>Yes (See MSDS)</i>
<i>UN Proper Shipping Name</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>UN Hazard Class</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>UN ID Number</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>UN Packing Group</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>VOC Content</i>	<i>Calculated</i>	<i>0% by weight</i>

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. (See MSDS for additional information)**

## LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If not satisfied when used as directed, product will be replaced without charge upon presentation of proof of purchase and used container. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

TDS Number: 0380TD

Date of Issue: January 20, 2010

SEE MSDS FOR ADDITIONAL DATA/INFORMATION