



Technical Data Sheet

Caulk Remover – Liquid - 0583

Description

Red Devil Caulk Remover is a liquid product designed for indoor or outdoor use. The product works on all types of caulk, softening for easy removal.

Key Features

- Indoor/Outdoor Use
- Works on All Types of Caulk
- Softens Caulk for Easy Removal
- Liquid Formulation for Easy Application
- Mild Odor
- Essentially Neutral pH

Uses

Use to soften & aid in removal of all types of caulk, interior & exterior.

Surface Preparation

Apply product directly to surface of caulk to be removed.

Directions

1. Store Caulk Remover above 32F prior to use. Apply when surface & air temperature between 40F & 90F.
2. Apply 1/8 inch coat to cured caulk to be removed & allow to soften caulk (@ least 2 hours). Some caulks such as Acrylics, may take up to 7 hours to soften.
3. When caulk has softened considerably, use a putty knife to remove as much as possible. Apply a second application & repeat procedure as required, especially for painted caulk.
4. Carefully remove remaining film with a razor blade, taking care not to damage surface.
5. Clean & dry substrate prior to application of new caulk.
6. Keep Caulk Remover sealed & stored in a cool, dry area when not in use.

<u>Physical/Performance Property</u>	<u>Test Method</u>	<u>Typical Result</u>
Weight Per Gallon	Gardner Cup	8.50
Specific Gravity	Test Lab	1.02
Boiling Point	Test Lab	> 100C
Evaporation Rate	Known	<0.01
Percent Volatile (Weight)	Computrac Analyzer	94% to 97%
Consistency/Appearance	Visual Observation	Cream-like fluid
Color	Visual Observation	White/off-white
pH (initial)	pH Meter	7.0
Odor	Subjective	Ester odor
Viscosity	Brookfield Viscometer	60,000 to 110,000 cps
Flash Point	Test Lab	> 225F
Shelf Life	Test Lab	Minimum 1 Year @ 77F
Storage Conditions	Test Lab	Cool & Dry/above 32F
Application Temperature	Test Lab/Field Evaluation	40F to 90F
EPCRA Hazard Class	Documents Review	Fire: No Pressure: No Reactivity: No Acute: Yes Chronic: No

Clean Up

Soap & water

For Best Results

- To avoid possible damage, test in a small, inconspicuous spot. (Some fiberglass, other plastic or refinished surfaces may also be affected.)
- Wipe Caulk Remover off paint (Interior or Exterior) & wallpaper immediately.

Color

White to Off-White

Packaging

8 oz HDPE Squeeze Bottle

Limitations

- Protect from freezing.
- Do not use on low-end ABS plastic tubs & showers or on old-fashioned plastic wall tiles.
- Painted caulk may require two applications.

Environmental, Safety & Transportation Information

<u>Criteria</u>	<u>Evaluation Method</u>	<u>Status</u>
<i>CARB Compliance</i>	<i>Documents Review</i>	<i>YES</i>
<i>Prop 65 Ingredients</i>	<i>Documents Review</i>	<i>NONE</i>
<i>DOT Proper Shipping Name</i>	<i>Review of Regs</i>	<i>Not Regulated by DOT</i>
<i>DOT Hazard</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>DOT UN/NA Number</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>Packing Group</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>VOC Content</i>	<i>Calculated</i>	<i>< 4%/wt; < 214 grams/Liter</i>

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. Eye irritant. May irritate skin with prolonged or repeated contact. Wear gloves for removal of remover & caulk residue. (See MSDS for additional information)

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material fails to perform as represented, it will be replaced without charge upon presentation of proof of purchase and used application bottle. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

TDS Number: 0583TD

Date of Issue: September 8, 2008

SEE MSDS FOR ADDITIONAL DATA/INFORMATION