



# Safety Data Sheet

Issue Date: 28-Aug-2013

Revision Date: 10-Feb-2025

Version 2

## 1. IDENTIFICATION

### Product identifier

**Product Name** Onetime Lightweight Spackling

### Other means of identification

**SDS #** RD-0038OPP-R2

**Product Code** 540 Series

### Recommended use of the chemical and restrictions on use

**Recommended Use** For patching & filling small holes in drywall w/ no need to prime before painting.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Red Devil, Inc.  
4175 Webb Street  
Pryor, Oklahoma 74361  
www.reddevil.com

### Emergency telephone number

**Company Phone Number** 918-825-5744  
Fax: 918-825-5761  
**Emergency Telephone** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** White paste

**Physical state** Paste

**Odor** Mild Acrylic/slight ammoniacal

### Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Soda lime borosilicate glass	65997-17-3	<20
Propylene Glycol	57-55-6	1-5
Amorphous silica (glass)	7631-86-9	<1

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

## 4. FIRST AID MEASURES

### Description of first aid measures

<b>General Advice</b>	Provide this SDS to medical personnel for treatment.
<b>Eye Contact</b>	Immediately flush with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention.
<b>Skin Contact</b>	Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.
<b>Inhalation</b>	Remove to fresh air. If breathing is difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.
<b>Ingestion</b>	Do not induce vomiting unless directed by medical personnel. If vomiting occurs, lean patient forward to maintain an open airway & prevent aspiration. Get immediate medical attention.

### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and sneezing.
-----------------	--

### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Medical Conditions Aggravated by Exposure: Asthma & asthma-like conditions may worsen from prolonged or repeated exposure to dust, should sanding be performed.
---------------------------	---

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray (fog). Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** Not determined.

### Specific Hazards Arising from the Chemical

Product is not flammable.

**Hazardous combustion products** Carbon oxides. Nitrogen oxides (NO<sub>x</sub>).

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal Precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet.
<b>Other Information</b>	Small Spills: 1 drum or less – Level D Equipment (gloves, chemical resistant apron, boots & eye protection). Large Spills: Rubber gloves, rubber boots, face shield & Tyvek suit as a minimum. Minimum

level of PPE for releases in which the oxygen level is < 19.5% or is unknown, should be Level B: triple gloves (rubber gloves & nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing & boots, hard hat & self-contained breathing apparatus.

**For Emergency Responders** Restrict access to spill area.

### **Environmental precautions**

**Environmental precautions** Minimize use of water to prevent environmental contamination. Prevent spill or rinse from contaminating storm drains, sewers, soil or groundwater. Do not allow discharge containing this material to enter streams, ponds, estuaries, oceans or other waters unless in accordance w/ requirements of National Pollutant Discharge Elimination System (NPDES) permit & permitting authority has been notified in writing prior to discharge. Do not allow discharge containing this material to enter sewer systems w/o previously notifying local sewage treatment plant authority. For information, contact State Water Board or EPA Regional Office  
Other: U.S. regulations may require reporting of spills of this material reaching surface waters if sheen is formed. See Section 12 for additional Ecological Information.

### **Methods and material for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

**Methods for Clean-Up** Sweep up absorbed material and shovel into suitable containers for disposal. Wash area with soap and water. For waste disposal, see section 13 of the SDS.

## **7. HANDLING AND STORAGE**

### **Precautions for safe handling**

**Advice on Safe Handling** Keep out of reach of children & pets. Do not take internally. Do not breathe vapors or dust. If dry sanding use NIOSH-approved dust mask. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing. Do not eat or drink while handling this material. In event of spill – see Section 6.

### **Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Stable under normal conditions of handling, use & storage. Store containers in a cool, dry location, away from direct sunlight & high temperatures. Protect from freezing. Store away from incompatible materials (caustics & oxidizers). Close container after each use & keep tightly closed when not in use. To maximize shelf life, store @ temperatures below 26C (80F).

**Incompatible Materials** Oxidizing agents, Caustics.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines** Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Soda lime borosilicate glass 65997-17-3	TWA: 1 fiber/cm <sup>3</sup> respirable fibers: length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400- 450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m <sup>3</sup> inhalable fraction	-	-

Amorphous silica (glass) 7631-86-9	-	TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m <sup>3</sup> <1% Crystalline silica TWA: 20 mppcf : (80)/(%) SiO <sub>2</sub> mg/m <sup>3</sup> TWA	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>
---------------------------------------	---	--	--

**Other Information**

If product is sanded, appropriate respirator should be worn to avoid breathing dust. Pre-existing respiratory disorders may be aggravated by exposure. If sanded, this material may generate silica dust. Inhaled silica has been classified by NTP as a human carcinogen (see section 11 table).

**Appropriate engineering controls****Engineering Controls**

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Provide appropriate local exhaust ventilation if material is to be sanded.

**Individual protection measures, such as personal protective equipment****Eye/Face Protection**

Use approved safety goggles or safety glasses. If necessary, refer to appropriate regulations and standards. Refer to 29 CFR 1910.133 for eye and face protection regulations.

**Skin and Body Protection**

Skin: Wear chemical resistant rubber gloves for repeated or prolonged use.  
Body: Not required w/ normal use. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

**Respiratory Protection**

Avoid breathing of dust. Avoid breathing of vapors, mists or spray. If concentrations exceed exposure limits specified, use a NIOSH-approved supplied air respirator. If protection factor exceeded, use self contained breathing apparatus (SCBA). A respiratory protection program that exceeds OSHA 1910.134 & ANSI Z88.2 requirements should be followed when conditions warrant respirator use. If dry sanding preferred, use approved NIOSH/OSHA respirator.

**General Hygiene Considerations** Wash hands w/ soap & water before breaks & @ end of workday. Remove & wash contaminated clothing prior to re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	Paste	<b>Odor</b>	Mild Acrylic/slight ammoniacal
<b>Appearance</b>	White paste	<b>Odor Threshold</b>	Not determined
<b>Color</b>	White		
<b><u>Property</u></b>	<b><u>Note: The information below is not intended for use in preparing product specifications</u></b>	<b><u>Remarks • Method</u></b>	
pH	7.0-10.0		
Melting point / freezing point	0 °C / ~32 °F		
Boiling point / boiling range	100 °C / ~212 °F		
Flash point	> 93.33 °C / > 200 °F	Seta Closed Cup	
Evaporation Rate	Not determined		
Flammability (Solid, Gas)	Not determined		
Flammability Limit in Air			
Upper flammability or explosive limits	Unknown		

<b>Lower flammability or explosive limits</b>	Unknown	
<b>Vapor Pressure</b>	Not established	
<b>Vapor Density</b>	Heavier than air	
<b>Relative Density</b>	~0.40-0.60	API Gravity @ 60°F D1298
<b>Water Solubility</b>	Soluble in water	
<b>Solubility in other solvents</b>	Not determined	
<b>Partition Coefficient</b>	Not determined	
<b>Autoignition temperature</b>	Not determined	
<b>Decomposition temperature</b>	Not determined	
<b>Kinematic viscosity</b>	Not determined	
<b>Dynamic Viscosity</b>	Not determined	
<b>Explosive Properties</b>	Not determined	
<b>Oxidizing Properties</b>	Not determined	

**Other information**

**VOC Content** < 10 g/L

## 10. STABILITY AND REACTIVITY

**Reactivity**

Not reactive under normal conditions.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Conditions to Avoid**

Incompatible Materials. Excessive heat or cold.

**Incompatible materials**

Oxidizing agents, Caustics.

**Hazardous decomposition products**

Carbon oxides. Nitrogen oxides (NOx).

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

**Eye Contact** Eye contact may result in tearing, redness & pain.

**Skin Contact** Prolonged and frequent contact may cause redness and irritation. Repeated skin contact may cause dermatitis.

**Inhalation** Overexposure to vapors during application & curing may mildly irritate respiratory tract & result in coughing & sneezing.

**Ingestion** May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propylene Glycol 57-55-6	= 20 g/kg ( Rat )	= 20800 mg/kg ( Rabbit )	-
Amorphous silica (glass) 7631-86-9	= 7900 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L ( Rat ) 1 h

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** Please see section 4 of this SDS for symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** Not known to be human skin or respiratory sensitizers.

**Carcinogenicity** Silica is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Amorphous silica (glass) 7631-86-9		Group 3	Known	X

**Legend**

*IARC (International Agency for Research on Cancer)*

*Group 3 IARC components are "not classifiable as human carcinogens"*

*NTP (National Toxicology Program)*

*Known - Known Carcinogen*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*X - Present*

**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document .

**Oral LD50** 1,637,254.90 mg/kg

**Dermal LD50** 1,702,745.10 mg/kg

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

PRACTICES SHOULD BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

not tested for aquatic or animal toxicity. Release of product to terrestrial, atmospheric & aquatic environments should be avoided.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Propylene Glycol 57-55-6	19000: 96 h Pseudokirchneriella subcapitata mg/L EC50	51400: 96 h Pimephales promelas mg/L LC50 static 710: 96 h Pimephales promelas mg/L LC50 41 - 47: 96 h Oncorhynchus mykiss mL/L LC50 static 51600: 96 h Oncorhynchus mykiss mg/L LC50 static	1000: 48 h Daphnia magna mg/L EC50 Static 10000: 24 h Daphnia magna mg/L EC50
Amorphous silica (glass) 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50

**Persistence/Degradability**

Not tested for persistence & biodegradability.

**Bioaccumulation**

This material is not expected to significantly bioaccumulate.

**Mobility**

Not tested for mobility in soil

**Other Adverse Effects**

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

### 13. DISPOSAL CONSIDERATIONS

**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**US EPA Waste Number**

Not applicable

### 14. TRANSPORT INFORMATION

**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT**

Not regulated

**IATA**

Not regulated

**IMDG**

Not regulated

### 15. REGULATORY INFORMATION

**International Inventories**

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Soda lime borosilicate glass	X	ACTIVE	X	X	X	X	X	X	X
Propylene Glycol	X	ACTIVE	X	X	X	X	X	X	X
Amorphous silica (glass)	X	ACTIVE	X	X	X	X	X	X	X

**Legend:**

*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*

*DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*

*EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

*ENCS - Japan Existing and New Chemical Substances*

*IECSC - China Inventory of Existing Chemical Substances*

*KECL - Korean Existing and Evaluated Chemical Substances*

*PICCS - Philippines Inventory of Chemicals and Chemical Substances*

*AICS - Australian Inventory of Chemical Substances*

**US Federal Regulations****CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**US State Regulations****California Proposition 65**

Not determined

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Propylene Glycol 57-55-6	X		X
Amorphous silica (glass) 7631-86-9		X	X

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	1	0	0	Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical hazards</b>	<b>Personal Protection</b>
	1	0	0	X

Issue Date: 28-Aug-2013  
Revision Date: 10-Feb-2025  
Revision Note: Regulatory review SDS sections updated 15

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**