



# Red Devil

# Kitchen & Bath

with **STAIN BLOCK™**

Red Devil's Kitchen & Bath Stain Block™ is specially formulated to resist the toughest stains, including red wine/grape juice, coffee, mustard, ketchup, soy sauce, etc. This advanced sealant can be painted with latex and oil-based paints, and cleans up with water. The cured sealant is mold and mildew resistant.

## FEATURES:

- Resists the Toughest Stains
- Water Clean Up
- Excellent Adhesion
- High Gloss Finish
- Paintable
- Durable Watertight Seal
- Easy Application
- Won't Shrink, Crack or Peel
- Low VOC

## USES:

Formulated for use on Sinks, Tubs, Showers, Toilets, Loose Tiles, Backsplashes, Countertops, Vanities, Fixtures & More!

## ADHERES TO:

Painted & Unpainted Wood, Tile, Plaster, Drywall, Brick, Glass, Metal, Aluminum, Concrete, Masonry & More.



INTERIOR &  
EXTERIOR USE



SUPERIOR  
PAINTABILITY



MULTI-SURFACE  
ADHESION



WATER  
CLEAN-UP



MADE  
IN THE **USA**



Meets or Exceeds Federal Specifications:

- ASTM C920 Requirements



[www.reddevil.com](http://www.reddevil.com)

Customer Service: 1-800-423-3845

Red Devil, Inc.  
4175 Webb Street  
Pryor, OK 74361

# TECHNICAL DATA SHEET

## KITCHEN & BATH STAIN BLOCK™

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0750	White	10.1 fl. oz (300 mL) Cartridge	0-75339-01135-5	12
075022	Biscuit	10.1 fl. oz (300 mL) Cartridge	0-75339-01132-4	12
0755	White	5.5 fl. oz (163 mL) Cartridge	0-75339-01138-6	12
075522	Biscuit	5.5 fl. oz (163 mL) Cartridge	0-75339-01131-7	12
0757	Clear	10.1 fl. oz (300 mL) Cartridge	0-75339-01133-1	12
0765	Clear	5.5 fl. oz (163 mL) Cartridge	0-75339-01134-8	12

### PHYSICAL & CHEMICAL PROPERTIES:

**Weight Per Gallon:** 9 +/-11

**Specific Gravity:** Approx. 1 to 1.1

**Total Non-Volatile % Solids (Weight):** > 65% +/- 2.5

**Viscosity:** Approx. 7 Seconds +/- 2

**Consistency/Appearance:** Smooth, Colored Paste

**Flash Point:** > 200°F - Non-Flame/Waterborne

**Odor:** Mild Acrylic

**Base Polymer:** Proprietary Polymer

**Filler/Pigment:** TiO2 Slurry

**pH (initial):** 7 to 9

**Freeze/Thaw Stability:** Pass 5 Cycles (ASTM C731)

**Shelf Life:** Minimum 1 Year @ 72°F

**Tack Free Time:** < 72 Hours @ 72°F

**Full Cure:** Approx. 3 days (3/16 bead)

**Storage Conditions:** Original Container: 40°F to 90°F (5°C to 32°C)

**Application Temperature:** 40°F to 90°F (5°C to 32°C)

**Paintability:** 24 to 72 hours (cool/humid conditions will extend drying time)

**Odor:** Excellent @ 50°F to 90°F

**Percent Elongation:** 450% minimum

**Service Temperature:** -25°F to 180°F (-32°C to 82°C)

**Clean-Up:** Water - before cure

### APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife or Damp Cloth. Protect from water until cured (72 hrs). Clean hands, skin, and tools immediately after use with warm soapy water. 0758 - 5 Gallon (For use with Bulk Type Caulk Gun).

### FOR BEST RESULTS:

- Store at temperatures above freezing.
- Joint width should not exceed ½". If joint depth exceeds ¼", use a backer rod.
- Apply in temperatures above 40°F

### CLEAN-UP:

Clean tools immediately w/ water. Wash skin with warm water & soap.

### LIMITATIONS:

- Not recommended for use on automotives, fish tanks/ aquariums, and mirrors.
- Not recommended for full-time water immersion applications.
- Protect from water until cured (72 Hours) - Cooler temperatures & higher humidity will extend cure time.
- Not recommended for below grade applications

### LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See MSDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazzard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5% by weight, < 25 g/l

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)**

**⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide and Carbon Black Exposure - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**