



Red Devil

ZIP-A-WAY™

ZIP-A-WAY™ Removable Sealant is a specially formulated weatherstripping temporary caulk that forms a tight seal around windows, doors, air conditioners, vents, fans, and electrical outlets. It is easy to apply and provides a watertight and weatherproof seal that prevents drafts and moisture. This seal and peel caulk for windows can be peeled away when no longer needed and will not mar or destroy most painted surfaces. Use to seal out drafts and save energy, especially in the winter months.

FEATURES:

- Applies/Dries Clear
- Interior/Exterior Use
- Paintable
- Remains Flexible
- Mildew Resistant
- Suitable for Below Grade Applications
- Applies to Dry or Damp Surfaces
- Removable Anytime After 5 to 7 Days in Most Conditions
(Formulated for removable after 6 months)

USES:

Formulated for use on Window & Door Frames, Vents, Fans, Air Conditioners, Electrical Outlets & More.

ADHERES TO:

Painted Wood, Metal, Glass, Aluminum, Vinyl & More.



INTERIOR &
EXTERIOR USE



PAINTABLE



MOLD & MILDEW
RESISTANT
WHEN CURED



EASY REMOVAL
WITHIN 3-6
MONTHS



MADE
IN THE **USA**



Meets or Exceeds Federal Specifications:

- ASTM 230, Class A
- ASTM C920, Class 25



www.reddevil.com

Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

ZIP-A-WAY™

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0606	White	10.1 fl. oz (300 mL) Cartridge	0-75339-00606-1	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 7.25 +/- 0.25

Specific Gravity: Approx. 0.87

Total Non-Volatile % Solids (Weight): 60% +/- 1.5

Viscosity: 700M cps +/-300M

Consistency/Appearance: Clear, Viscous Paste

Flash Point: > 100°F; Flammable

Odor: Solvent

Base Polymer: Kraton Thermoplastic Rubber Blend

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Expect 1 Year Unopened @ 72°F

Slump: < 0.15

Flexibility: Pass 1 in Mandrel @ 32°F

Tack Free Time: < 30 minutes (normal conditions)

Storage Conditions: 40°F to 90°F (5°C to 32°C)

Application Temperature: 10°F to 100°F (For applications <40°F cartridge should be stored @ RT (72°F) prior to use)

Service Temperature: -25°F to 125°F (-32°C to 52°C)

Paintability: Excellent (24 hours w/ latex, 72 hours w/ oil based)

Shrinkage: 25 to 45% (Substrate Porosity)

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Consumer Commodity
DOT Hazard	Adhesive Flammable Liquid
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 37%/wt, < 400 g/L

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife or Damp Cloth. Remove excess with a damp cloth before surface skins over. Full clarity reached in 1 to 2 weeks.

FOR BEST RESULTS:

- Apply only with excellent ventilation (See MSDS).
- Store cartridge @ room temperature (72°F to 77°F) prior to use if application temperature is below 40°F.
- Do not store or use around heat, open flame, etc. - Product flammable
- Apply to dry surfaces whenever possible although product will adhere to damp substrates as well.
- Remove temporary sealant after 3 to 6 months.

CLEAN-UP:

Mineral Spirits or Toluene before cure (See solvent label for directions & cautions)

NOTE: Some Orange-Based Cleaners also work. See label directions/cautions.

LIMITATIONS:

- Not for use in areas of complete submersion.
- Not FDA or USDA approved.
- Not recommended for pool or hot tub applications.
- Not recommended for adhering mirrors.
- Do not apply to recently painted surfaces.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide and Carbon Black Exposure - www.P65Warnings.ca.gov