



Fireplace & Stove

Fireplane & Stove Repair Silicate Sealant is a non-flammable, silicate-based compound that sets rock-hard when fired. The black textured paste adheres to fire brick, cinder block, metal, and mortar. It cures with a warm fire and provides a durable, long-lasting seal that withstands temperatures up to 2700°F.

FEATURES:

- Prevents Drafts
- Non-Flammable
- Interior Use Only
- Withstands Temperatures Up to 2700°F
- Ideal For Patching Fire Bricks and Sealing Wood-burning Stoves
- Water Clean Up

USES:

Formulated for use on Sealing Openings, Cracks, Joints, and Seams Encountered in Fireboxes, Chimneys, Furnaces, Stoves, Flue Pipes, Multiple Other Refractory Applications & More.

ADHERES TO:

Fire Brick, Cinder Block, Concrete, Metal, Mortar & More.



INTERIOR
USE ONLY



NON
FLAMMABLE



VOC
COMPLIANT



WATER
CLEAN-UP



Meets or Exceeds Federal Specifications:

- ASTM C199
- ASTM E136



www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

FIREPLACE & STOVE

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0466	Black	10.1 fl. oz (300 mL) Cartridge	0-75339-00466-1	12

PHYSICAL & CHEMICAL PROPERTIES:

Base Polymer: Silicate Mortar

Cure Type: Water-Based

Weight Per Gallon: 14.4 lbs./gal

Consistency/Appearance (Uncured): Glossy Paste

Physical Cured State: Solid Mortar

Odor: None

Freeze/Thaw Stability: Passes 3 Cycles

Shelf Life: Minimum 1 Year Unopened @ 77°F

Tack Free Time: 10 Minutes at 75°F

Full Cure: 24 Hours Until Air-Hardened

Service Temperature: -30°F to 2700°F (-34°C to 1482+°C)

Flame Spread: 0

Smoke Development: 0

Clean-Up: Solvent (Before Cure)

Crack Resistance: Excellent

APPLICATION:

Remove old caulking/sealant. Clean, dry & remove any loose material, from the surface, that may interfere with adhesion, including dirt, debris, oil, and residue. Cut the nozzle tip to the desired bead size at a 45° angle. Load the cartridge into a standard-sized caulking gun and apply sealant to the gap or joint. Using steady pressure, force material into cavity. Sealant suitable for interior applications only. When desired depth of sealant has been achieved smooth service with a Red Devil Putty Knife. If sealant pulls back from surface, clean surface with a damp rag or sponge and re-apply. Important - Do not allow material to get wet prior to heat cure. Begin firing at low temperature. Do not start with a hot fire. Gradually increase the temperature to allow cement to harden into a solid durable body, free from pores.

FOR BEST RESULTS:

- Surface should be clean & free of contaminants.
- For interior surfaces only.
- Store at temperatures above freezing.
- Provide low/warm fire for initial curing.

LIMITATIONS:

- For interior use only
- Protect from freezing

CLEAN-UP:

Excess product should be cleaned off tools and nonprous surfaces while uncured with dry cloth or paper towels. Solvents such as acetone or mineral spirits may need to be used with excessive amounts. Wash skin with warm water & mild soap.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Reproductive Harm Risk from Ethylene Glycol & Cancer Risk From Titanium Dioxide Exposure - www.P65Warnings.ca.gov