



Gutter & Foundation

Gutter & Foundation Butyl Rubber Sealant is a high-quality, long-lasting formula that is ideal for outdoor jobs requiring a durable, watertight seal. It can be used around concrete foundations and expansion joints, on gutters and in below grade areas such as basements.

FEATURES:

- Provides a Water-Tight Seal
- For Basements and Below Grade Areas
- Paintable
- Remains Flexible
- Interior/Exterior Use
- Mold & Mildew Resistant When Cured

USES:

Formulated for use on Gutters, Shingles, Chimney and Roof Flashings, Storm Doors and Windows, Below Grade Areas, Downspouts, Skylights & More.

ADHERES TO:

Glass, Masonry, Wood, Stone, Concrete, Fiberglass, Aluminum, Brick, Metal, Cinder Block & More.



INTERIOR &
EXTERIOR USE



SUPERIOR
PAINTABILITY



MOLD & MILDEW
RESISTANT
WHEN CURED



FORMS A
WATER RESISTANT
SEAL



Meets or Exceeds Federal Specifications:
• TT-S-001657



www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

GUTTER & FOUNDATION SEALANT

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0697	White	10.1 fl. oz (300 mL) Cartridge	0-75339-00697-9	12
0697AG	Gray	10.1 fl. oz (300 mL) Cartridge	0-75339-00695-2	12

PHYSICAL & CHEMICAL PROPERTIES:

Specific Gravity: 1.20 - 1.25

Viscosity: 450,000 - 550,000 cps Million cps

Appearance/Consistency: Viscous Paste

Tensile Strength: 125 psi

Odor: Solvent

Boeing Flow: Nil

Filler/Pigment: Calcium Carbonate, TiO₂

Shore A Hardness: 30 - 35

Bubble Formation: No Bubbles Formed

Tenacity: Pass

Vehicle Migration: Pass

Adhesion: Excellent

Shelf Life: Expect 1 Year @ 72°F

Service Temperature: -20°F to 180°F (-29°C to 82°C)

Full Cure: 7 to 10 Days

Non-Staining: Non-Staining When Used As Recommended

Water Resistance: No voids, cracks, separation

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Hydrocarbons, Liquid, n.o.s.
DOT Hazard	Class 3
DOT UN/NA Number	UN 3295
Packing Group	PG III
VOC Content	< 106 g/L

APPLICATION:

Remove old caulking/sealant. Clean, dry & remove any loose material, from the surface, that may interfere with adhesion, including dirt, debris, oil, and residue. Cut the nozzle tip to the desired bead size at a 45° angle. Load the cartridge into a standard-sized caulking gun and apply sealant to the gap or joint. Smooth sealant using a damp cloth or finishing tool for a professional finish. Remove excess sealant with a damp cloth before it skins over. Allow the sealant to dry before painting.

FOR BEST RESULTS:

- Apply only in well ventilated areas.
- Do not store or use around heat, open flame.
- Store product at or below 80°F.
- Do not use for joints subject to heavy abrasion or wear.
- Prime bare surfaces before caulking.

LIMITATIONS:

- Not for use in areas for complete submersion (pool, hot tub, aquarium, marine applications).
- Not recommended for adhering mirrors.
- Not recommended for use in window glazing applications.

CLEAN-UP:

Uses mineral spirits before cure.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Reproductive Harm Risk from Ethylene Glycol & Cancer Risk From Titanium Dioxide Exposure - www.P65Warnings.ca.gov