



Red Devil



Window & Door Caulk

A premium siliconized acrylic sealant formulated to provide an extra-tight seal around windows, doors & other areas of the home.

USES:

- Window and Door Frames
- Siding
- Trim
- Baseboards
- Crown Molding
- Corner Joints
- Ceiling and Wall Joints

ADHERES TO:

- Painted/Unpainted Wood
- Drywall
- Plaster

FEATURES:

- Interior/Exterior
- Multi-Purpose
- Paintable
- Excellent Adhesion
- Water clean up
- Meets or exceeds ASTM C834-05
- Easy to Use
- VOC Compliant



EXCELLENT
ADHESION



EASY WATER
CLEAN-UP



PAINTABLE



INTERIOR /
EXTERIOR



MULTI-SURFACE
APPLICATION



www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

HOUSE & HOME RESTORE™ WINDOW & DOOR CAULK

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0848	White	5.0 fl oz. Squeeze Tube	0-75339-08480-9	5

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 13.25 +/- 0.5 lbs.

Extrusion Viscosity: 9+/- 2 Seconds

Total Non Volatile % Solids (Weight): 79.5% +/- 2.5

Coverage: 25 Linear ft at 3/16" Bead

pH: 7 to 9

Odor: Mild

Stain Index: 0

Flash Point: > 200°F (94°C)

Freeze/Thaw Stability: Passes 5 Cycles

Shelf Life: 12 Months

Slump: < 0.05

Tack Free Time: 30 Minutes

Paint Over Time: Latex: 2-6 Hours / Oil-based: 24 Hours

Full Cure: 72 Hours

Storage Conditions: 40°F to 90°F

Application Temperature: 40°F to 90°F

Service Temperature: -20°F to 180°F

Elongation at Break: 400% +/- 100%

Tensile Strength: 10psi +/- 3 psi

Shrinkage: < 30%

25% Extension Recovery: 98%

Clean-Up: Water

APPLICATION:

Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax & old adhesive.

1. Remove tip & trim nozzle to desired bead size.
2. Apply using steady, even pressure to completely bridge joints.
3. Smooth caulk using Red Devil Caulk Smoother or a damp cloth for a neat appearance. Wipe away excess with a damp cloth before surface skins over.
4. May be painted over in 2 to 6 hrs depending on climatic conditions. Larger beads, cooler temperatures &/or higher humidity will slow cure time.
5. Protect from water until cured (72 hrs.).

FOR BEST RESULTS:

- Surface should be clean & free of contaminants.
- Prime bare surfaces before caulking.
- Apply caulk in temperatures between 40F (& rising) & 90F.
- Protect from exposure to water/rain for 72 hrs.
- Do not use for joints subject to heavy abrasion or wear.
- Do not attempt to thin caulk.
- Apply enough caulk for the job & do not remove too much during tooling for the caulk to do it's job.

LIMITATIONS:

- Do not apply when rain or freezing temperatures are expected
- Protect from rain & exposure to water for 72 hours
- Not recommended for marine applications, on automobiles or aquariums
- Larger beads, cooler temperatures & higher humidity will slow down cure

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes
DOT Proper Shipping Name	Not Regulated
DOT Hazzard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5%/wt, < 25g/L

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Cancer Risk and Reproductive Harm From Calcium Carbonate and Titanium Dioxide Exposure - www.P65Warnings.ca.gov