



Red Devil

Kitchen & Bath

Low Odor 100% Silicone Sealant

Kitchen & Bath Low Odor Silicone Sealant is a premium quality 100% silicone sealant formulated for low odor. Provides long-lasting flexibility, excellent adhesion and creates a protective barrier against moisture and mildew. Kitchen and bath applications. Its watertight seal cures to an ultra-smooth, satin finish.

FEATURES:

- Provides a Durable, Permanent Flexibility, Watertight Seal
- Non-Corrosive, Will Not Crack, Shrink or Peel
- Excellent Adhesion to Many Surfaces
- USDA Recognized
- Mold & Mildew Resistant When Cured
- Non-Paintable

USES:

Formulated for Sinks, Showers, Tubs, Backsplashes, Vanities, Countertops, Pipes, Ceramic, Porcelain, Fiberglass, Fixtures, Glass, Brick, Stone, Masonry, and More.

ADHERES TO:

Ceramic Tile, Glass, Porcelain, Marble, Vinyl, Plastic, Fiberglass & More.



UL LISTED



MULTI-SURFACE
ADHESION



MOLD & MILDEW
RESISTANT
WHEN CURED



FORMS A
WATER-
RESISTANT SEAL



Meets or Exceeds Federal Specifications:

- TT-S-00230C Class A
- ASTM C920, Class 25



www.reddevil.com

Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

KITCHEN & BATH LOW ODOR SILICONE SEALANT

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0836	White	9.0 fl. oz (266 mL) Cartridge	0-75339-00836-2	12
0883	White	2.8 fl. oz (83 mL) Cartridge	0-75339-08830-2	12
0885	Clear	2.8 fl. oz (83 mL) Cartridge	0-75339-08850-0	12
0887	Clear	9.0 fl. oz (266 mL) Cartridge	0-75339-08870-8	12
083620	Almond	9.0 fl. oz (266 mL) Cartridge	0-75339-08362-8	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 8.50 +/- 0.50

Specific Gravity: 1.0 to 1.25

Total Non-Volatile % Solids (Weight): > 90%

Extrudability/Application: 25 seconds +/- 10

Consistency/Appearance: Smooth, Visous Paste

Odor: Low

Base Polymer: Siloxane blend

Filler/Pigment: Fumed Silica

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Minimum 1 Year @ 72°F

Tack Free Time: < 1 Hour @ 72°F

Artificial Weathering: No change @ 10,000 hrs. QUV

Low Temperature Flexibility: Pass

Tack Free Time: 30 minutes

Cure Time: 24 hrs.

Shore A Hardness: 23 +/-3

Storage Conditions: Cool, Dry Place

Application Temperature: 10°F to 100°F (5°C to 32°C)

Clean-Up: -60°F to 400°F

Paintability: Non Paintable

Elongation: 350%

Paintability: +/-25%

Service Temperature: -60°F to 400°F (-51°C to 204°C)

Mildew Resistance: Excellent

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife or Damp Cloth. Remove excess with a damp cloth before surface skins over. Full clarity reached in 1 to 2 weeks.

FOR BEST RESULTS:

- Sealant is not paintable. Paint before applying.
- Apply sealant in a continuous operation
- The cure rate is dependent upon temperature and atmospheric moisture. As temperature decreases, the cure rate slows down (and vice versa)

CLEAN-UP:

Dry Paper Towel/Rag or Mineral Spirits before cure. Wash skin with mild soap and water.

LIMITATIONS:

- Sealant NOT PAINTABLE
- Sealant does not adhere well to Teflon coated materials, Polyethylene, Polypropylene or Methylmethacrylate (Plexiglas®)
- Must evaluate product and make determination as to fitness of use in your particular application.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazzard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 3% by weight, < 40 g/L

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS.
KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide and Carbon Black Exposure - www.P65Warnings.ca.gov