



Red Devil

LIFETIME® Windows • Doors • Trim

LIFETIME® PRO Siliconized Acrylic Latex Sealant is a high performance, multi-purpose sealant formulated to last as long as you own your home. This unique formulation provides the maximum level of adhesion to a variety of substrates indoors or outdoors. Product is paintable and includes HomeShield Antimicrobial Protection

FEATURES:

- Mildew Resistant When Cured
- Easy Application
- Excellent Adhesion
- Maximum Durability
- Permanently Flexible
- Paintable
- VOC Compliant
- Water Clean up
- Contains HomeShield Antimicrobial Protection
- Interior/Exterior
- Spec230 Class A and ASTM C920 Performance

USES:

Formulated for use on Window & Door Frames, Siding, Trim, Baseboards, Ducts, Countertops, Sinks, Bathtubs, and Vents.

ADHERES TO:

Painted & Unpainted Wood, Plaster, Drywall, Brick, Glass, Metal, Aluminum, Masonry & More.



INTERIOR &
EXTERIOR USE



MULTI-SURFACE
ADHESION



ASTM C920
Performance



WATER
CLEAN-UP



Meets or Exceeds Federal Specifications:

- ASTM 230, Class A
- ASTM C920, Class 25



MADE
IN THE USA



www.reddevil.com

Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

LIFETIME PRO WINDOW, DOOR & TRIM ADVANCED SEALANT

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0856PR	White	10.1 fl. oz (300 mL) Cartridge	0-75339-01007-5	12
0866PR	Clear	10.1 fl. oz (300 mL) Cartridge	0-75339-01008-2	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: Approx 13.2 +/-1
Specific Gravity: Approx. 1.55 to 1.65
Total Non-Volatile % Solids (Weight): > 80% +/- 2.5
Viscosity: Approx. 10 Seconds +/- 3
Consistency/Appearance: Smooth Paste
Flash Point: > 200°F - Non-Flame/Waterborne
Odor: Mild
Base Polymer: Acrylic Emulsion Blend
Filler/Pigment: Calcium Carbonate/Titanium Dioxide
pH (initial): 7 to 9
Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)
Shelf Life: Expect 1 Year @ 72°F
Tack Free Time: < 1 Hour @ 72°F
Full Cure: 72 Hours (cool & humid environments will extend)
Storage Conditions: Original Container: 40°F to 90°F
Application Temperature: 40°F to 90°F (5°C to 32°C)
Paintability: Latex: 2 Hours; Oil-Based 24 Hours
Elongation at Break/Ultimate Tensile: 700% Minimum
Service Temperature: -25°F to 180°F (-32°C to 82°C)
Tooling/Workability: Excellent @ 50°F to 90°F
% Elongation: Approx. 40%
Clean-Up: Water - Before Cure
Coverage: 50 feet w/ 3/16" bead

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Red Devil® Caulk Smoother, Putty Knife or Damp Cloth. Wipe away excess with a damp cloth before surface skins over. Protect from water until cured (72 Hours). Full clarity reached in 1 to 2 weeks. Cool and humid conditions will extend cure time.

FOR BEST RESULTS:

- Store at temperatures above freezing.
- Apply in temperatures above 40°F (5°C) - sealant, surface & air should be @ 40F to 90F when applied.
- Joint width should not exceed ½". If joint depth exceeds ¼", use a backer rod.
- Prime bare surfaces before caulking.

CLEAN-UP:

Clean tools immediately w/ water. Wash skin with warm water & soap.

LIMITATIONS:

- Not recommended for automotive use, on mirrors or aquariums.
- Protect from water until cured (72) hrs) - cooler temperatures % higher humidity will extend cure time.
- Avoid use in marine environments & other below-grade applications.
- Not recommended for below waterline applications.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See MSDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5% by weight, < 25g/L

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide and Carbon Black Exposure - www.P65Warnings.ca.gov