



MULTI-PURPOSE SPRAY TACK™

Multi-purpose Spray Tack™ is a non-flammable pressure-sensitive adhesive with rapid drying and quick-grab technology. This adhesive forms a water-resistant bond for temporary, permanent, single-sided, and double-sided applications. Multi-Purpose Spray Tack is formulated without methylene chloride or other hazardous air pollutants and provides long-lasting tack on a variety of materials.

FEATURES:

- Nonflammable Solvent and Propellant System
- Fast, Long-Lasting Tack
- High Solids for Increased Coverage
- No Methylene Chloride or NPB
- HAPs Free (Hazardous Air Pollutants)
- Permanent or Temporary Bond
- Adjustable Spray Pattern: 3 – 12 inches
- Water-Resistant Bond

USE ON:

Air Ducts, Insulation, Foam Fabrication, Manufactured Housing, Furniture & More.

ADHERES TO:

Galvanized Steel, Stainless Steel, Aluminum, Rigid Plastic Substrates, Fiberglass, Foams, Urethane Foams, Kraft Backed Foils, Foil Jacketing, Textiles, Backed Upholstery Vinyl, Carpets, and other substrates.



NON-FLAMMABLE
NON-METH



HIGH BONDING
STRENGTH



WIDE WEB
SPRAY PATTERN



INSTANT TACK



www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

SPRAY TACK™ MULTI-PURPOSE CLEAR WEB ADHESIVE

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0849DI	Clear/Amber	40 lb. Canister	0-75339-00670-2	1

PHYSICAL & CHEMICAL PROPERTIES:

Solids: 30% +/- 2%

Bonding Range: 1 minute - 2 hours

Dry/Tack Time: 1 - 3 minutes

Open Time: 1 hour

Application Temperature: 65°F to 90°F (18°C to 32°C)

Spray Pattern: Web

Shelf Life: 12 months in unopened container

Coverage: Approx. 54 sq. ft. @ 2.5g

Clean Up: Mineral Spirits

STORAGE:

Store in a cool, dry, well-ventilated area, out of direct sunlight. Keep canister tightly closed when not in use. Canister should be stored between 60°F and 90°F (16°C to 32°C) and kept off the floor. Do not handle or store near an open flame or other sources of excessive heat.

PRODUCT USAGE:

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Avoid breathing fume/gas/mist/ vapors/ spray. Wash hands and exposed skin areas with soap and warm water thoroughly after handling. Do NOT touch eyes. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Stop leak if safe to do so. Wear eye protection/face protection/protective gloves. Take off contaminated clothing and wash it before reuse. Dispose of contents/ container to a licensed treatment, storage, or disposal facility.

APPLICATION:

1. Test adhesive on small area before use to confirm surface compatibility.
2. Prepare surfaces by ensuring they are clean, dry, and free of debris, oil, and grease. Do not wet surfaces. Adhesive can be applied to one or both surfaces.
3. Hold the spray gun 6–10 inches from the surface at a 90° angle. Apply an even web-style coat to cover 80%–100% of the surface without oversaturating or puddling.
4. For porous surfaces, apply a second coat after first coat becomes tacky.
5. Allow adhesive to dry 1–5 minutes, or until tacky with no transfer when touched. Dry time may vary based on temperature, humidity, and airflow.
6. Carefully align surfaces before bonding. Press surfaces together firmly, working from the center outward to remove air pockets and wrinkles.
7. Apply consistent pressure to ensure proper adhesion. The initial bond is repositionable if adjustment is needed.
8. Allow 24–48 hours for full bond strength to develop.

LIMITATIONS:

- Not recommended for use with unbacked plasticized vinyl materials.
- Product is freeze/thaw stable; if material has been exposed to temperatures below 41°F (5°C), allow it to warm to room temperature (72°F / 22°C) and agitate thoroughly prior to use.
- Do not apply or form bonds at material or substrate temperatures below 65°F (18°C), as bond performance may be adversely affected.

CRITERIA	STATUS
CARB Compliance	No
Prop 65 Ingredients	No
DOT Proper Shipping Name	N.O.S.
DOT Hazzard	Chemicals Under Pressure
DOT UN/NA Number	UN3500
Packing Group	2.2
VOC Content	< 303 g/L

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: CHEMICAL UNDER PRESSURE: MAY EXPLODE IF HEATED. CAUSES MILD SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. HARMFUL IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF REACH OF CHILDREN & PETS. NOT FOR INTERNAL CONSUMPTION. (See SDS for additional safety information)