

Caulk Strip

Red Devil's Caulk Strips are self-adhesive butyl based decorative trim sealers for Kitchen & Bath tub, fixture, counter, floor, and wall applications. Simply peel away the backing paper and press into place.

FEATURES:

- Provides Watertight Seal
- Installs in Minutes
- Excellent White Color
- Pre-shaped for Easy Installation
- Siliconized Caulk Adhesive
- Excellent Stain Resistance
- Typically Cures Fully in 24 hrs
- Cured Strip is Mildew Resistant
- Provides a Professional Look to Kitchen & Bath Areas


USES:

Bridge small gaps between...

- Bathtubs & Floors/Walls
- Fixtures & Floors/Walls
- Countertops & Walls



**EXCELLENT
ADHESION**



**FULL CURE IN
24 HOURS**



**EASY
APPLICATION**



**MOLD & MILDEW
RESISTANT
WHEN CURED**



**EXCELLENT STAIN
RESISTANCE**

TECHNICAL DATA SHEET

CAULK STRIP

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0150	White	7/8" x 11' Strip	0-75339-10150-6	4
0151	White	1-5/8" x 11' Strip	0-75339-10151-3	3
0152	White	1/2" x 6' Strip	0-75339-10152-0	4
0155	Off-White	1" x 12' Strip	0-75339-01550-6	4
0170	White	1-1/4" x 5' Strip	0-75339-10170-4	4

PHYSICAL & CHEMICAL PROPERTIES:

Total Non Volatile % Solids (Weight): 100%

Consistency/Appearance: White/Off-White Strip

Odor: Mild

Base Polymer: Butyl Rubber

Pigment: Calcium Carbonate

Freeze/Thaw Stability: Passes 5 Cycles

Shelf Life: 2 years in original unopened container

Tack Free Time: 8 Hours

Full Cure: 24 Hours

Shore A Hardness: 12

Storage Conditions: 40°F to 90°F

Application Temperature: 60°F to 90°F

Water Resistance (full cure): Excellent

Peel Strength (Glass @ 24 hr cure): 5 lbs/inch

Clean Up (before cure): Mineral Spirits

Paintability: Excellent After Full Cure

APPLICATION:

1. Remove all loose, protruding or mildewed caulk. If silicone caulk is present, it must be completely removed.
2. Clean area thoroughly to remove caulk residue, mildew, dirt, and soap film. Wipe surface with rubbing alcohol and allow to dry completely before installing caulk strip.
3. Measure the length of the Tub or fixture to be sealed and position the strip around or along the area to determine the correct length before cutting. Once you are sure of the length, cut the strip(s) accordingly.
4. Bend the caulk strip by folding it at the score line to form a 90 angle.
5. Peel the first 2 inches of backing paper and press the caulk strip against the surface area. Continue to peel the backing paper pressing firmly until the entire length of caulk strip has been applied.
6. After installing, press fingers firmly over the entire length of caulk strip to ensure a watertight seal.
7. For best results, protect area from water for at least 8 hours.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Cancer and Reproductive Risk From Calcium Carbonate and Silicon Dioxide Exposure - www.P65Warnings.ca.gov