



Red Devil



Wallpaper Seam Repair

The easiest solution for repairing torn or peeling wallpaper, this premium adhesive provides a strong final bond between surface and wallpaper and prevents peeling in high-humidity areas such as kitchens and baths. Excellent adhesion, odorless & easy water clean up.

FEATURES:

- Superior Durability
- Excellent Adhesion
- Water Clean Up
- Low Odor
- Easy to Use
- VOC Compliant

USES:

- Window and Door Frames
- Siding
- Trim
- Baseboards
- Crown Molding
- Corner Joints
- Ceiling and Wall Joints

ADHERES TO:

- Wood Surfaces
- Drywall
- Plaster Walls
- Wallboard



EXCELLENT
ADHESION



EASY WATER
CLEAN-UP



SUPERIOR
DURABILITY



LOW ODOR



EASY
EASY TO USE



www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

HOUSE & HOME RESTORE™ WALLPAPER SEAM REPAIR

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0878	Clear	5.0 fl oz. Squeeze Tube	0-75339-08780-0	5

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 9.0+/- 0.5 lbs.

Extrusion Viscosity: 6+/- 2 Seconds

Total Non Volatile % Solids (Weight): 61% +/- 2.5

Coverage: 20-25 Linear ft at 3/16" Bead

pH: 7 to 9

Odor: Mild

Color: Applies White, Dries Clear

Flash Point: > 200°F (94°C)

Freeze/Thaw Stability: Passes 5 Cycles

Shelf Life: 12 Months

Slump: < 0.15

Tack Free Time: < 2 Hours

Full Cure: 72 Hours

Storage Conditions: 40°F to 90°F

Application Temperature: 40°F to 90°F

Service Temperature: 0°F to 200°F

Shrinkage: < 50%

Clean-Up: Soap and Water

APPLICATION:

Wallpaper backing & surface, to which wallpaper will adhere, should be sound, clean and dry.

1. Clip off tip of spout @ a 45 degree angle to desired bead size.
2. Carefully apply adhesive to back of loose or torn wallpaper or surface to which wallpaper will adhere.
3. Use a plastic putty knife or spreader to smooth surface & eliminate any bubbles. & immediately wipe away any excess with a damp cloth or sponge taking care to remove all adhesive from face of wallpaper.
4. Clean up with water or water & mild soap.
5. Allow 72 hrs for adhesive to reach final bond set.

FOR BEST RESULTS:

- Surface (back of wallpaper & substrate) should be clean & free of contaminants.
- Allow 72 hrs for final bond set.
- Wipe any excess from face of wallpaper immediately using with a damp cloth or sponge.
- Use a plastic putty knife or spreader to smooth surface & eliminate any bubbles.

LIMITATIONS:

- Designed for use on wallpaper only
- Allow 72 hrs bond set time

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	No
DOT Proper Shipping Name	Not Regulated
DOT Hazzard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 0.5%/wt, < 10 g/L

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)