



Window & Door

Window & Door Siliconized Acrylic Caulk seals around windows, doors, and other areas. This multi-purpose, paintable sealant can be used indoors or outdoors to help increase energy efficiency by reducing drafts, limiting cold spots, and also providing a barrier to the entry of dirt, insects, and other pests. This caulk has excellent adhesion to most surfaces, can be used on a variety of substrates and is mildew resistant when cured.

FEATURES:

- VOC Compliant
- 35 Year Durability Guarantee
- Mold & Mildew Resistant When Cured
- Water Clean-Up
- Excellent Adhesion
- Easy Application & Tooling
- Interior/Exterior Use
- Paintable

USES:

Formulated for use on Window & Door Frames, Siding, Trim, Baseboards, Crown Molding, Corner Joints, Subfloors, Countertops, Sinks, Bathtubs, Vents & More.

ADHERES TO:

Painted & Unpainted Wood, Tile, Plaster, Drywall, Brick, Glass, Metal, Aluminum, Cement, Masonry & More.



INTERIOR &
EXTERIOR USE



SUPERIOR
PAINTABILITY



MOLD & MILDEW
RESISTANT
WHEN CURED



WATER
CLEAN-UP



Meets or Exceeds Federal Specifications:

- ASTM C834-05



www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

Window & Door

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0846	White	10.1 fl. oz (300 mL) Cartridge	0-75339-00846-1	12
084620	Almond	10.1 fl. oz (300 mL) Cartridge	0-75339-08462-5	12
084630	Cedar	10.1 fl. oz (300 mL) Cartridge	0-75339-08463-2	12
084640	Dark Brown	10.1 fl. oz (300 mL) Cartridge	0-75339-08464-9	12
084650	Gray	10.1 fl. oz (300 mL) Cartridge	0-75339-08465-6	12
084660	Black	10.1 fl. oz (300 mL) Cartridge	0-75339-08466-3	12
0876	Clear	10.1 fl. oz (300 mL) Cartridge	0-75339-00876-8	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 13.75 +/- 0.75

Specific Gravity: Approx. 1.65

Total Non-Volatile % Solids (Weight): > 80.5% +/- 2.5

Extrudability/Application: Approx. 350,000 cPs

Consistency/Appearance: Smooth, Viscous Paste

Flash Point: > 200°F - Non-Flammable

Odor: Mild Acrylic

Base Polymer: Acrylic Emulsion Blend

Filler/Pigment: Calcium Carbonate, TiO₂

pH (initial): 7 to 10

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Expect 1 Year @ 72°F

Tack Free Time: < 1 Hour @ 72°F

Full Cure: 72 Hours (cool & humid environments will extend)

Storage Conditions: 40°F to 90°F (5°C to 32°C)

Application Temperature: 40°F to 90°F (5°C to 32°C)

Paintability: Latex-Based 2-6 Hours; Oil-Based 24 Hours

Elongation: 700% Minimum

Service Temperature: -20°F to 180°F (-29°C to 82°C)

Clean-Up: Water

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife or Damp Cloth. Remove excess with a damp cloth before surface skins over. Clean tools & hands immediately with soap & water.

FOR BEST RESULTS:

- Store at temperatures above freezing.
- Joint width should not exceed ½". If joint depth exceeds ¼", use a backer rod.
- Use on primed surfaces.
- Do not over-tool the applied caulk.

LIMITATIONS:

- Not recommended for use on automotives, fish tanks/ aquariums, and mirrors.
- Not recommended for below waterline or below-grade applications.
- Protect from water until cured (72 Hours) - Cooler temperatures & higher humidity will extend cure time.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 0.5% by weight, < 10 g/L

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide Exposure - www.P65Warnings.ca.gov