



Fix-A-Floor® TILE Grout

Fix-A-Floor® Tile Grout is a pre-mixed acrylic latex grouting composition that provides a quick and easy solution for repairing holes and gaps in grout lines. This shrink/crack-proof formula is water, stain, and mildew resistant.

FEATURES:

- Pre-Mixed & Ready to Use
- Tack-Free in 30 Minutes
- Stain & Water Resistant
- Won't Shrink or Crack
- Excellent Adhesion
- Mildew Resistant Once Cured
- Easy Water Clean Up
- Low Odor & Low VOC

USE ON:

- Ceramic
- Porcelain
- Mosaic
- Marble
- Granite
- Stone
- Glass

ADHERES TO:

- Masonry
- Glass
- Wood
- Drywall



PRE-MIXED
READY TO USE



STAIN & WATER
RESISTANT



TACK-FREE
IN 30 MIN



WON'T SHRINK
OR CRACK



WATER
CLEAN UP



www.reddevil.com
www.fixafloorworldwide.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

FIX-A-FLOOR® TILE GROUT

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
FIX510	White	5.5 fl. oz (163 mL) Squeeze Tube	0-75339-04207-6	12
FIX520	Almond	5.5 fl. oz (163 mL) Squeeze Tube	0-75339-04211-3	12
FIX550	Gray	5.5 fl. oz (163 mL) Squeeze Tube	0-75339-04215-1	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 13.50

Specific Gravity: 1.62

Total Non-Volatile % Solids (Weight): 85.0%

Viscosity: 75,000 cps

Consistency: Paste

pH (initial): 9.50

Base Polymer: Acrylic Latex Emulsion Blend

Flash Point: >200°F

Freeze/Thaw: Pass 3 cycles (0°F/77°F @ 24 hours)

Shelf Life: 12 months @ 72°F

Storage Temperature: 40°F to 90°F (4°C to 32°C)

Application Temperature: 55°F to 90°F (13°C to 32°C)

Tack Free Time: Approx. 30 minutes

Full Cure Time: 24-48 hours

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5 % by weight, < 40 g/L

APPLICATION:

When repairing drill holes from the Fix-A-Floor® Repair Adhesive application, ensure any excess adhesive or residue has been completely cleaned off the application surface and all applied adhesive has fully cured.

When repairing existing tile installations, remove 1/16" of old grout with a grout rake or chisel, and disinfect the application area to prevent mildew growth.

Scrub surface with a wet sponge or brush, then wipe dry with a cloth to remove any loose debris or contaminants. Remove cap, cut nozzle tip at a 45° angle to desired size, matching the width of the joint. Squeeze tube directly into each joint and smooth over with a grout float or damp cloth. For best results, work in areas approximately 4 square feet at a time and apply when surface, air, and material temperatures are > 55°F. Remove excess grout with a damp sponge or cloth. Allow tile grout to dry for 1 hour, then buff surface with a clean, dry cloth. Let grout fully cure for 48 hours before exposing to water, traffic, or grout sealer. Cure time may be longer in areas of high humidity.

FOR BEST RESULTS:

- Don't apply when surfaces/air/material temperature is < 55°F
- Apply in properly ventilated areas.
- Allow full cure before subjecting to water exposure.
- Allow full cure before applying any type of grout sealer

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Cancer Risk and Reproductive Harm - www.P65Warnings.ca.gov