



# Red Devil

## All-Purpose **QUICK GRIP**<sup>™</sup> CONSTRUCTION Adhesive

Quick Grip<sup>™</sup> is a premium, all-purpose construction adhesive with a quick setting, instant grab that holds like an iron grip. Its high initial tack often eliminates the need for nails and screws. This powerful formula is also low-VOC and eco-friendly.

### FEATURES:

- Fast Grab, High initial Tack
- Non-Flammable
- High Strength
- GREENGUARD<sup>®</sup> Certified
- Freeze Thaw Stable
- Water Resistant
- Low VOC

### USES:

Formulated for use on Wood, Plywood, Carpet, Ceramic Tile, Chip Board, Concrete, Brick, Masonry, Cork, Drywall, Foamboard, FRP Panels & More.

### ADHERES TO:

Stone, Brick, Concrete, Ceramic, Wood, Plywood, Foamboard, Cork, Drywall, Plaster, Vinyl & More.



IMMEDIATE  
BONDING  
STRENGTH



MEETS  
GREENGUARD<sup>®</sup>  
STANDARDS



MOLD & MILDEW  
RESISTANT  
WHEN CURED



ASTM C-557  
PERFORMANCE

Meets or Exceeds Federal Specifications:

- ASTM C557 & AFG-01
- ASTM D3498



MADE  
IN THE **USA**



[www.reddevil.com](http://www.reddevil.com)

Customer Service: 1-800-423-3845

Red Devil, Inc.  
4175 Webb Street  
Pryor, OK 74361

# TECHNICAL DATA SHEET

## QUICK GRIP™ CONSTRUCTION ADHESIVE

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0696	Off-White	9.0 fl. oz (266 mL) Cartridge	0-75339-01322-9	12

### PHYSICAL & CHEMICAL PROPERTIES:

**Weight Per Gallon:** 12 +/- 2

**Total Non-Volatile % Solids (Weight):** 25% to 30%

**Specific Gravity:** ~ 1.00 to 1.50

**pH (initial):** 7 to 10

**Consistency/Appearance:** Smooth Paste

**Base Polymer:** Proprietary acrylic latex

**Odor:** Very Mild, Acrylic

**Pigment/Filler:** Calcium Carbonate

**Flash Point:** > 200°F - Non-Flammable

**Freeze/Thaw Stability:** Passes 5 Cycles (ASTM)

**Shelf Life:** Minimum 1 year unopened @ 72°F

**Slump:** None

**Artificial Weathering:** Paint or coat in exterior applications

**Open Time:** 20 to 30 Minutes (temperature & humidity)

**Storage Conditions:** 40°F to 90°F (4°C to 32°C)

**Application Temperature:** 50°F to 90°F (-17°C to 82°C)

**Service Temperature:** 5°F to 125°F (-17°C to 82°C)

**Tooling:** Excellent, prior to skin formation

**Paintability:** Excellent

**Initial Dry Time:** 24 hours @ 77°F/50% RH

**Full Cure:** 7 days, in normal conditions

**Viscosity:** 650,000 cp - 800,000 cps

### APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife or Damp Cloth. Remove excess with a damp cloth before surface skins over. Full clarity reached in 1 to 2 weeks.

### FOR BEST RESULTS:

- Product, surfaces, and working area should be at least 50°F
- Best application temperature range, 50°F to 90°F.
- One of the substrates should be porous.
- For exterior applications, visible adhesive should be painted or topped with a suitable coating.

### CLEAN-UP:

Tools and adhesive may be cleaned with warm water and soap prior to cure.

### LIMITATIONS:

- Not designed for continuous submersion.
- Not recommended for use on mirrors.
- One surface must be porous.
- Not recommended for PE, PP, Nylon™ or Teflon™.

### LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 0.5%/wt, < 5 g/L

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)**

**⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide and Carbon Black Exposure - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**