



# PRE-MIXED VINYL SPACKLING

Patch holes and nailheads quickly and easily in plaster, wallboard, wood and stucco with Pre-Mixed Vinyl Spackling. This general purpose, water-based spackling compound is specially formulated for easy application and sanding. It dries fast and holds tight.

## FEATURES:

- Easy Water Clean-Up
- Paintable
- Dries Fast
- Interior/Exterior Use
- Sands Easily
- Easy Application & Tooling
- VOC Compliant

## ADHERES TO:

Plaster, Drywall, Wallboard, Wood, Primed Metal & More.

## USES:

Excellent for filling holes & cracks in interior walls, material will not crumble or flake.



WATER-BASED



INTERIOR  
& EXTERIOR



PAINTABLE



EASY APPLICATION  
SANDING &  
PAINTABILITY



VOC  
COMPLIANT



[www.reddevil.com](http://www.reddevil.com)  
Customer Service: 1-800-423-3845

Red Devil, Inc.  
4175 Webb Street  
Pryor, OK 74361

# TECHNICAL DATA SHEET

## PRE-MIXED VINYL SPACKLING

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0531	Off-White	1 Gallon (3.79 liter) Tub	0-75339-00531-6	2
0532	Off-White	1/2 (284 mL) Pint Tub	0-75339-00532-3	12
0534	Off-White	1 Quart (0.95 Liter) Tub	0-75339-00534-7	6
0538	Off-White	1 (568mL) Pint Tub	0-75339-00538-5	12
0615	Off-White	5.5 fl. oz (163 mL) Squeeze Tub	0-75339-00615-3	12

### PHYSICAL & CHEMICAL PROPERTIES:

**Weight Per Gallon:** 10.0 +/-0.50

**Specific Gravity:** 1.20

**Total Non-Volatile % Solids (Weight):** 77% +/- 2.0

**Total Non-Volatile % Solids (Volume):** 61% +/- 2.0

**Consistency/Appearance:** Thick, Smooth Paste

**pH (initial):** 8.5 +/- 0.50

**Odor:** Very Low - Mild Latex

**Base Polymer:** Vinyl Acrylic Emulsion Blend

**Filler/Pigment:** Calcium Carbonate

**Flash Point:** Non-Flammable/Waterborne; >200F

**Freeze/Thaw Stability:** Pass 5 Cycles (ASTM C731)

**Shelf Life:** Expect 2 Years @ 77°F

**Slump:** None in Typical Application

**Rheological Characteristics:** Thixotropic

**Storage Conditions:** Original Container 40°F to 90°F

**Application Temperature:** 50°F to 90°F (10°C to 32°C)

**Tooling:** Excellent @ 50°F to 90°F (10°C to 32°C)

**Service Temperature:** 0°F to 180°F (-18°C to 93°C)

**Paintability:** Excellent @ 1 to 2 Hours Drying (Latex & Oil-Based)

### APPLICATION:

Surface should be clean, sound, dry, and free from dirt, dust, grease, oil, mildew, loose paint. Apply only when spackling compound, air & surface temperatures are above 50°F (10C) & rising. Apply with spackling knife & press firmly into crack or small void. Two or more applications may be required for larger cracks & voids. Allow patch to dry for 1-2 hours between applications, depending upon climatic conditions. When patch is completely dry (1-2 hours in normal humidity), patch may be sanded smooth. Sanded patch should be dust-free & otherwise clean, prior to priming & painting.

### FOR BEST RESULTS:

- Surface should be sound & prepared as described within Application.
- Apply when spackling, air & substrate are 50°F & rising.
- New or unpainted porous surfaces should be primed & allowed to dry before patching.
- Sanded patches should be primed & painted.

### CLEAN-UP:

Clean tools & skin with warm water & soap.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazzard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5%/wt, < 10 g/L

### LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS.  
KEEP FROM FREEZING. (See SDS for additional safety information)**

**⚠ WARNING: Cancer Risk From Titanium Dioxide Exposure - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**