



FOAM & FILL[®] Large Gaps and Cracks Expanding Polyurethane Sealant

Foam & Fill[®] Large Gaps & Cracks Expanding Polyurethane Sealant is quick and easy to use. It expands to fill holes, cracks, gaps, and voids around windows, doors, pipes, outlets, vents, and foundations. This insulating foam forms an airtight, waterproof bond and seals out drafts, moisture, and pests. Cured foam can be sanded, painted, or stained. Contains no HCFCs or CFCs so it is safe for the environment.

FEATURES:

- Quick and Easy to Use
- Fills Holes, Gaps and Cracks
- Insulates and Prevents Drafts
- Seals Out Insects and Pests
- Interior & Exterior Use
- UL Listed Component
- Contains No HCFC's or CFC's

USES:

Formulated for use on Window & Door Frames, Pipes, Electrical Outlets, Vents, Holes, Gaps, Foundation and More.

ADHERES TO:

Wood, Concrete, Brick, Glass, Metal, PVC & Other Plastics.



FILLS LARGE HOLES, GAPS & CRACKS



UV PROTECTED WHEN PAINTED



FISH & PLANT SAFE



UL[®] LISTED

Meets or Exceeds Federal Specifications:

- ASTM E-84



www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

Triple Expanding Polyurethane Foam Sealant

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
090806	Champagne	8 oz (227 g) Can	0-75339-01634-3	6
0909	Champagne	12 oz (340 g) Can	0-75339-00909-3	12
0912	Champagne	20 oz (567 mL) Can	0-75339-00912-3	12

PHYSICAL & CHEMICAL PROPERTIES:

Thermal Conductivity: 0.22 to 0.2 Btu In/Hr F sq ft.

Flame Speed: 15

Smoke Developed: 35

Color: Champagne like

Odor: Mild (Use w/ adequate ventilation)

Tack Free Time: 10 minutes

Fully Expanded: 24 hours

Expansion: 12 oz. can: Approx. 0.35 cu. Ft.

Linear Footage (3/8" Foam Bead): 12 oz. can: Approx. 0.35 cu. Ft.

Fully Cured: 4 to 24 hours (depending on temperature & humidity)

Paint Over Time (Latex and Oil Based): When fully cured

Weathering: Must be protected w/ premium quality paint when used in sunlight or UV light.

Heat Resistance: Cured foam must be covered w/ a thermal barrier if exposed to temperatures above 250°F (121°C). Product should not be exposed to direct flame.

Clean-Up: Uncured use Red Devil Gun Foam Cleaner or Acetone.

Cured foam can not be removed with solvents. If foam hardens on skin, use an industrial hand cleaner with pumice.

Shelf Life: 15 Months unopened at 77°F (25°C)

Water Resistance: Excellent (When cured)

Storage: Store in cool, dry area. Store in upright position at temps above freezing. Avoid temps above 100°F

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	None
DOT Proper Shipping Name	Consumer Commodity
DOT Hazard	Aerosols, Class 2.1, UN 1950
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 154 g/L

APPLICATION PREPARATION:

Shut off all gas pilot lights, electrical igniter's, burners and other sources of ignition and heat before and during use, as this product is **FLAMMABLE** during dispensing. Surface should be clean, dry & free of contaminants for maximum adhesion.

FOR BEST RESULTS:

- Always wear protective gloves and eyewear when using.
- Shake can vigorously for at least 1 minute before using.
- Test on a cloth or newspaper first.
- Applies foam subject to UV/Sunlight must be painted with appropriate premium paint or elastomeric coating.
- Apply when temperature is above 65°F and below 100°F. (Extrusion in lower temperatures will be slow and product curing may be affected).

CLEAN-UP:

Uncured Foam - Clean immediately with Red Devil Gun Foam Cleaner.
Cured Foam - cannot be removed with solvents. If foam hardens on skin, apply petroleum jelly, put on plastic gloves, leave on for 1 hours and rub off with clean cloth. Repeat if necessary.

RESTRICTIONS:

- Not recommended for filling enclosed cavities. Do not use between walls or under tub surrounds as expansion may alter dimensions. Care should be taken when using in conjunction with installation of doors and windows as expansion of foam may alter operation of components.
- Not for use as a fire stop foam.
- Can be used on virtually all, clean surfaces EXCEPT Teflon, Silicone and Polyethylene.
- Do not expose to rain or excessive moisture for 24 hours.
- Do not apply to surfaces with excessive moisture content.
- Flammable during dispensing.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

 **WARNING: Risk of Cancer and Reproductive Harm - www.P65Warnings.ca.gov**