



Red Devil

LIFETIME[®] Ultra 230

LIFETIME[®] Ultra 230 Premium Elastomeric Acrylic Latex Sealant is a high-performance, multi-purpose sealant formulated to last for the lifetime of your home. This unique formulation provides the maximum level of durability on a variety of substrates indoors or outdoors. It offers excellent paintability and includes HomeShield™ Antimicrobial Protection to ensure against the worst types of mold and mildew. Available in many colors.

FEATURES:

- Lifetime Durability Guarantee
- Multi-Surface Application
- Won't Shrink or Crack
- Withstands Active Joint Movement
- Mold & Mildew Resistant When Cured
- HomeShield™ Antimicrobial Protection
- Interior/Exterior Use
- Low VOC

USES:

Formulated for use on Window & Door Frames, Siding, Trim, Baseboards, Subfloors, Countertops, Sinks, Bathtubs, Vents, Concrete, Metal & More.

ADHERES TO:

Painted & Unpainted Wood, Tile, Plaster, Drywall, Brick, Glass, Metal, Aluminum, Concrete, Masonry & More.



INTERIOR &
EXTERIOR USE



SUPERIOR
PAINTABILITY



MOLD & MILDEW
RESISTANT
WHEN CURED



WATER
CLEAN-UP



Meets or Exceeds Federal Specifications:

- ASTM 230, Class A
- ASTM C920, Class 25



MADE
IN THE **USA**



www.reddevil.com

Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

LIFETIME® Ultra 230

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0770	White	10.1 fl. oz (300 mL) Cartridge	0-75339-01129-4	12
077010	Cedar	10.1 fl. oz (300 mL) Cartridge	0-75339-01128-7	12
077020	Almond	10.1 fl. oz (300 mL) Cartridge	0-75339-01123-2	12
077040	Brown	10.1 fl. oz (300 mL) Cartridge	0-75339-01125-6	12
077050	Gray	10.1 fl. oz (300 mL) Cartridge	0-75339-01127-0	12
077060	Black	10.1 fl. oz (300 mL) Cartridge	0-75339-01124-9	12
0777	Clear	10.1 fl. oz (300 mL) Cartridge	0-75339-01126-3	12
0705	Clear	5.5 fl. oz (163 mL) Squeeze Tube	0-75339-01662-6	12
0775	White	5.5 fl. oz (163 mL) Squeeze Tube	0-75339-01130-0	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 12 +/- 2.0

Specific Gravity: Approx. 1.40 to 1.50

Total Non-Volatile % Solids (Weight): > 80% +/- 2.5

Viscosity: Approx. 8 Seconds +/- 2

Consistency/Appearance: Smooth, Colored Paste

Flash Point: > 200°F - Non-Flame/Waterborne

Odor: Mild

Base Polymer: Acrylic Emulsion Blend

Filler/Pigment: Calcium Carbonate, TiO₂

pH (initial): 7 to 9

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Expect 1 Year @ 72°F

Tack Free Time: < 1 Hour @ 72°F

Full Cure: 72 Hours (cool & humid environments will extend)

Storage Conditions: 40°F to 90°F (5°C to 32°C)

Application Temperature: 40°F to 90°F (5°C to 32°C)

Paintability: Latex-Based 4-6 Hours; Oil-Based 24 Hours

Elongation at Break/Ultimate Tensile: 700% Minimum

Service Temperature: -25°F to 180°F (-32°C to 82°C)

Clean-Up: Water

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife or Damp Cloth. Remove excess with a damp cloth before surface skins over. Full clarity reached in 1 to 2 weeks.

FOR BEST RESULTS:

- Store at temperatures above freezing.
- Joint width should not exceed ½". If joint depth exceeds ¼", use a backer rod.
- Use on primed surfaces.

LIMITATIONS:

- Not recommended for use on automotives, fish tanks/aquariums, and mirrors.
- Not recommended for below waterline or below-grade applications.
- Protect from water until cured (72 Hours) - Cooler temperatures & higher humidity will extend cure time.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 0.5% by weight, < 10 g/L

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide and Carbon Black Exposure - www.P65Warnings.ca.gov