



Red Devil

ONETIME®

LightenUP™ Spackling

ONETIME® Lighten Up™ Spackling fills cracks, dents, nail holes, and other holes in interior and exterior surfaces such as drywall, plaster, wood and stucco. This lightweight, color-change formula goes on pink, but dries white, indicating when it's time to paint. Pre-mixed for fast, professional repairs in just one application, it doesn't need sanding and won't shrink, crack or flake.

FEATURES:

- Goes On Pink, Dries White When It's Time To Paint
- No Sanding Required
- Won't Shrink, Sag Or Crack
- Only One Application Needed
- Interior/Exterior
- Water Clean Up
- VOC Compliant

ADHERES TO:

Plaster, Wood, Drywall & Stucco.

USES:

Plaster Walls, Drywall, Wallboard, & Wood Surfaces.



NO SANDING
REQUIRED



INTERIOR
& EXTERIOR



PAINTABLE



WON'T CRACK,
SHRINK OR SAG



VOC
COMPLIANT



MADE
IN THE **USA**



www.reddevil.com

Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

ONETIME® LIGHTEN UP™ SPACKLING

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0572	Off-White	1/2 (284 mL) Pint Tub	0-75339-00541-5	12
0574	Off-White	1 Quart (0.95 Liter) Tub	0-75339-00544-6	6

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 3.5 +/- 1.0

Specific Gravity: Approx. 0.40 to 0.50

Total Non-Volatile % Solids (Weight): 60 to 70%

Application: Excellent After Stirring Well

Consistency/Appearance: Smooth Paste as Applied

pH (initial): 9.0 +/- 1.0

Odor: Mild Latex, Slight Ammonia

Base Polymer: Proprietary Blend

Filler/Pigment: Proprietary Blend

Flash Point: Non-Flammable/Waterborne; >200F

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Minimum 6 Months @ 77°F

Slump: None (1/4 x 1/4 wallboard)

Storage Conditions: Original Container 40°F to 90°F

Application Temperature: 50°F to 90°F (10°C to 32°C)

Tooling: Excellent After Stirring

Service Temperature: -5°F to 180°F (-18°C to 93°C)

Paintability: Excellent @ Color Change

Shrinkage: None

APPLICATION:

Surface should be clean, sound, dry, and free from dirt, dust, grease, oil, mildew, wax & loose paint. Stir product well prior to use. Thin slightly as described above if desired. Apply only when spackling compound, air & substrate are between 50F & 90F. Apply with spackling knife & press into crack or void. Applied product will be a light to medium pink. To achieve more even drying in larger holes, stuff the hole with newspaper prior to patching. New or unpainted porous surfaces should be primed & allowed to dry, prior to patching. When drying patch has changed color from pink to white, it is ready for painting. When used in exterior applications, product must be painted when thoroughly dry with oil based or water based paint.

FOR BEST RESULTS:

- New or unpainted porous surfaces should be primed or painted & allowed to dry, prior to patching.
- Cured patches should be painted with oil or latex paint when completely dry - color change from pink to white has fully occurred.

CLEAN-UP:

Water or Mild Soap & Water.

LIMITATIONS:

- Do not apply when rain or freezing temperatures are expected.
- Protect from exposure to rain & water for 72 hours (longer in conditions of cool temperatures & higher humidity).
- Exterior applications must be painted with oil or latex paint following complete drying - color change from pink to white color.
- Apply product when spackling air temperature & substrate are above 50F & rising.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5%/wt, < 10 g/L

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS.
KEEP FROM FREEZING. (See SDS for additional safety information)**

WARNING: Cancer Risk From Titanium Dioxide Exposure - www.P65Warnings.ca.gov

