

Fix-A-Floor®

ADHESIVE & RESIDUE REMOVER

Fix-A-Floor® Adhesive & Residue Remover is a powerful, solvent-based formula designed to lift tough adhesive buildup and dried residue from hard surfaces. Ideal for post-repair cleanup, it quickly removes any leftover haze from Fix-A-Floor® injection adhesive applications and restores surfaces to a clean, residue-free finish.



FEATURES:

- Extra Strength Formula
- Surface Safe
- Works Fast
- Easy to Use
- Low Odor & Low VOC

USE ON:

- Ceramic
- Porcelain
- Marble
- Granite
- Natural stone
- Limestone
- Concrete
- Wood
- Glass



**EXTRA
STRENGTH**



**MULTI-SURFACE
APPLICATION**



**LOW VOC
& LOW ODOR**



**WATER
CLEAN-UP**



**INTERIOR
& EXTERIOR**



TECHNICAL DATA SHEET

FIX-A-FLOOR® ADHESIVE & RESIDUE REMOVER

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
FIX016	Transparent	16 fl. oz (473 mL) Squeeze Bottle	8-59704-00301-1	10

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 6.64 lb/gal

Specific Gravity: Approx. 0.80

Loss on Drying: (Weight): 23%

Viscosity: 4.962 cSt

Appearance: Clear and Bright

Odor: Low

Flash Point: Non-Flammable, > 200° F

Coverage: Approx. 250 ft² (dependent on surface porosity/temp)

Shelf Life: Expect 12 Months @ 72°F

Storage Conditions: 40°F to 90°F (5°C to 32°C)

Application Temperature: 50°F to 90°F (10°C to 32°C)

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazzard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	See SDS

APPLICATION:

1. Ensure the work area is well-ventilated and wear chemical-resistant gloves before use.
2. Pre-test solution on an inconspicuous area, according to application instructions, to determine desired results.
3. Apply Fix-A-Floor® Adhesive & Residue Remover directly to the affected area or liberally apply to a clean, dry cloth and spread onto the affected area. For tougher residues, allow solution to sit for 2-4 minutes after application.
4. Use a damp sponge to scrub and remove the adhesive or residue from the application surface.
5. Wipe the surface off with a clean cloth and buff dry until all residue is removed.

CLEAN-UP, STORAGE, & DISPOSAL:

CLEAN-UP with soap and water. **STORE** properly sealed and upright in original container at approx. 77°F (25°C) **KEEP FROM FREEZING**. **DISPOSE** of in accordance with federal, state, and local regulations.

FOR BEST RESULTS:

- Do not use on rubber, PVC, unfinished wood, unglazed tile, or unsealed stone/concrete surfaces.
- Do not allow solution to completely dry or sit longer than recommended on application surface.

LIMITED WARRANTY:

This product is warranted to be free of manufacturing defects. If a manufacturing defect is found within one year from the date of purchase, such defective product shall be replaced. No warranty either expressed or implied is made regarding the performance of this product since conditions under which these goods are transported, stored, used or applied are beyond our control. This warranty is made in lieu of all other warranties either expressed or implied and the seller shall not be responsible for consequential, incidental, special or other damages no matter what the cause.

CAUTION: MAY BE HARMFUL OR FATAL IF SWALLOWED. EYE & SKIN IRRITANT. NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING.
(See SDS for additional safety information)