



# Safety Data Sheet

Issue Date: 19-Aug-2013

Revision Date: 02-Apr-2019

Version 2

## 1. IDENTIFICATION

### Product identifier

**Product Name** Fireplace & Stove Repair – Sodium Silicate Based – Textured Black/Charcoal - Cartridge

### Other means of identification

**SDS #** RD-0026

**Product Code** 0466 Series

### Recommended use of the chemical and restrictions on use

**Recommended Use** A tough silicate cement that sets hard when fired. The black textured paste designed for interior use, adheres to fire brick, cinder block, metal & mortar. Cures w/ a warm fire & provides a durable, long-lasting seal that withstands temperatures to 2700°F. Long-lasting seal that withstands temperatures up to 2700°F.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Red Devil, Inc.  
4175 Webb Street  
Pryor, Oklahoma 74361  
www.reddevil.com

### Emergency telephone number

**Company Phone Number** 918-825-5744  
Fax: 918-825-5761  
**Emergency Telephone** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Black/Dark Charcoal Gray      **Physical state** Textured paste      **Odor** Mild to no Odor

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2

### Signal Word

**Warning**

### Hazard statements

Causes skin irritation  
Causes serious eye irritation



**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
Wear protective gloves  
Wear eye/face protection

**Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN: Wash with plenty of water  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash before reuse

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No	Weight-%
Sodium Silicate	1344-09-8	45-55
CAS #68953-58-52 & #68855-54-9; Silica and Clay Blend	Proprietary	40-50
Non-hazardous Ingredients*	Proprietary	<10
Silicate, as Perlite	Proprietary	<2.5
Carbon Black	1333-86-4	<0.05

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

\* Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
(Silica and Carbon black) Inhalation of particulates unlikely due to product's physical state.

**4. FIRST AID MEASURES**

**Description of first aid measures**

<b>General Advice</b>	Provide this SDS to medical personnel for treatment.
<b>Eye Contact</b>	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention. Eye irritation may be severe, if not immediately removed.
<b>Skin Contact</b>	Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.
<b>Inhalation</b>	Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention. Inhalation unlikely, as product is a paste.
<b>Ingestion</b>	Ingestion highly unlikely. Do not induce vomiting unless directed by medical personnel. If vomiting occurs, lean patient forward to maintain an open airway & prevent aspiration. Get immediate medical attention.

**Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.
-----------------	---

**Indication of any immediate medical attention and special treatment needed**

<b>Notes to Physician</b>	Medical Conditions Aggravated By Exposure: Dermatitis or other pre-existing skin
---------------------------	--

conditions may be aggravated by overexposure to this product. May cause serious skin and eye irritation.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray (fog). Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** Not determined.

### Specific Hazards Arising from the Chemical

Product is not flammable.

**Hazardous combustion products** Carbon oxides.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

**Other Information** Small Spills: 1 drum or less – Level D Equipment (gloves, chemical resistant apron, boots & eye protection).  
Large Spills: Rubber gloves, rubber boots, face shield & Tyvek suit as a minimum. Minimum level of PPE for releases in which the oxygen level is < 19.5% or is unknown, should be Level B: triple gloves (rubber gloves & nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing & boots, hard hat & self-contained breathing apparatus.

**For Emergency Responders** Restrict access to spill area.

### Environmental precautions

**Environmental precautions** Minimize use of water to prevent environmental contamination. Prevent spill or rinse from contaminating storm drains, sewers, soil or groundwater. Do not allow discharge containing this material to enter streams, ponds, estuaries, oceans or other waters unless in accordance w/ requirements of National Pollutant Discharge Elimination System (NPDES) permit & permitting authority has been notified in writing prior to discharge. Do not allow discharge containing this material to enter sewer systems w/o previously notifying local sewage treatment plant authority. For information, contact State Water Board or EPA Regional Office  
Other: U.S. regulations may require reporting of spills of this material reaching surface waters if sheen is formed. See Section 12 for additional Ecological Information.

### Methods and material for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

**Methods for Clean-Up** Sweep up absorbed material and shovel into suitable containers for disposal. Wash area with soap and water. For waste disposal, see section 13 of the SDS.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on Safe Handling**

Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing. Do not eat or drink while handling this material. In event of spill – see Section 6.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions**

Stable under normal conditions of handling, use & storage. Store containers in a cool, dry location, away from direct sunlight & high temperatures. Protect from freezing. Store away from incompatible materials. Close container after each use & keep tightly closed when not in use. To maximize shelf life, store @ temperatures below 26C (80F).

**Incompatible Materials**

Acids.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines**

Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Silicate, as Perlite	-	(vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Carbon Black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

**Appropriate engineering controls**

**Engineering Controls**

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**

Use approved safety goggles or safety glasses. If necessary, refer to appropriate regulations and standards.

**Skin and Body Protection**

Skin: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill response. If necessary, refer to appropriate regulations & standards.

Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment) or appropriate Standards of Canada. Use foot protection, as described in appropriate regulations & standards.

**Respiratory Protection**

If mists or sprays are created, use appropriate respiratory protection. Oxygen levels below 19.5% considered IDLH by OSHA. In such instances, use full-facepiece pressure demand SCBA or a full facepiece, supplied air respirator w/ auxiliary self-contained air supply.

**General Hygiene Considerations** Wash contaminated clothing before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b> <b>Appearance</b> <b>Color</b>	Textured paste Black/Dark Charcoal Gray Black/Dark Charcoal Gray	<b>Odor</b> <b>Odor Threshold</b>	Mild to no Odor Not determined
--	--	--------------------------------------	-----------------------------------

<b><u>Property</u></b>	<b><u>Note: The information below is not intended for use in preparing product specifications</u></b>	<b><u>Remarks • Method</u></b>
------------------------	---	--------------------------------

<b>pH</b>	10-11.25
<b>Melting point / freezing point</b>	<0°C / <32°F
<b>Boiling point / boiling range</b>	Not Established
<b>Flash point</b>	>93.33°C / >200°F
<b>Evaporation Rate</b>	Not determined
<b>Flammability (Solid, Gas)</b>	Not determined
<b>Flammability Limit in Air</b>	
<b>Upper flammability or explosive limits</b>	Unknown
<b>Lower flammability or explosive limits</b>	Unknown
<b>Vapor Pressure</b>	Not established
<b>Vapor Density</b>	Not established
<b>Relative Density</b>	~1.50-2.00
<b>Water Solubility</b>	slightly soluble
<b>Solubility in other solvents</b>	Not determined
<b>Partition Coefficient</b>	Not determined
<b>Autoignition temperature</b>	Unknown
<b>Decomposition temperature</b>	Not determined
<b>Kinematic viscosity</b>	Not determined
<b>Dynamic Viscosity</b>	Not determined
<b>Explosive Properties</b>	Not determined
<b>Oxidizing Properties</b>	Not determined

### Other information

**VOC Content** <10 g/L

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
---------------------------------	--

### Conditions to Avoid

Incompatible Materials. Excessive heat or cold.

### Incompatible materials

Acids.

### Hazardous decomposition products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Eye Contact</b>	Causes serious eye irritation.
<b>Skin Contact</b>	Prolonged and frequent contact may cause redness and irritation. Repeated skin contact may cause dermatitis.
<b>Inhalation</b>	Unlikely, due to paste consistency.
<b>Ingestion</b>	May be harmful if swallowed; Ingestion can cause irritation of the upper digestive and respiratory tracts.

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Sodium Silicate 1344-09-8	= 1960 mg/kg ( Rat )	> 4640 mg/kg ( Rabbit )	-
Non-hazardous Ingredients*	> 90 mL/kg ( Rat )	-	-
Carbon Black 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Please see section 4 of this SDS for symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** Not known to be human skin or respiratory sensitizers.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. Carbon black is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Carbon Black 1333-86-4	A3	Group 2B		X

#### Legend

*ACGIH (American Conference of Governmental Industrial Hygienists)*  
*A3 - Animal Carcinogen*  
*IARC (International Agency for Research on Cancer)*  
*Group 2B - Possibly Carcinogenic to Humans*  
*Group 3 IARC components are "not classifiable as human carcinogens"*  
*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*  
*X - Present*

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

**Oral LD50** >2,000 mg/kg  
**Dermal LD50** >2,000 mg/kg

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

PRACTICES SHOULD BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION. Leaching of uncured product into waterways & lakes will be similar to sodium silicate.

**Component Information**

Chemical name	Algae/aquatic plants	Fish	Crustacea
Sodium Silicate 1344-09-8		3185: 96 h Brachydanio rerio mg/L LC50 semi-static 301 - 478: 96 h Lepomis macrochirus mg/L LC50	216: 96 h Daphnia magna mg/L EC50
Carbon Black 1333-86-4			5600: 24 h Daphnia magna mg/L EC50

**Persistence/Degradability**

Not tested for persistence & biodegradability.

**Bioaccumulation**

Not tested for bio-accumulation potential.

**Mobility**

Not tested for mobility in soil

**Other Adverse Effects**

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

**13. DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods**

**Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**14. TRANSPORT INFORMATION**

**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT**

Not regulated

**IATA**

Not regulated

**IMDG**

Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

Chemical name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Sodium Silicate	X	X	X	X	X	X	X	X
CAS #68953-58-52 & #68855-54-9; Silica and Clay Blend	X	X	X	X	X	X	X	X
Non-hazardous Ingredients*	X	X	X	X	X	X	X	X
Silicate, as Perlite		X			X	X	X	X
Carbon Black	X	X	X	X	X	X	X	X

**Legend:**

- TSCA* - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL* - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS* - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS* - Japan Existing and New Chemical Substances
- IECSC* - China Inventory of Existing Chemical Substances
- KECL* - Korean Existing and Evaluated Chemical Substances
- PICCS* - Philippines Inventory of Chemicals and Chemical Substances
- AICS* - Australian Inventory of Chemical Substances

**US Federal Regulations**

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**SARA 313**

Not determined

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Carbon Black - 1333-86-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
CAS #68953-58-52 & #68855-54-9; Silica and Clay Blend			X
Silicate, as Perlite	X	X	X
Carbon Black 1333-86-4	X	X	X

## 16. OTHER INFORMATION

<b><u>NFPA</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	2	0	0	Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical hazards</b>	<b>Personal Protection</b>
	2	0	0	Not determined

**Issue Date:** 19-Aug-2013  
**Revision Date:** 02-Apr-2019  
**Revision Note:** SDS sections updated 2, 4, 9, 11

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**