Red Devil®

MULTI-PURPOSE SPRAY TACK™

Multi-purpose Spray Tack™ is a web patterned spray adhesive with rapid drying and quick-grab technology. This adhesive forms a water-resistant bond for temporary and permanent double-sided applications. Multi-Purpose Spray Tack is formulated without methylene chloride or other hazardous air pollutants and provides long-lasting adhesion on a variety of materials.

FEATURES:

- Fast, Long-Lasting Tack
- High Solids for Increased Coverage
- No Methylene Chloride or NPB
- HAPs Free (Hazardous Air Pollutants)
- Permanent or Temporary Bond
- Adjustable Spray Pattern: 3 – 12 inches
- Water-Resistant Bond
- 50 State Compliant
- Meets & Exceeds SCAQMD Rule 1168

USE ON:

Fiberglass Insulation, Sheathing, Air Ducts, Pipes & More.

ADHERES TO:

Galvanized Steel, Stainless Steel, Aluminum, Fiberglass Duct Liner/ Wrap, Kraft Backed Foils, OSB, Wood, Masonry, Concrete, Drywall/ Gypsum Board, Paper, Cardboard, Fabric, & Carpet.

WATER-RESISTANT BOND

HIGH BONDING STRENGTH

WIDE WEB SPRAY PATTERN

INSTANT TACK

MADE IN THE USA

www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

SPRAY TACK™ MULTI-PURPOSE CLEAR WEB ADHESIVE

PART#	COLOR	SIZE	UPC #	CASE QTY.
0849DI	Natural	27 lbs NET WT.	0-75339-00670-2	1

PHYSICAL & CHEMICAL PROPERTIES:

Solids: 32% +/- 2%
Bonding Range: 3 to 60 Minutes
Dry/Tack Time: 3 - 5 minutes
Application Temperature: 65°F to 90°F (18°C to 32°C)
Spray Pattern: Web
Shelf Life: 15 months in unopened container
Coverage: Approx. 54 sq. ft. @ 2.5g
Clean Up: Mineral Spirits

STORAGE:

Store in a cool, dry, well-ventilated area, out of direct sunlight. Keep canister tightly closed when not in use. Canister should be stored between 65°F and 90°F (16°C to 32°C) and kept off the floor. Do not handle or store near an open flame or other sources of excessive heat.

PRODUCT USAGE:

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Avoid breathing fume/gas/mist/ vapors/ spray. Wash hands and exposed skin areas with soap and warm water thoroughly after handling. Do NOT touch eyes. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Stop leak if safe to do so. Wear eye protection/face protection/protective gloves. Take off contaminated clothing and wash it before reuse. Dispose of contents/ container to a licensed treatment, storage, or disposal facility.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	No
DOT Proper Shipping Name	N.O.S.
DOT Hazzard	Chemical Under Pressure, Flammable
DOT UN/NA Number	3501
Packing Group	2.1
VOC Content	< 80 g/L

APPLICATION:

1. Test adhesive on small area before use to confirm surface compatibility.

2. Prepare surfaces by ensuring they are clean, dry, and free of debris, oil, and grease. Do not wet surfaces. Adhesive can be applied to one or both surfaces.

3. Hold the spray gun 6–10 inches from the surface at a 90° angle. Apply an even web-style coat to cover 80%–95% of the surface without oversaturating or puddling.

4. For porous surfaces, apply a second coat after first coat becomes tacky.

5. Allow adhesive to dry 3–5 minutes, or until tacky with no transfer when touched. Dry time may vary based on temperature, humidity, and airflow.

6. Carefully align surfaces before bonding. Press surfaces together firmly, working from the center outward to remove air pockets and wrinkles.

7. Apply consistent pressure to ensure proper adhesion. The initial bond is repositionable if adjustment is needed.

8. Allow 24–48 hours for full bond strength to develop.

LIMITATIONS:

- Not recommended for use with unbacked plasticized vinyl materials.
- Product is freeze/thaw stable; if material has been exposed to temperatures below 41°F (5°C), allow it to warm to room temperature (72°F / 22°C) and agitate thoroughly prior to use.
- Do not apply or form bonds at material or substrate temperatures below 65°F (18°C), as bond performance may be adversely affected.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: CHEMICAL UNDER PRESSURE: MAY EXPLODE IF HEATED. CAUSES MILD SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. HARMFUL IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF REACH OF CHILDREN & PETS. NOT FOR INTERNAL CONSUMPTION. (See SDS for additional safety information)