

0697/OI Series RD PRO Architectural Grade Butyl Sealant:

- **What is the base chemistry for this product?** Solvent based, Butyl Rubber Architectural Grade Sealant.
- **Is product flammable or combustible?** Yes, formulation contains Mineral Spirits. (See MSDS)
- **Is this formulation Spec Compliant?** Yes – it complies to Fed Spec TT-S-001657, Fed Spec TT-C-00598C & Fed Spec TT-C-001796A.
- **Is product suitable for interior or exterior applications?** Yes, but consult label & MSDS as formula is solvent based & not VOC Compliant.
- **Is product paintable?** Yes, when directions are followed.
- **Does product retain a degree of flexibility after cure?** Yes.
- **Is product suitable for below-grade applications?** Yes, when properly applied.
- **Is product available in colors?** Yes; White & Gray.
- **What are some applications this product was designed for?** Metal windows & doors, siding, gutters, skylights, shingles, flashing, chimneys, downspouts, foundations & many below-grade areas. (Not recommended for underwater applications) (See TDS)
- **What are some limitations of this product?** Requires solvent clean up prior to cure & exhibits a solvent odor during application & cure. Cure time is approximately 7 days & product is combustible. Product is not VOC Compliant, therefore not suitable for sale or use in California, OTC or other regulated areas. (See MSDS)
- **What is the best temperature range for product application?** 40F to 90F to clean, dry substrates (See TDS).
- **Where can additional information be found on this product?** See MSDS & TDS on this website (www.reddevil.com).