

0704/0718 Series Elastomeric Patching Compounds (Smooth & Textured):

- **What is the base chemistry for these products?** Proprietary aqueous emulsion base.
- **Are these EPC's VOC Compliant?** Yes.
- **Do these EPC's contain Prop 65 Ingredients?** Yes – see MSDS's.
- **Do these formulas offer water clean up?** Yes.
- **How much shrinkage should be expected w/ these EPC's?** Minimal shrinkage.
- **What are some substrates on which these EPC's will perform?** Stucco, EIFS, Cinder Block, Concrete, Brick, Drywall, Plaster, Wood, Glass, Non-Ferrous & Primed Ferrous Metals.
- **Appearance of 0704?** Smooth paste w/ excellent application characteristics.
- **Appearance of 0718?** Textured paste w/ excellent application characteristics.
- **Is there an odor present during application & drying?** Yes – mild. No odor @ full cure.
- **Are these EPC's Freeze/Thaw stable?** Yes – 5 cycles.
- **What shelf life should be expected from these EPC's?** Minimum 1 yr, original container – unopened.
- **What tack free time is typical for these EPC's?** < 4 hrs (cooler temps & higher humidity can prolong to 24 hrs or more)
- **What storage temperatures are suggested?** 40F to 90F.
- **What application temps are suggested?** 50F to 90F.
- **What service temperature range should be expected?** Approximately -30F to 180F.
- **Are these EPC's paintable?** Yes, when fully cured.
- **How are these EPC's packaged?** 0704 Smooth – Tub, 0718 Textured – Cartridge.
- **Where can additional information be found on this products?** See MSDS & TDS on this website (www.reddevil.com).