



### **0785 Series Kitchen & Bath Multi-Surface Adhesive Caulk:**

- **What is the base chemistry for this product series?** Proprietary emulsion blend, fortified with silicone.
- **Is 0785 Series VOC Compliant?** Yes. Product suitable for sale in California & OTC areas.
- **Are any Prop 65 Ingredients added to this formulation?** No.
- **What is unique about the 0785 Series surface after cure?** Product cures to a very smooth, more scrubbable surface than many alternative caulks.
- **Is 0785 K&B Series mildew resistant?** Yes. Cured bead is mildew resistant with good housekeeping practices.
- **What is the color of 0785 K&B Series as supplied?** Product available in Bright White, Bisque, Bone & Clear (Clear product applies White & cures Clear within 14 days under normal conditions).
- **Is 0785 Series suitable for water clean up?** Yes.
- **Is 0785 Series paintable?** Yes. White is paintable after 4 to 6 hrs drying in normal conditions (cooler temperatures & higher humidity will prolong drying time). Colors are also paintable after 4 to 6 hrs if desired or paintable @ a future point should room's color scheme change. Clear is paintable after full clarity achieved (approximately 14 days or less).
- **How is the initial appearance of the 0785 Series achieved?** Product manufactured under a unique Vacuumized process.
- **What was the 0785 K&B Series primarily designed to do?** Provide a water resistant seal for interior/exterior applications. Product suitable for use on wood, drywall, metal, concrete, brick, plaster, masonry & tile. Ideal for cracks & joints around windows, doors, trim, molding, baseboards, thresholds, air conditioners & vents.
- **What surface preparation guidelines are recommended when using the 0785 K&B Series?** Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint & old caulking. Bare surfaces should be primed before caulking for best results & application should take place when caulk, air & substrate are 50F to 90F for best results. Mildew can be removed from surface by scrubbing with a solution of 4 oz TSP (Trisodium Phosphate), 1 quart of liquid bleach mixed with 3 quarts of warm water. Protect eyes & hands by wearing goggles & chemical resistant gloves. Thoroughly rinse surface & allow to dry completely before caulking & painting.
- **How long should 0785 Series be protected from rain or water after application?** 72 hrs.
- **What is the consistency of the 0785 K&B Series as supplied?** Smooth, creamy paste.
- **Does the 0785 K&B Series have an odor during application & cure?** Yes, a mild/low odor is present that disappears with full cure.
- **Is the 0785 K&B Series flammable?** No.

- **Is the 0785 K&B Series considered Freeze-Thaw stable?** Yes, although product should be stored in temperatures between 40F & 90F for best results.
- **When does 0785 Series become tack free?** Approximately 1 hour or less (Conditions of cooler temperatures & higher humidity will extend drying time).
- **What is a typical Shore A Durometer Hardness for the 0785 K&B Series?** 60.
- **What is the Service Temperature of 0785 K&B Series after cure?** Approximately 10F to 150F.
- **Is 0785 Series suitable for use on automobiles or for applications below-grade or below waterline?** No.
- **Can 0785 Series be thinned?** No – thinning is not recommended.
- **How can maximum adhesion to substrate be achieved?** Bare surfaces should be primed before caulking.
- **How can a neat, straight bead edge be achieved?** Apply masking tape to both sides of joint (remove immediately after tooling/before initial surface skin forms).
- **What is the standard packaging for the 0785 K&B Series?** 5.5 Fluid Ounce HDPE Squeeze Tube.
- **Where can additional information be found on the 0785 Kitchen & Bath Series?** See MSDS & TDS on this website ([www.reddevil.com](http://www.reddevil.com)).