



0676 Series Multi-Purpose Construction Adhesive:

- **What is the base chemistry for this adhesive series?** Product is a solvent based formulation.
- **Does the formula comply with any specifications?** Yes; ASTM C557.
- **What is the approximate Working Time for the formulation?** Approximately 30 minutes.
- **What is the approximate Drying Time for the formulation?** 24 to 48 hrs depending upon application & conditions.
- **Is the product water resistant?** Yes.
- **Will product work with polystyrene & urethane foams?** Yes; follow directions on label or consult TDS. (DO NOT APPLY TO POLYSTYRENE FOAM WHEN SURFACE OR ADHESIVE TEMPERATURE EXCEEDS 90F)
- **What was this product designed to do?** Product is a multi-purpose adhesive, designed for use w/ Polystyrene & Urethane Foams, Wood Paneling, Drywall, Tub Surrounds, Concrete, Ceramic Tile, Metal, Plastic, Molding & Trim.
- **Is product flammable?** Yes.
- **Should large applications be reinforced with mechanical fasteners/support?** Yes.
- **Is product suitable for continuous water immersion?** No.
- **Is product recommended for use on subfloors?** No.
- **Is product VOC Compliant?** No; See MSDS for additional information. (0677 29 oz cartridge is suitable for sale in California & OTC areas due to container size)
- **Does product contain any Prop 65 Ingredients?** Yes. Formula contains Toluene, a chemical known to the state of California to cause cancer or reproductive harm.
- **What sizes/packaging is available?** Product is available in 3 sizes; a 4 oz metal squeeze tube, a 10.5 oz spiral/lined cartridge & a 29 oz spiral/lined cartridge.
- **What is the recommended clean up solvent prior to cure?** Mineral Spirits or equiv. (follow label directions on Mineral Spirits)
- **What is the product color as supplied?** Cream to Tan.
- **Where can additional information be found on this adhesive product?** See MSDS & TDS on this website (www.reddevil.com).