

**0848 House & Home Restore Window & Door Caulk:**

- **What is the base chemistry of this product?** Acrylic emulsion.
- **Is 0848 a VOC Compliant formulation?** Yes. Product is suitable for sale in California, OTC & other regulated areas.
- **Are any Prop 65 Ingredients used in 0848?** Yes (see MSDS)
- **Is 0848 a water clean up formula?** Yes.
- **Is 0848 suitable for Interior & Exterior applications?** Yes. Exterior applications should be protected from rain or water spray for 72 hrs & product should not be applied when freezing temperatures are expected.
- **What is the color of 0848 as supplied?** White.
- **How much shrinkage should be expected with 0848?** < 30%.
- **What is the recommended temperature range for product application?** 40F to 90F.
- **What tack free time is typical when using 0848?** 30 minutes or less, however higher humidity & cooler temperatures will extend & warmer/arid conditions will reduce tack free time.
- **What is the cure time for a 3/16 inch bead of 0848?** Approximately 72 hrs. Cool/humid conditions will extend & warm/arid conditions will shorten this time.
- **Is 0848 a paintable product?** Yes. Drying time for latex paints generally 2 to 6 hrs depending on climatic conditions & oil based paints can generally be applied after 72 hrs.
- **Is 0848 Freeze-Thaw Stable?** Yes, product will withstand 5 cycles of F/T @ 0 degrees F & 72 degrees F.
- **Does 0848 remain flexible after cure?** Yes.
- **Where can additional information be found on this product?** See MSDS & TDS on this website ([www.reddevil.com](http://www.reddevil.com)).