



# Red Devil

## 100% SILICONE WATERPROOF FLOORING PERIMETER SEALANT

100% Silicone Perimeter Sealant is specially formulated to seal around waterproof flooring installations, including Laminate, LVP, LVT, Engineered Hardwood, and Tile floors. This medium-modulus sealant accommodates for floor swelling or contracting and is designed to blend with all general flooring colors.

### FEATURES:

- Permanent Flexibility
- Superior Adhesion
- Won't Crack, Shrink, or Peel
- 100% Waterproof
- VOC Compliant
- Mildew Resistant When Cured
- Lifetime Durability

### USE ON:

- Expansion Spaces
- Moldings & Trim
- Transitions
- Open Gaps
- Laminate Floors
- LVP & LVT Floors
- Engineered Hardwood Floors
- Tile Floors

### ADHERES TO:

- Vinyl
- Aluminum
- Glass
- Ceramic Tile
- Porcelain Tile
- Fiberglass
- Painted Surfaces
- Water-resistant Composite Board



**WATERPROOF  
BARRIER**



**SUPERIOR  
ADHESION**



**PERMANENTLY  
FLEXIBLE**



**WON'T CRACK,  
SHRINK OR PEEL**



**LIFETIME**



**MADE  
IN THE USA**



Meets or Exceeds Federal Specifications:

- ASTM C920, Class 25



[www.reddevil.com](http://www.reddevil.com)

Customer Service: 1-800-423-3845

Red Devil, Inc.  
4175 Webb Street  
Pryor, OK 74361

# TECHNICAL DATA SHEET

## 100% SILICONE WATERPROOF FLOORING PERIMETER SEALANT

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
082520	Light Wood	10.1 fl. oz (300 mL) Cartridge	0-7533903990-8	4
082525	Medium Wood	10.1 fl. oz (300 mL) Cartridge	0-7533903992-2	4
082545	Dark Wood	10.1 fl. oz (300 mL) Cartridge	0-7533903994-6	4
082550	Medium Gray	10.1 fl. oz (300 mL) Cartridge	0-7533903982-3	4
082555	Dark Gray	10.1 fl. oz (300 mL) Cartridge	0-7533903984-7	4
082570	Dark Mahogany	10.1 fl. oz (300 mL) Cartridge	0-7533903996-0	4

### PHYSICAL & CHEMICAL PROPERTIES:

**Weight Per Gallon:** 8.5 +/- 0.50

**Specific Gravity:** Approx. 1.0 to 1.25

**Total Non-Volatile % Solids (Weight):** > 90%

**Extrudability/Application:** 60 Seconds +/- 10

**Consistency/Appearance:** Smooth, Viscous Paste

**Joint Movement:** Approx. +/- 25%

**Odor:** Low

**Base Polymer:** Siloxane Blend

**Filler/Pigment:** Fumed Silica

**Shore A Hardness:** 23 +/- 3 (ASTM D2340)

**Freeze/Thaw Stability:** Pass 5 Cycles (ASTM C731)

**Shelf Life:** Minimum 1 Year @ 77°F

**Tack Free Time:** < 2 Hours @ 72°F

**Full Cure:** 24 Hours

**Storage Conditions:** Original Container: 40°F to 90°F

**Application Temperature:** 10°F to 100°F (-12°C to 38°C)

**Tooling:** 5 to 10 Minutes

**Low Temperature Flexibility:** Pass

**Service Temperature:** -60°F to 400°F (-51°C to 149°C)

**Clean-Up:** Mineral Spirits

### APPLICATION:

Clean and dry surface of baseboards and floor perimeter. Use a backer rod to fill expansion joint between waterproof flooring and baseboard, if necessary. Clip tip of nozzle off at a 45° angle to desired bead size and puncture the inner seal. Load cartridge into caulking gun and apply sealant to expansion joint or open gap. Run a damp cloth or putty knife flush along the joint or gap for a smooth finish. Clean-up any uncured excess sealant with mineral spirits. Excess cured sealant can be removed with a sharp blade. Cured sealant is not paintable.

### LIMITATIONS:

- Silicone will not adhere to itself, Teflon, Polyethylene, Polypropylene or other sealants.
- Silicone sealant is not paintable. Paint before applying

### LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 3%/wt, < 40 g/L

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)**

 **WARNING: Cancer Risk From Titanium Dioxide Exposure - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**