



Red Devil

BUTYL RUBBER SEALANT

RED DEVIL INDUSTRIAL® Butyl Architectural Grade Sealant is a high performance sealant that is ideal for below grade applications and outdoor jobs requiring a durable, watertight seal. Cured sealant is mildew resistant.

FEATURES:

- Excellent Adhesion to Most Building Surfaces
- Interior & Exterior Use
- Paintable
- Solvent Clean Up
- Mold & Mildew Resistant When Cured
- Suitable for Below Grade Applications

USES:

Formulated for use on Window & Door Frames, Shingles, Chimneys/Roofs, Skylights, Below-grade Areas, Siding, Leaders & More.

ADHERES TO:

Aluminum, Plastic, Stone, Metal, Wood, Marble, Brick & More.



INTERIOR &
EXTERIOR USE



PAINTABLE



MOLD & MILDEW
RESISTANT
WHEN CURED



EXCELLENT
ADHESION

Meets or Exceeds Federal Specifications:

- TT-C-1796A
- A-A-272



MADE
IN THE **USA**



www.reddevil.com

Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

BUTYL RUBBER SEALANT

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
06970I	White	10.1 fl. oz (300 mL) Cartridge	0-75339-00274-2	12
0697GI	Gray	10.1 fl. oz (300 mL) Cartridge	0-75339-00275-9	12

PHYSICAL & CHEMICAL PROPERTIES:

Viscosity (Spindle T-F @ 2.5rpm): 450,000 - 550,000 cps million cps

Specific Gravity: Approx. 1.20 to 1.25

Shore A Hardness: 30 - 35

Consistency/Appearance: Viscous Paste

Tensile Strength: 125 psi

Odor: Solvent

Boeing Flow: Nil

Filler/Pigment: Calcium Carbonate, TiO₂

Bubble Formation: No Bubbles Formed

Tenacity: Pass

Vehicle Migration: Pass

Adhesion: Excellent

Shelf Life: 1 year @ 72°F

Service Temperature: -20°F to 180°F (-29°C to 82°C)

Full Cure Time: 7 to 10 days

Non-Staining: Non-staining when used as recommended

Water Resistance: No voids, cracks, separation

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife or Damp Cloth. Remove excess with a damp cloth before surface skins over.

FOR BEST RESULTS:

- Apply only in well ventilated areas.
- Do not store or use around heat, open flame.
- Store product at or below 80°F.
- Do not use for joints subject to heavy abrasion or wear.
- Prime bare surfaces before caulking.

CLEAN UP:

Use Mineral Spirits Before Cure.

LIMITATIONS:

- Not for use in areas for complete submersion (pool, hot tub, aquarium, marine applications).
- Not recommended for adhering mirrors.
- Not recommended for use in window glazing applications.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See MSDS)
DOT Proper Shipping Name	Hydrocarbons, Liquid, n.o.s.
DOT Hazzard	Class 3
DOT UN/NA Number	UN 3295
Packing Group	PG III
VOC Content	< 106 g/L

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS.

KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: This product can expose you to Titanium Dioxide, Talc, and Carbon Black, which are known to the state of California to cause cancer. For more information go to – www.P65Warnings.ca.gov