



CREATE-A-COLOR®

Create-A-Color® Caulk is a superior sealant that can easily be tinted with latex paint to custom-match the sealant color to fixtures, countertops, tile, walls, and more. It offers excellent adhesion to most surfaces and a long-lasting seal that cures to an ultra-smooth, satin finish that is mildew resistant. This color match caulk is specially formulated to be tinted using the Red Devil® Create-A-Color® Sealant Mixer.

FEATURES:

- Excellent Adhesion
- Easy Mixing With Create A Color Mixers
- Excellent Color Match At 24 Hours
- Water Clean Up
- Low Odor
- 35 Year Durability
- VOC Compliant
- Paintable After Fully Cured

USES:

Formulated for use on Window & Door Frames, Siding, Trim, Baseboards, Countertops, Sinks, Showers, Fixtures & More.

ADHERES TO:

Painted & Unpainted Wood, Plaster/Drywall, Masonry, Ceramic Tile, Aluminum, Glass & More.



EXCELLENT
ADHESION



LOW ODOR



MOLD & MILDEW
RESISTANT
WHEN CURED



Excellent Color
Match After
24 Hours



Meets or Exceeds Federal Specifications:

- Recommended Thrust Ratio: 6:1 & Up



www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

Create A Color® Caulk™

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0409	White	9.4 fl. oz (278 mL) Cartridge	0-75339-10409-5	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 9.0 +/- 0.50

Total Non-Volatile % Solids (Weight): 60 to 65%

Viscosity: Approx. 9 Seconds +/- 2

pH (initial): 8.50 to 9.50

Slump/Sag: < 0.10

Color: White (dries clear w/o paint addition)

Odor: Mild Acrylic

Shrinkage: Less than 50%

Application Temperature Range: 40°F to 90°F (5°C to 32°C)

Color Match w/ Paint: Color Match @ 24 hours (lighter color initially)

Flash Point (T.O.C.): Greater Than 200°F (TOC) - Non-Flammable

Tack Free Time: < 24 Hour

Freeze/Thaw Stability: Passes 5 Cycles (ASTM)

Stain Index: 0

Water Resistance: Excellent (when fully cured)

Crack Resistance: Superior (no cracking @ 5000 hours QUV)

Elongation at Break/Ultimate Tensile: 500% minimum

Service Temperature: 0°F to 180°F (-17°C to 82°C)

Clean-Up: Water

Tensile Strength at Break: <10 psi

25% Extention Recovery (ASTM C-735): Approx. 98%

Coverage: Approx. 50 linear feet/cartridge (3/16" bead)

Shelf Life: Minimum 1 Year unopened @ 72°F

Storage Conditions: 40°F to 90°F (5°C to 32°C)

Standard Container: Clear Plastic Cartridge

APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Protect eyes & hands by wearing goggles & chemical resistant gloves. Thoroughly rinse surface & allow to dry completely before proceeding.

FOR BEST RESULTS:

- Surface should be clean & free of contaminants.
- Apply enough caulk for the job & do not remove too much material when tooling.
- For a neat, straight bead edge, mask both sides of joint with masking tape; remove tape before skin forms.
- Do not apply when rain or freezing temperatures are expected.
- Final mixer stroke should be very, very slow & w/o rotation in order to remove large air pops from color-matched caulk.
- Remember to puncture seal after cutting nozzle tip.

CLEAN-UP:

Clean equipment immediately after use with water. Wash skin with warm water & mild soap.

LIMITATIONS:

- Not recommended for use in marine applications, below grade, automobiles or aquariums.
- Protect from water until cured (72 Hours) - Cooler temperatures & higher humidity will extend cure time.
- Protect from freezing.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 0.5%/wt, < 10 g/L

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS.

KEEP FROM FREEZING. (See SDS for additional safety information)

⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide and Carbon Black Exposure - www.P65Warnings.ca.gov