



# Red Devil

## DURAGUARD™ Kitchen & Bath

Kitchen & Bath Siliconized Acrylic Caulk is an advanced formula fortified with silicone for long-lasting flexibility and excellent adhesion to ensure a protective barrier against moisture. It provides a watertight seal around kitchen and bath fixtures and cures to an ultra smooth, satin finish.

### FEATURES:

- Provides a Durable, Watertight Seal
- Low VOC
- Will Not Crack, Shrink or Peel
- Paintable
- Excellent Adhesion to Many Surfaces
- Mold & Mildew Resistant
- Water Clean Up

### USES:

Formulated for use on Bathroom Installation/Sealing, Tubs & Tile, Countertops, Trimwork, Cabinets, Siding, Crown Molding, Baseboards & More.

### ADHERES TO:

Wood, Ceramic, Tile, Porcelain, Marble, Glass, Plastic, Vinyl, Metal, Fiberglass & More.



MOLD & MILDEW  
RESISTANT  
WHEN CURED



MULTI-SURFACE  
ADHESION



ASTM C920  
PERFORMANCE



WATER  
CLEAN-UP



PAINTABLE

Meets or Exceeds Federal Specifications:

- ASTM C920, Class 25 (White)
- ASTM C920, Class 12.5 (Clear)
- ASTM C834
- TT-S-00230C Class A



MADE  
IN THE USA



[www.reddevil.com](http://www.reddevil.com)

Customer Service: 1-800-423-3845

Red Devil, Inc.  
4175 Webb Street  
Pryor, OK 74361

# TECHNICAL DATA SHEET

## KITCHEN AND BATH SILICONIZED ACRYLIC CAULK

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0405	White	5.5 fl. oz (163 mL) Tube	0-75339-00405-0	12
040520	Almond	5.5 fl. oz (163 mL) Tube	0-75339-04052-2	12
0406	White	10.1 fl. oz (300 mL) Cartridge	0-75339-00406-7	12
040620	Almond	10.1 fl. oz (300 mL) Cartridge	0-75339-02406-5	12
0408	Clear	10.1 fl. oz (300 mL) Cartridge	0-75339-04080-5	12
0445	Clear	5.5 fl. oz (163 mL) Tube	0-75339-04450-6	12

### PHYSICAL & CHEMICAL PROPERTIES:

**Weight Per Gallon:** 13 +/-1

**Specific Gravity:** 1.43 to 1.68

**Slump:** 0

**Total Non-Volatile % Solids (Weight):** 79% +/-2

**Extrudability/Application:** 8 seconds +/-2

**Joint Movement:** +/- 25%

**Odor:** Mild

**Elongation:** 300% +/-100

**Base Polymer:** Siliconized Acrylic Emulsion

**Filler/Pigment:** Calcium Carbonate

**Flash Point:** None

**Tooling Time:** 10 minutes

**Slump:** 24 hrs. (Colors)/<72 Hours (Clear)

**Shore A Hardness:** 29 +/-10

**Freeze/Thaw Stability:** Pass 5 Cycles (ASTM C731)

**Shelf Life:** Minimum 1 Year @ 72°F

**Tack Free Time:** <1 Hour

**Paintability:** Paintable

**Storage Conditions:** Cool, Dry Place

**Consistency/Appearance:** Smooth, Paste

**Application Temperature:** 40°F to 100°F (5°C to 32°C)

**Service Temperature:** -20°F to 180°F (-34°C to 82°C)

**Low-Temperature Flexibility:** Pass (ASTM C734)

**Mildew Resistance:** Excellent

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5 % by weight, < 1 g/L

### APPLICATION:

Remove old caulking/sealant. Clean, dry & remove any loose material, from the surface, that may interfere with adhesion, including dirt, debris, oil, and residue. Cut the nozzle tip to the desired bead size at a 45° angle. Load the cartridge into a standard-sized caulking gun and apply sealant to the gap or joint. Smooth sealant using a damp cloth or finishing tool for a professional finish. Remove excess sealant with a damp cloth before it skins over. Clean up excess uncured caulk with damp sponge. After cure, remove excess with razor blade.

### FOR BEST RESULTS:

- Store at temperatures above freezing.
- Joint width should not exceed 3". If joint depth exceeds ½", use a backer rod.
- Store away from extreme heat or cold 40°F

### LIMITATIONS:

- Not recommended for use on automotives, fish tanks/aquariums.
- Not recommended for below waterline or below-grade applications.
- Should not be exposed to rain or freezing temperatures within 72 hours of application - Cooler temperatures & higher humidity will extend the cure time.

### CLEAN-UP:

Clean tools immediately w/water. Wash skin with mild soap and water.

### LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)**

**⚠ WARNING: Reproductive Harm Risk from Ethylene Glycol & Cancer Risk From Titanium Dioxide Exposure - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**