



Red Devil

Kitchen & Bath

Siliconized Adhesive Caulk

Kitchen & Bath Siliconized Adhesive Caulk is an advanced formula fortified with silicone for long-lasting flexibility and excellent adhesion to ensure a protective barrier against moisture. It provides a waterproof seal around kitchen and bath fixtures and cures to an ultra smooth, satin finish.

FEATURES:

- Provides a Durable, Waterproof Seal
- Will Not Crack, Shrink or Peel
- Satin Finish
- Paintable
- Scrub Resistant
- Low Odor & Low VOC
- Mold & Mildew Resistant When Cured
- Easy Water Clean Up

USES:

Formulated for Installing and Sealing Countertops, Vanities, Bathtubs, Showers, Sinks, Spashboards, Trimwork, Cabinets, Siding, Baseboards, and other Kitchen & Bath Fixtures.

ADHERES TO:

Wood, Ceramic & Porcelain Tile, Marble, Glass, Plastic, Vinyl, Metal, Fiberglass & More.



Meets or Exceeds Specifications:

- ASTM C920, Class 12.5 (Clear)
- ASTM C834



MOLD & MILDEW
RESISTANT
WHEN CURED



MULTI-SURFACE
ADHESION



WON'T CRACK,
SHRINK OR PEEL



WATER
CLEAN-UP



PAINTABLE



MADE
IN THE USA



www.reddevil.com

Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

KITCHEN AND BATH SILICONIZED ADHESIVE CAULK

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0405	White	5.5 fl. oz (163 mL) Squeeze Tube	0-75339-00405-0	12
040520	Almond	5.5 fl. oz (163 mL) Squeeze Tube	0-75339-04052-2	12
0406	White	10.1 fl. oz (300 mL) Cartridge	0-75339-00406-7	12
040620	Almond	10.1 fl. oz (300 mL) Cartridge	0-75339-02406-5	12
0408	Clear	10.1 fl. oz (300 mL) Cartridge	0-75339-04080-5	12
0445	Clear	5.5 fl. oz (163 mL) Squeeze Tube	0-75339-04450-6	12

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 13 +/-1

Specific Gravity: 1.43 to 1.68

Slump: 0

Total Non-Volatile % Solids (Weight): 79% +/-2

Extrudability/Application: 8 seconds +/-2

Joint Movement: +/- 12.5% (Clear)

Elongation: 300% +/-100

Base Polymer: Siliconized Acrylic Emulsion

Filler/Pigment: Calcium Carbonate

Tooling Time: 10 minutes

Slump: 24 hrs. (Colors)/<72 Hours (Clear)

Shore A Hardness: 29 +/-10

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Minimum 1 Year @ 72°F

Tack Free Time: <1 Hour

Paint Over Time: 2 hrs. (White & Colors), 72 hrs. (Clear)

Full Cure: 24 hrs. (White & Colors), 72 hrs. (Clear)

Storage Conditions: Cool, Dry Place

Consistency/Appearance: Smooth, Paste

Application Temperature: 50°F to 90°F (10°C to 32°C)

Service Temperature: -20°F to 180°F (-34°C to 82°C)

Low-Temperature Flexibility: Pass (ASTM C734)

VOC Content: < 25 g/L (White & Colors), < 10 g/L (Clear)

APPLICATION:

Remove old caulk from surface. Clean and dry area thoroughly to remove dust and grease. Cut the nozzle tip to the desired bead size at a 45° angle. Load the cartridge into a standard-sized caulking gun and apply sealant to the gap or joint. Smooth caulk with a putty knife or finishing tool for a professional finish. Remove excess sealant with a damp cloth before it skins over. Protect from water for 24 hours.

FOR BEST RESULTS:

- Store at temperatures above freezing.
- Joint width should not exceed 3". If joint depth exceeds 1/2", use a backer rod.
- If caulking around bathtub, fill with water first.

LIMITATIONS:

- Not recommended for use on automotives, fish tanks/aquariums.
- Not recommended for below waterline or below-grade applications.
- Should not be exposed to rain or freezing temperatures within 24 hours of application - Cooler temperatures & higher humidity will extend the cure time.

CLEAN-UP:

Clean tools immediately w/water. Wash skin with mild soap and water.

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)

FOR PRODUCT SKUS: 0405, 040520, 0406, 040620

⚠ WARNING: Reproductive Harm Risk from Ethylene Glycol & Cancer Risk From Titanium Dioxide Exposure - www.P65Warnings.ca.gov