



MULTI-PURPOSE SPRAY TACK™

Multi-purpose Spray Tack™ is a VOC compliant high-strength, high shear adhesive with rapid drying and quick-grab technology. This adhesive forms a water-resistant bond for temporary or permanent double-sided applications and provides long-lasting tack on a variety of materials.

FEATURES:

- Fast, Long-Lasting Tack
- Permanent or Temporary Bond
- Adheres to Multiple Substrates
- Water-Resistant Bond
- VOC Compliant
- Meets SCAQMD Rule 1168

USE ON:

Duct Liners/Wraps, Pipes, Insulation, Boards/Panels, Upholstery, Carpet, Underlayment & More.

ADHERES TO:

Galvanized Steel, Stainless Steel, Aluminum, Fiberglass, Wood, Paper, Cardboard, Fabric, Leather, and a variety of other substrates.



MULTI-SURFACE
APPLICATION



HIGH BONDING
STRENGTH



WIDE WEB
SPRAY PATTERN



INSTANT TACK



www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

SPRAY TACK™ MULTI-PURPOSE CLEAR WEB ADHESIVE

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0843DI	Natural	12 oz. (340 g) Canister	0-75339-00510-0	12

PHYSICAL & CHEMICAL PROPERTIES:

Solids: 26% +/- 2%

Bonding Range: 3-60 minutes

Dry/Tack Time: 3 - 5 minutes

Application Temperature: 65°F to 90°F (18°C to 32°C)

Spray Pattern: Web

Shelf Life: 12 months in unopened container

Clean Up: Mineral Spirits

STORAGE:

Store in a cool, dry, well-ventilated area, out of direct sunlight. Canister should be stored between 60°F and 90°F (16°C to 32°C) and kept off the floor. Do not handle or store near an open flame or other sources of excessive heat.

PRODUCT USAGE:

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Avoid breathing fume/gas/mist/ vapors/ spray. Wash hands and exposed skin areas with soap and warm water thoroughly after handling. Do NOT touch eyes. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Stop leak if safe to do so. Wear eye protection/face protection/protective gloves. Take off contaminated clothing and wash it before reuse. Dispose of contents/ container to a licensed treatment, storage, or disposal facility.

APPLICATION:

1. Test adhesive on small area before use to confirm surface compatibility.
2. Prepare surfaces by ensuring they are clean, dry, and free of debris, oil, and grease. Do not wet surfaces. Adhesive can be applied to one or both surfaces.
3. Hold the spray canister 6–10 inches from the surface at a 90° angle. Apply an even web-style coat to cover 85%–95% of the surface without oversaturating or puddling.
4. For porous surfaces, apply a second coat after first coat becomes tacky.
5. Allow adhesive to dry 3–5 minutes, or until tacky with no transfer when touched. Dry time may vary based on temperature, humidity, and airflow.
6. Carefully align surfaces before bonding. Press surfaces together firmly, working from the center outward to remove air pockets and wrinkles.
7. Apply consistent pressure to ensure proper adhesion. The initial bond is repositionable if adjustment is needed.
8. Allow 24 hours for full bond strength to develop.

LIMITATIONS:

- Product is freeze/thaw stable; if material has been exposed to temperatures below 41°F (5°C), allow it to warm to room temperature (72°F / 22°C) and agitate thoroughly prior to use.
- Do not apply or form bonds at material or substrate temperatures below 65°F (18°C), as bond performance may be adversely affected.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes
DOT Proper Shipping Name	Aerosols
DOT Hazzard	Flammable gases
DOT UN/NA Number	UN1950
Packing Group	2.1
VOC Content	292 g/L

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CAUTION: EXTREAMLY FLAMMABLE. CHEMICAL UNDER PRESSURE: MAY EXPLODE IF HEATED. CAUSES MILD SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. HARMFUL IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF REACH OF CHILDREN & PETS. NOT FOR INTERNAL CONSUMPTION. (See SDS for additional safety information)

⚠ WARNING: Risk of Reproductive Harm from HEXANE Exposure - www.P65Warnings.ca.gov