



# Red Devil

## PRE-MIXED TILE GROUT

Pre-mixed Tile Grout is a water-resistant unique grouting composition that provides professional quality on ceramic and mosaic tile projects with do-it-yourself ease. It is formulated with premium acrylic latex for a user-friendly consistency, improved durability, and mildew resistance

### FEATURES:

- Pre-Mixed & Ready to Use
- Tack-Free in 30 Minutes
- Stain & Water Resistant
- Won't Shrink or Crack
- Excellent Adhesion
- Mildew Resistant Once Cured
- Easy Water Clean Up
- Low Odor & Low VOC

### ADHERES TO:

Masonry, Glass, Wood, Drywall

### USE ON:

Ceramic, Porcelain, Mosaic,  
Marble, Granite, Stone, Glass



PRE-MIXED  
READY TO USE



STAIN & WATER  
RESISTANT



TACK-FREE  
IN 30 MIN



WON'T SHRINK  
OR CRACK



WATER  
CLEAN UP



MADE  
IN THE **USA**



[www.reddevil.com](http://www.reddevil.com)

[www.fixafloorworldwide.com](http://www.fixafloorworldwide.com)

Customer Service: 1-800-423-3845

Red Devil, Inc.  
4175 Webb Street  
Pryor, OK 74361

# TECHNICAL DATA SHEET

## PRE-MIXED TILE GROUT

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0422	White	1/2 Pint Tub	0-75339-00422-7	12
042260	Black	1/2 Pint Tub	0-75339-01552-0	12
0424	White	1 Quart Tub	0-75339-00424-1	6
0425	White	5.5 fl. oz Squeeze Tube	0-75339-00425-8	12
0428	White	1 Pint Tub	0-75339-00428-9	12

### PHYSICAL & CHEMICAL PROPERTIES:

**Weight Per Gallon:** 13.50

**Specific Gravity:** 1.62

**Total Non-Volatile % Solids (Weight):** 85.0%

**Viscosity:** 75,000 cps

**Consistency:** Paste

**pH (initial):** 9.50

**Base Polymer:** Acrylic Latex Emulsion Blend

**Flash Point:** >200°F

**Freeze/Thaw:** Pass 3 cycles (0°F/77°F @ 24 hours)

**Shelf Life:** 12 months @ 72°F

**Storage Temperature:** 40°F to 90°F (4°C to 32°C)

**Application Temperature:** 55°F to 90°F (13°C to 32°C)

**Tack Free Time:** Approx. 30 minutes

**Full Cure Time:** 24-48 hours

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5 % by weight, < 40 g/L

### APPLICATION:

Remove 1/16" of old grout with a grout rake or chisel, and disinfect the application area to prevent mildew growth. Scrub surface with a wet sponge or brush, then wipe dry with a cloth to remove any loose debris or contaminants. Remove cap, cut nozzle tip at a 45° angle to desired size, matching the width of the joint. Squeeze tube directly into each joint and smooth over with a grout float or damp cloth. For best results, work in areas approximately 4 square feet at a time and apply when surface, air, and material temperatures are > 55°F. Wait 15 minutes for the tile grout to set, then remove excess grout with a damp sponge or cloth. Allow tile grout to dry for 1 hour, then buff surface with a clean, dry cloth. Let grout fully cure for 48 hours before exposing to water, traffic, or grout sealer. Cure time may be longer in areas of high humidity.

### FOR BEST RESULTS:

- Don't apply when surfaces/air/material temperature is < 55°F
- Apply in properly ventilated areas.
- Allow full cure before subjecting to water exposure.
- Allow full cure before applying any type of grout sealer

### LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)**

**⚠ WARNING: Cancer Risk and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**