



# Red Devil

# Speed Demon®

Speed Demon® Acrylic Caulk is a general purpose, acrylic latex caulk that applies easily and dries quickly. It can be used indoors or outdoors on masonry, painted and unpainted wood, and most siding.

## FEATURES:

- Water Clean-Up
- Easy Application & Tooling
- Paintable
- Interior & Exterior Use
- VOC Compliant
- HomeShield™ Antimicrobial Protection
- Interior/Exterior Use

## USES:

Formulated for use on Interior Windows, Doors, Trim, Baseboards, Molding & More.

## ADHERES TO:

Painted & Unpainted Wood, Brick, Plaster, Drywall, Masonry & More.



INTERIOR &  
EXTERIOR USE



PAINTABLE



VOC COMPLIANT



WATER  
CLEAN-UP

Meets or Exceeds Federal Specifications:

- Recommended Thrust Ratio 6:1 & Up



MADE  
IN THE **USA**



[www.reddevil.com](http://www.reddevil.com)

Customer Service: 1-800-423-3845

Red Devil, Inc.  
4175 Webb Street  
Pryor, OK 74361

# TECHNICAL DATA SHEET

## SPEED DEMON® ACRYLIC LATEX CAULK

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0736	White	10.1 fl. oz (300 mL) Cartridge	0-75339-00736-5	12

### PHYSICAL & CHEMICAL PROPERTIES:

**Weight Per Gallon:** 13.5 +/- 1.50

**Total Non-Volatile % Solids (Weight):** > 78% +/-2%

**Specific Gravity:** Approx. 1.40 to 1.80

**Extrudability/Application:** 300,000 to 400,000 cps

**Consistency/Appearance:** Smooth, Creamy Paste

**pH (initial):** 7 to 10

**Odor:** Mild

**Base Polymer:** Aqueous Emulsion

**Filler/Pigment:** Calcium Carbonate

**Freeze/Thaw Stability:** Passes 3 Cycles (ASTM)

**Shelf Life:** Expect 1 Year @ 72°F

**Tack Free Time:** < 1 Hour @ 72°F

**Full Cure:** 72 Hours

**Storage Conditions:** 40°F to 90°F (5°C to 32°C)

**Application Temperature:** 40°F to 90°F (5°C to 82°C)

**Tooling:** Excellent

**% Elongation:** 200%

**Service Temperature:** 0°F to 160°F (-18°C to 71°C)

**Coverage:** 50-55 Linear Feet (3/16" Bead)

### APPLICATION:

Remove old caulking/sealant. Surface must be clean, dry & free from dirt, dust, grease, oil, mildew, wax, loose paint, frost, & other residue or material that may interfere with adhesion. Clip off tip of nozzle/spout @ 45° angle to desired bead size. Load cartridge into caulking gun and apply. Smooth caulk using a Caulk Smoother, Putty Knife or Damp Cloth. Remove excess with a damp cloth before surface skins over. Full clarity reached in 1 to 2 weeks.

### FOR BEST RESULTS:

- Joint size should not exceed 3/8". If joint depth exceeds 3/8", use a backer rod.
- Prime bare surfaces before caulking.
- Store at temperatures above freezing and below 90°F
- Do not overtool.

### CLEAN-UP:

Mild Soap and Water.

### LIMITATIONS:

- Not recommended for underwater applications.
- Not recommended for use on fish tanks/aquariums.
- Not recommended for use on mirrors.
- Protect from rain/water exposure for 72 hours.
- Apply only to clean, dry substrates.

### LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See SDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazzard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	< 1.5%/wt, < 25 g/L

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)**

**⚠ WARNING: Risk of Cancer and Reproductive Harm From Titanium Dioxide and Carbon Black Exposure - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**