



## Fixture Caulk Strip 0152

# Technical Data Sheet

### Description

A self-adhesive butyl based decorative trim white caulk strip for bathroom fixture applications. Product pre-shaped for easy installation. NEW & IMPROVED ADHESION.

### Key Features

- Excellent White Color
- Easy to Use
- Improved Adhesion
- Excellent Stain Resistance
- Typically Cures Fully in 24 hrs
- Cured Strip Mildew Resistant

### Uses

Use to bridge small gaps in bathroom fixture applications, such as between fixture & floor or fixture & wall.

### Surface Preparation

Surface should be sound, clean & dry prior to application.

### Directions

1. Remove from package & apply by pressing into place according to label instructions.

<u>Physical/Performance Property</u>	<u>Test Method</u>	<u>Typical Result</u>
<b>Total Non Volatile % Solids (Weight)</b>	<b>Computrac Analyzer</b>	<b>100%</b>
<b>Consistency/Appearance</b>	<b>Visual Observation</b>	<b>White Caulk Strip</b>
<b>Odor</b>	<b>Subjective</b>	<b>Mild</b>
<b>Base Polymer</b>	<b>Known</b>	<b>Butyl Rubber</b>
<b>Pigment</b>	<b>Known</b>	<b>Calcium Carbonate/TiO2</b>
<b>Freeze/Thaw Stability</b>	<b>Test Lab 0 F/77 F @24 hrs or ASTM C731</b>	<b>Passes 5 Cycles</b>
<b>Shelf Life</b>	<b>Lab 50 C Oven – Accelerated</b>	<b>Minimum 2 yrs in original container @ 77F</b>
<b>Tack Free Time</b>	<b>ASTM D2377</b>	<b>8 hours</b>
<b>Full Cure</b>	<b>Test Lab</b>	<b>24 hours</b>
<b>Shore A Hardness</b>	<b>ASTM D2240</b>	<b>12</b>
<b>Storage Conditions</b>	<b>Test Lab</b>	<b>40F to 90F</b>
<b>Application Temperature</b>	<b>Test Lab</b>	<b>60F to 90F</b>
<b>Toxicity</b>	<b>Document Review</b>	<b>Non-toxic when used as directed</b>
<b>Stain Resistance</b>	<b>Test Lab</b>	<b>No Color Change</b>
<b>Water Resistance (full cure)</b>	<b>Test Lab</b>	<b>Excellent</b>
<b>Crack Resistance (full cure)</b>	<b>Test Lab</b>	<b>No crack</b>
<b>Peel Strength (Glass @ 24 hr cure)</b>	<b>Instron</b>	<b>5 lbs/inch</b>
<b>Clean Up Solvent (before cure)</b>	<b>Test Lab</b>	<b>Mineral Spirits</b>
<b>Standard Packaging</b>	<b>Known</b>	<b>Plastic Clam Shell</b>
<b>VOC Content</b>	<b>Calculated</b>	<b>12% by weight</b>
<b>Paintability</b>	<b>Test Lab</b>	<b>Excellent @ Full Cure</b>
<b>Mildew Resistance</b>	<b>Test Lab</b>	<b>Excellent (cured product)</b>

**Clean Up**

Mineral Spirits prior to cure.

**Color**

White

**For Best Results**

- Apply only to sound, clean, dry substrates.
- Apply between 60F & 90F.

**Packaging**

Plastic Clam Shell

**Limitations**

- May remain tacky for up to 8 hrs.
- Solvent Clean Up.

**Environmental, Safety & Transportation Information**

<u>Criteria</u>	<u>Evaluation Method</u>	<u>Status</u>
<i>CARB Compliance</i>	<i>Documents Review</i>	<i>No</i>
<i>Prop 65 Ingredients</i>	<i>Documents Review</i>	<i>None</i>
<i>DOT Proper Shipping Name</i>	<i>Review of Regs</i>	<i>Not Regulated</i>
<i>DOT Hazard</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>DOT UN/NA Number</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>Packing Group</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>VOC Content</i>	<i>Calculated</i>	<i>Approx. 12% by weight.</i>

**CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. (See MSDS for additional information)**

**LIMITED WARRANTY**

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used packaging. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

TDS Number: 0152TD

Date of Issue: January 20, 2010

SEE MSDS FOR ADDITIONAL DATA/INFORMATION