



Technical Data Sheet

Wall & Counter Caulk Strip 0155

Description

A self-adhesive butyl based decorative trim white caulk strip for kitchen & bathroom wall & counter applications. Product pre-shaped for easy installation. NEW & IMPROVED ADHESION.

Key Features

- Excellent White Color
- Easy to Use
- Improved Adhesion
- Excellent Stain Resistance
- Typically Cures Fully in 24 hrs
- Cured Strip Mildew Resistant

Uses

Use to bridge small gaps in kitchen & bathroom wall & counter applications, such as between fixture & floor, fixture & wall or counter & wall.

Surface Preparation

Surface should be sound, clean & dry prior to application.

Directions

1. Remove from package & apply by pressing into place according to label instructions.

<u>Physical/Performance Property</u>	<u>Test Method</u>	<u>Typical Result</u>
Total Non Volatile % Solids (Weight)	Computrac Analyzer	100%
Consistency/Appearance	Visual Observation	White Caulk Strip
Odor	Subjective	Mild
Base Polymer	Known	Butyl Rubber
Pigment	Known	Calcium Carbonate/TiO2
Freeze/Thaw Stability	Test Lab 0 F/77 F @24 hrs or ASTM C731	Passes 5 Cycles
Shelf Life	Lab 50 C Oven – Accelerated	Minimum 2 yrs in original container @ 77F
Tack Free Time	ASTM D2377	8 hours
Full Cure	Test Lab	24 hours
Shore A Hardness	ASTM D2240	12
Storage Conditions	Test Lab	40F to 90F
Application Temperature	Test Lab	60F to 90F
Toxicity	Document Review	Non-toxic when used as directed
Stain Resistance	Test Lab	No Color Change
Water Resistance (full cure)	Test Lab	Excellent
Crack Resistance (full cure)	Test Lab	No crack
Peel Strength (Glass @ 24 hr cure)	Instron	5 lbs/inch
Clean Up Solvent (before cure)	Test Lab	Mineral Spirits
Standard Packaging	Known	Plastic Clam Shell
VOC Content	Calculated	12% by weight
Paintability	Test Lab	Excellent @ Full Cure
Mildew Resistance	Test Lab	Excellent (cured product)

Clean Up

Mineral Spirits prior to cure.

Color

White

For Best Results

- Apply only to sound, clean, dry substrates.
- Apply between 60F & 90F.

Packaging

Plastic Clam Shell

Limitations

- May remain tacky for up to 8 hrs.
- Solvent Clean Up.

Environmental, Safety & Transportation Information

<u>Criteria</u>	<u>Evaluation Method</u>	<u>Status</u>
<i>CARB Compliance</i>	<i>Documents Review</i>	<i>No</i>
<i>Prop 65 Ingredients</i>	<i>Documents Review</i>	<i>None</i>
<i>DOT Proper Shipping Name</i>	<i>Review of Regs</i>	<i>Not Regulated</i>
<i>DOT Hazard</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>DOT UN/NA Number</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>Packing Group</i>	<i>Review of Regs</i>	<i>N/A</i>
<i>VOC Content</i>	<i>Calculated</i>	<i>Approx. 12% by weight.</i>

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. (See MSDS for additional information)

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used packaging. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

TDS Number: 0155TD

Date of Issue: January 20, 2010

SEE MSDS FOR ADDITIONAL DATA/INFORMATION