



Technical Data Sheet

Tub & Floor Caulk Strip 0170 Series White & Almond

Description

A self-adhesive butyl based decorative trim caulk strip for tub & floor applications. Product pre-shaped for easy installation.
NEW & IMPROVED ADHESION.

Key Features

- Excellent White Color
- Easy to Use
- Improved Adhesion
- Excellent Stain Resistance
- Typically Cures Fully in 24 hrs
- Cured Strip Mildew Resistant

Uses

Use to bridge small gaps between bathtub & floor.

Surface Preparation

Surface should be sound, clean & dry prior to application.

Directions

1. Remove from package & apply by pressing into place according to label instructions.

<u>Physical/Performance Property</u>	<u>Test Method</u>	<u>Typical Result</u>
<i>Total Non Volatile % Solids (Weight)</i>	<i>Computrac Analyzer</i>	<i>100%</i>
<i>Consistency/Appearance</i>	<i>Visual Observation</i>	<i>White or Almond Caulk Strip</i>
<i>Odor</i>	<i>Subjective</i>	<i>Mild</i>
<i>Base Polymer</i>	<i>Known</i>	<i>Butyl Rubber</i>
<i>Pigment</i>	<i>Known</i>	<i>Calcium Carbonate/TiO2</i>
<i>Freeze/Thaw Stability</i>	<i>Test Lab 0 F/77 F @24 hrs or ASTM C731</i>	<i>Passes 5 Cycles</i>
<i>Shelf Life</i>	<i>Lab 50 C Oven – Accelerated</i>	<i>Minimum 2 yrs in original container @ 77F</i>
<i>Tack Free Time</i>	<i>ASTM D2377</i>	<i>8 hours</i>
<i>Full Cure</i>	<i>Test Lab</i>	<i>24 hours</i>
<i>Shore A Hardness</i>	<i>ASTM D2240</i>	<i>12</i>
<i>Storage Conditions</i>	<i>Test Lab</i>	<i>40F to 90F</i>
<i>Application Temperature</i>	<i>Test Lab</i>	<i>60F to 90F</i>
<i>Toxicity</i>	<i>Document Review</i>	<i>Non-toxic when used as directed</i>
<i>Stain Resistance</i>	<i>Test Lab</i>	<i>No Color Change</i>
<i>Water Resistance (full cure)</i>	<i>Test Lab</i>	<i>Excellent</i>
<i>Crack Resistance (full cure)</i>	<i>Test Lab</i>	<i>No crack</i>
<i>Peel Strength (Glass @ 24 hr cure)</i>	<i>Instron</i>	<i>5 lbs/inch</i>
<i>Clean Up Solvent (before cure)</i>	<i>Test Lab</i>	<i>Mineral Spirits</i>
<i>Standard Packaging</i>	<i>Known</i>	<i>Plastic Clam Shell</i>
<i>VOC Content</i>	<i>Calculated</i>	<i>12% by weight</i>
<i>Paintability</i>	<i>Test Lab</i>	<i>Excellent @ Full Cure</i>
<i>Mildew Resistance</i>	<i>Test Lab</i>	<i>Excellent (cured product)</i>

Clean Up

Mineral Spirits prior to cure.

Color

White or Almond

For Best Results

- Apply only to sound, clean, dry substrates.
- Apply between 60F & 90F.

Packaging

Plastic Clam Shell

Limitations

- May remain tacky for up to 8 hrs.
- Solvent Clean Up.

Environmental, Safety & Transportation Information

<u>Criteria</u>	<u>Evaluation Method</u>	<u>Status</u>
CARB Compliance	Documents Review	No
Prop 65 Ingredients	Documents Review	None
DOT Proper Shipping Name	Review of Regs	Not Regulated
DOT Hazard	Review of Regs	N/A
DOT UN/NA Number	Review of Regs	N/A
Packing Group	Review of Regs	N/A
VOC Content	Calculated	Approx. 12% by weight.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. (See MSDS for additional information)

LIMITED WARRANTY

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used packaging. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

TDS Number: 0170TD Series

Date of Issue: January 20, 2010

SEE MSDS FOR ADDITIONAL DATA/INFORMATION