## <u>0750, 0750/22, 0755, 0755/22, 0757, 0765 Series DuraGuard Plus Premium Siliconized Adhesive Caulk – White, Clear & Biscuit</u>

- What is the base chemistry of the DuraGuard Plus? Proprietary aqueous emulsions including styrenated acrylic blends.
- Is this series VOC Compliant? Yes.
- Does this product series contain any Prop 65 Ingredients? Yes see MSDS.
- Do these formulas offer water clean up? Yes.
- Are these formulas paintable? Yes.
- Do these products remain flexible after cure? Yes.
- Are these formulas considered mildew resistant? Yes they include the HomeShield antimicrobial package good housekeeping practices will maximize resistance.
- What is the product consistency as supplied? Smooth, creamy paste.
- What colors are available in the DuraGuard series? Clear, White & Biscuit.
- **Is any odor present during application & cure?** Yes a very mild odor is present; no detectable odor @ full cure.
- **Are any of these formulas flammable?** No all are waterborne w/ flash points > 200F.
- What packaging is available? Cartridge & squeeze tube
- What is the recommended temperature range for product application? 40F to 90F
- What is the expected Service Temperature Range? -20F to 180F.
- What are some typical uses for these products? Countertops, vanities, fixtures, sinks, tubs, splashboards.
- Where can additional information be found on these products? See MSDS & TDS on this website (www.reddevil.com).