

SAFETY DATA SHEET

Issue Date 11-Mar-2013 Revision Date 07-Jul-2022 Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name Kitchen & Bath Stain Block™ - White & Colors

Other Means of Identification

SDS # RD-0157 KB

Product Code 0750 Series: 0750, 075022, 0755, 075522, 0758

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Premium Kitchen & Bath Sealant, w/ added benefit of enhanced stain resistance – offers

water clean-up.

Details of the Supplier of the Safety Data Sheet

Supplier Address Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com

Emergency Telephone Number

Company Phone Number 918-825-5744

Fax: 918-825-5761

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

The product contains no substances which at their given concentration, are considered to be hazardous to health

Appearance White & Biscuit; paste. Cartridges & Squeeze tubes

Physical State Smooth paste

Odor Mild acrylic

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% |
|----------------------------|-------------|----------|
| Emulsion Blend | MIXTURE | <90 |
| Non-hazardous Ingredients* | Proprietary | <9 |
| Coalescent | 25265-77-4 | <3 |
| Acrylic Thickener | MIXTURE | <2 |
| Titanium dioxide | 13463-67-7 | <2.0 |
| Ammonium Hydroxide | 7664-41-7 | <1.0 |

^{*}Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Inhalation of particulates unlikely due to product's physical state.

4. FIRST AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Seek immediate medical attention/advice.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If irritation persists, seek medical attention.

Inhalation Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains

difficult, get medical attention.

Ingestion Do not induce vomiting unless directed by medical personnel. If vomiting occurs, lean

patient forward to maintain an open airway & prevent aspiration. Get immediate medical

attention.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact

with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and

sneezing.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Provide general supportive measures and treat symptomatically. May aggravate

pre-existing skin disorders.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Water spray (fog). Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is combustible & may ignite if exposed to high temperature or direct flame.

Hazardous Combustion Products

Carbon, titanium & iron oxides, depending upon formulation.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal PrecautionsWear protective clothing as described in Section 8 of this safety data sheet.

Other Information Small Spills: 1 drum or less – Level D Equipment (gloves, chemical resistant apron, boots &

eye protection).

Large Spills: Rubber gloves, rubber boots, face shield & Tyvek suit as a minimum. Minimum level of PPE for releases in which the oxygen level is < 19.5% or is unknown, should be Level B: triple gloves (rubber gloves & nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing & boots, hard hat & self-contained breathing apparatus.

For Emergency Responders Restrict access to spill area.

Environmental Precautions Minimize use of water to prevent environmental contamination. Prevent spill or rinse from

contaminating storm drains, sewers, soil or groundwater. Do not allow discharge containing

this material to enter streams, ponds, estuaries, oceans or other waters unless in

accordance w/ requirements of National Pollutant Discharge Elimination System (NPDES) permit & permitting authority has been notified in writing prior to discharge. Do not allow discharge containing this material to enter sewer systems w/o previously notifying local sewage treatment plant authority. For information, contact State Water Board or EPA

Regional Office

Other: U.S. regulations may require reporting of spills of this material reaching surface

waters if sheen is formed.

Methods and Material for Containment and Cleaning Up

Methods for Containment Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Cleaning Up Sweep up absorbed material and shovel into suitable containers for disposal. Wash area

with soap and water. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling Avoid breathing vapors. Use only with adequate ventilation. Open windows & doors to

ensure fresh air cross-ventilation during application and curing. Wash thoroughly with soap and water after handling. Avoid contact with skin, eyes or clothing. While handling product keep out of reach of children and pets. Do not eat or drink while handling this material. See

section 6 of this SDS for clean up instructions.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Close container after each use. Store

containers away from excessive heat & freezing. Do not store @ temperatures above 120 °

F. Protect from direct sunlight. Store away from incompatible materials. To maximize shelf

life, store @ temperatures below 26C (80F).

Incompatible Materials Strong acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Exposure guidelines / protective equipment are for routine handling and accidental spills

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--------------------|---------------------------|--------------------------------------|------------------------------|
| Titanium dioxide | TWA: 10 mg/m ³ | TWA: 15 mg/m³ total dust | IDLH: 5000 mg/m ³ |
| 13463-67-7 | | (vacated) TWA: 10 mg/m³ total | |
| | | dust | |
| Ammonium Hydroxide | STEL: 35 ppm | TWA: 50 ppm | IDLH: 300 ppm |
| 7664-41-7 | TWA: 25 ppm | TWA: 35 mg/m ³ | TWA: 25 ppm |
| | | (vacated) STEL: 35 ppm | TWA: 18 mg/m ³ |
| | | (vacated) STEL: 27 mg/m ³ | STEL: 35 ppm |
| | | | STEL: 27 mg/m ³ |

Appropriate Engineering Controls

Engineering Controls

Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face ProtectionUse approved safety goggles or safety glasses. If necessary, refer to appropriate

regulations & standards.

Skin and Body Protection Skin: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill

response. If necessary, refer to appropriate regulations & standards.

Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment) or appropriate Standards of Canada. Use foot protection, as described in appropriate regulations &

standards.

Respiratory Protection If mists or sprays are created, use appropriate respiratory protection. Oxygen levels below

19.5% considered IDLH by OSHA. In such instances, use full-facepiece pressure demand SCBA or a full facepiece, supplied air respirator w/ auxillary self-contained air supply.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Smooth paste

Appearance White & Biscuit; paste. Cartridges & Odor Mild acrylic

Squeeze tubes

ColorWhite & ColorsOdor ThresholdNot determined

Property Note: The information below is not Remarks • Method

intended for use in preparing

product specifications

pH 7.0-9.0

Melting Point/Freezing Point < 0 °C / <32 °F Boiling Point/Boiling Range Not Established

Flash Point > 93.33 °C / > 200 °F

Evaporation Rate
Flammability (Solid, Gas)
Upper Flammability Limits
Lower Flammability Limit
Vapor Pressure
Vapor Density
Specific Gravity
Not determined
Unknown
Unknown
Not established
Heavier than air

Specific Gravity \sim 1.0-1.10 @ 25 °C (77 °F)

Water Solubility Soluble in water Solubility in Other Solvents Not determined **Partition Coefficient** Not determined **Autoignition Temperature** Unknown **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined <1.5%

 VOC Content (%)
 <1.5%</td>

 VOC Content
 <25 g/L</td>

10. STABILITY AND REACTIVITY

Reactivity

Cures upon contact with air.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Incompatible Materials. Excessive heat or cold.

Incompatible Materials

Strong acids.

Hazardous Decomposition Products

Thermal decomposition can generate irritating dust, fumes and toxic gases (carbon, titanium, and iron oxides, depending upon formulation).

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Eye Contact Eye contact may result in tearing, redness & pain.

Skin Contact Prolonged and frequent contact may cause redness and irritation. Repeated skin contact

may cause dermatitis.

Inhalation Overexposure to vapors during application & curing may mildly irritate respiratory tract &

result in coughing & sneezing.

Ingestion

May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------------------------|---------------------|---------------------|--|
| Coalescent 25265-77-4 | = 3200 mg/kg (Rat) | > 15200 mg/kg (Rat) | - |
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Ammonium Hydroxide 7664-41-7 | = 350 mg/kg(Rat) | - | = 5.1 mg/L (Rat) 1 h = 2000 ppm (Rat) 4 h |

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Sensitization Not known to be human skin or respiratory sensitizers.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Trace residual Formaldehyde present in base emulsion viewed as possible cancer hazard.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|------------------|-------|----------|-----|------|
| Titanium dioxide | | Group 2B | | X |
| 13463-67-7 | | · | | |

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Acute: Eyes & Skin. Chronic: Skin.

Numerical Measures of Toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

PRACTICES SHOULD BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

Product not tested for aquatic or animal toxicity. Release of product to terrestrial, atmospheric & aquatic environments should be avoided.

| | Chemical Name | Algae/aquatic plants | Fish | Toxicity to microorganisms | Crustacea |
|---|---------------|--|---------------------|----------------------------|------------------------|
| Γ | Coalescent | 18.4: 72 h | 30: 96 h Pimephales | | 95: 96 h Daphnia magna |
| | 25265-77-4 | Pseudokirchneriella subcapitata mg/L EC50 | promelas mg/L LC50 | | mg/L LC50 |

| Ammonium Hydroxide 7664-41-7 | 0.44: 96 h Cyprinus carpio mg/L LC50 0.26 - 4.6: 96 h | 25.4: 48 h Daphnia magna mg/L LC50 |
|---------------------------------|--|---------------------------------------|
| 7004-41-7 | Lepomis macrochirus mg/L | mg/L LC30 |
| | LC50 1.17: 96 h Lepomis | |
| | macrochirus mg/L LC50 | |
| | flow-through 0.73 - 2.35: 96 | |
| | h Pimephales promelas | |
| | mg/L LC50 5.9: 96 h | |
| | Pimephales promelas mg/L | |
| | LC50 static 1.5: 96 h | |
| | Poecilia reticulata mg/L | |
| | LC50 1.19: 96 h Poecilia | |
| | reticulata mg/L LC50 static | |

Persistence and Degradability

Not tested for persistence & biodegradability

Bioaccumulation

Not tested for bio-accumulation potential

Mobility

Not tested for mobility in soil

| Two tested for mobility in soil | | | |
|---------------------------------|-----------------------|--|--|
| Chemical Name | Partition Coefficient | | |
| Coalescent 25265-77-4 | 3.47 | | |
| Ammonium Hydroxide 7664-41-7 | -1.14 | | |

Other Adverse Effects

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

Ozone

Not expected to produce any ozone depletion

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of WastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number Not applicable.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Listed
DSL Listed
NDSL Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|--------------------|--------------------------|----------------|--------------------------|
| Ammonium Hydroxide | 100 lb | 100 lb | RQ 100 lb final RQ |
| 7664-41-7 | | | RQ 45.4 kg final RQ |

SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardNoFire hazardNoSudden release of pressure hazardNoReactive HazardNo

SARA 313

| Chemical Name | CAS No | Weight-% | SARA 313 - Threshold Values % |
|--------------------------------|-----------|----------|----------------------------------|
| Ammonium Hydroxide - 7664-41-7 | 7664-41-7 | <1.0 | 1.0 |

CWA (Clean Water Act)

| Component | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|--|--------------------------------|------------------------|---------------------------|-------------------------------|
| Ammonium Hydroxide 7664-41-7 (<1.0) | 100 lb | | | Х |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

| Chemical Name | California Proposition 65 |
|-------------------------------|---------------------------|
| Titanium dioxide - 13463-67-7 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|---------------------------------|------------|---------------|--------------|
| Titanium dioxide 13463-67-7 | X | X | X |
| Ammonium Hydroxide 7664-41-7 | X | X | X |

| 10. UTHER INFURIMATION | u |
|------------------------|----------|
| | |

| <u>NFPA</u> | Health Hazards | Flammability | Instability | Special Hazards |
|-------------|----------------|--------------|------------------|---------------------|
| | 1 | 1 | 0 | Not determined |
| HMIS_ | Health Hazards | Flammability | Physical Hazards | Personal Protection |
| | 1 | 1 | 0 | Not determined |

Issue Date11-Mar-2013Revision Date07-Jul-2022

Revision Note New Product Number Addition 0758

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet