

Safety Data Sheet

Issue Date: 19-Aug-2018 Revision Date: 22-Aug-2018 Version 1

1. IDENTIFICATION

Product identifier

Product Name Strong Bond™ Heavy-Duty Adhesive & Sealant-White

Other means of identification

SDS # RD-181

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive/sealant.

Details of the supplier of the safety data sheet

Supplier Address

Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com

Emergency telephone number

Company Phone Number 918-825-5744

Fax: 918-825-5761

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

AppearanceWhite & Various OtherPhysical statePasteOdorTypical

Colors

Classification

The classification and labeling information in this Safety Data Sheet should be viewed as provisional, as the product's ingredients and percentages are kept as a trade secret / proprietary.

Acute toxicity - Dermal	Category 4
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word Warning

Hazard statements

Harmful in contact with skin
Causes serious eye irritation
May cause an allergic skin reaction



Precautionary Statements - Prevention

Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing must not be allowed out of the workplace

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of water and soap

Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention Call a poison center or doctor/physician if you feel unwell

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Very toxic to aquatic life with long lasting effects

Unknown Acute Toxicity

NOTE: Acute Toxicity classifications / calculations are approximates

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Calcium Carbonate	471-34-1	50
Silyl Terminated Polyether	NA1	30-35
Vinyltrimethoxysilane	2768-02-7	1-5
Titanium dioxide	13463-67-7	1-5
Petroleum distillates, hydrotreated middle	64742-46-7	1-5
Micronised Wax	NA2	1-5
Diisodecyl phthalate	26761-40-0	1
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	<1
Dibutyltin Diacetyldiacetonate	22673-19-4	<1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

(Calcium Carbonate, Titanium Dioxide) Inhalation of particulates unlikely due to product's physical state.

4. FIRST AID MEASURES

Description of first aid measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Seek immediate medical attention/advice. Rinse immediately with plenty of water, also

under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical

advice/attention.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation or rash occurs: Get medical advice/attention. Call a

Revision Date: 22-Aug-2018

physician if you feel unwell.

Inhalation Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician/poison center

if individual's condition declines or if symptoms persist.

Ingestion Rinse mouth. Do not induce vomiting, unless directed by medical personnel. Never give

anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. Get medical

attention if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact

with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and sneezing. The product contains a small amount of sensitizing substance which may provoke an allergic reaction among sensitive individuals in contact with skin.

Notes to Physician Provide general supportive measures and treat symptomatically. May aggravate

pre-existing skin disorders.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire Use carbon dioxide (CO2), dry chemical or water spray.

Large Fire Dry chemical, Use foam or water spray.

Indication of any immediate medical attention and special treatment needed

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is combustible & may ignite if exposed to high temperature or direct flame.

Hazardous combustion products Carbon oxides. Hydrogen chloride.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal PrecautionsWear protective clothing as described in Section 8 of this safety data sheet.

For Emergency Responders Restrict access to spill area.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Clean-Up Sweep up absorbed material and shovel into suitable containers for disposal. Wash area

with soap and water. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Contaminated work clothing must not be allowed out of the workplace. Wash face, hands and any exposed skin thoroughly after handling. Avoid

Revision Date: 22-Aug-2018

breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container closed & store in a cool, well-ventilated area. Avoid contact w/ water or

moisture. Keep container from excessive heat & freezing. Store away from incompatible

materials.

Incompatible Materials Strong oxidizing agents. Acids. Bases. Combustible material.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate	-	-	TWA: 10 mg/m ³ total dust
471-34-1			TWA: 5 mg/m ³ respirable dust
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7	_	(vacated) TWA: 10 mg/m ³ total	
		dust	TWA: 0.3 mg/m ³ CIB 63
			ultrafine, including engineered
			nanoscale
Dibutyltin Diacetyldiacetonate	STEL: 0.2 mg/m ³ Sn	TWA: 0.1 mg/m ³ Sn	IDLH: 25 mg/m ³ Sn
22673-19-4	TWA: 0.1 mg/m ³ Sn	(vacated) TWA: 0.1 mg/m ³ Sn	TWA: 0.1 mg/m ³ except
	S*	(vacated) S*	Cyhexatin Sn

Pre-existing respiratory disorders may be aggravated by exposure. If sanded, this material may generate titanium dioxide dust. Inhaled titanium dioxide has been classified by IARC

as a human carcinogen (see section 11).

Appropriate engineering controls

Ventilation must be adequate to maintain the ambient workplace atmosphere below the **Engineering Controls**

exposure limit(s) outlined in the SDS.

Individual protection measures, such as personal protective equipment

Use approved safety goggles or safety glasses. If necessary, refer to appropriate **Eye/Face Protection**

regulations and standards. Refer to 29 CFR 1910.133 for eye and face protection

regulations.

Skin and Body Protection Wear protective gloves and protective clothing. Reference Wiley's "Quick Selection Guide

to Chemical Protective Clothing". Refer to 29 CFR 1910.138 for appropriate skin and body

protection.

If mists or sprays are created, use appropriate respiratory protection. Oxygen levels below **Respiratory Protection**

19.5% considered IDLH by OSHA. In such instances, use full-facepiece pressure demand SCBA or a full facepiece, supplied air respirator w/ auxillary self-contained air supply. Refer

to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Avoid contact with skin, eyes and clothing. After handling this product, wash hands before

eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before

reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Paste

Appearance White & Various Other Colors Odor Typical

Color Various **Odor Threshold** Not determined

Remarks • Method **Property** Values

Not determined

Not determined

Not available pН Melting point / freezing point Not determined Boiling point / boiling range Not determined Flash point Not determined **Evaporation Rate** Not determined Flammability (Solid, Gas) Not determined Flammability Limit in Air

Upper flammability or explosive

limits

Lower flammability or explosive Not determined

limits

Oxidizing Properties

Vapor Pressure Not determined **Vapor Density** Not determined

Relative Density 16 **Water Solubility** insoluble Solubility in other solvents Not determined **Partition Coefficient** Not determined **Autoignition temperature** Not determined **Decomposition temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Incompatible Materials. Excessive heat or cold.

Incompatible materials

Strong oxidizing agents. Acids. Bases. Combustible material.

Hazardous decomposition products

Carbon oxides. Calcium oxides. Hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes eye irritation.

May cause an allergic skin reaction. May be harmful in contact with skin. Prolonged and **Skin Contact**

frequent contact may cause redness and irritation. Repeated skin contact may cause

dermatitis.

Inhalation May cause irritation if inhaled.

Ingestion May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium Carbonate	= 6450 mg/kg (Rat)	-	-
471-34-1			
Petroleum distillates, hydrotreated middle 64742-46-7	= 7400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 4.6 mg/L (Rat)4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Vinyltrimethoxysilane 2768-02-7	= 7340 μL/kg (Rat)	= 3360 μL/kg (Rabbit)	-
Diisodecyl phthalate 26761-40-0	= 64 g/kg (Rat)	> 3160 mg/kg (Rabbit)	> 12.54 mg/L (Rat)4 h
N-(3-(Trimethoxysilyl)propyl)ethylen	= 2413 mg/kg (Rat) = 7460 μ L/kg	-	-
ediamine	(Rat)		
1760-24-3			

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

RD-181 - King Kaulk Adhesive & Sealant-White & Colors

Revision Date: 22-Aug-2018

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.

CarcinogenicityTitanium dioxide is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
13463-67-7				

Legend

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document ...

Unknown Acute Toxicity NOTE: Acute Toxicity classifications / calculations are approximates.

ATEmix (oral) 6,233.10 mg/kg
ATEmix (dermal) 1,161.10 mg/kg
ATEmix (inhalation-dust/mist) 30.00 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Crustacea	
Petroleum distillates, hydrotreated		35: 96 h Pimephales promelas mg/L		
middle		LC50 flow-through 10000: 96 h		
64742-46-7		Pimephales promelas mg/L LC50		
		static		
Diisodecyl phthalate	500: 72 h Desmodesmus	0.55: 96 h Lepomis macrochirus	500: 24 h Daphnia magna Straus	
26761-40-0	subspicatus mg/L EC50 0.8: 96 h	mg/L LC50 static 1: 96 h	mg/L EC50 0.02: 48 h Daphnia	
	Pseudokirchneriella subcapitata	Pimephales promelas mg/L LC50	magna mg/L EC50 Static	
	mg/L EC50 static	flow-through 10000: 96 h Leuciscus		
	_	idus mg/L LC50 static		

Persistence/Degradability

Biological/Abiological Degradation – Evaluation: Poorly biodegradable. Product unstable in water. The elimination data also refer to products of hydrolysis.

Bioaccumulation

There is no data for this product.

Mobility

Not tested for mobility in soil

Other Adverse Effects

Do not discharge into environment w/o control. Product has not been tested. Statements on Ecotoxicology derived from properties of individual components

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal should be in accordance with applicable regional, national and local laws and **Disposal of Wastes**

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Dibutyltin Diacetyldiacetonate	Toxic
22673-19-4	

14. TRANSPORT INFORMATION

Please see current shipping paper for most up to date shipping information, including Note

exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Calcium Carbonate	Х	Х	Х	Х	Х	Х	Х	Х
Petroleum distillates, hydrotreated middle	Х	Х	Х		Х	Х	Х	Х
Titanium dioxide	Х	Х	Х	Х	Х	Х	Х	Х
Vinyltrimethoxysilane	Х	Х	Х	Х	Х	Х	Х	Х
Diisodecyl phthalate	Х	Х	Х	Χ	Х	Х	Х	Х
N-(3-(Trimethoxysilyl)propyl) ethylenediamine	Х	Х	Х	Х	Х	Х	Х	Х
Dibutyltin Diacetyldiacetonate	X	Х	Х	Х	Х	Х	Х	Х

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Not determined

CWA (Clean Water Act)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Diisodecyl phthalate		X		

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65	
Titanium dioxide - 13463-67-7	Carcinogen	
Diisodecyl phthalate - 26761-40-0	Developmental	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Titanium dioxide 13463-67-7	X	X	Х
Diisodecyl phthalate 26761-40-0			Х

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	3	1	0	Not determined
HMIS_	Health Hazards	Flammability	Physical hazards	Personal Protection
	3*	1	0	X

* = Chronic Health Hazard Chronic Hazard Star Legend

Issue Date: 19-Aug-2018 22-Aug-2018 **Revision Date: Revision Note:** New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet