Red Devil

READY TO USE SELF-LEVELING

CONCRETE CRACK FILLER

Red Devil Concrete Crack Filler is an easy-to-use, pre-mixed material formulated to fill and repair narrow cracks on any horizontal concrete surface. This self-leveling solution dries to a smooth gray finish that naturally blends with the surface, and provides a durable, weather resistant seal that accommodates minor concrete settlement and movement.

USES:

Driveways, Sidewalks, Patios/Slabs, Garage Floors, & Basement Floors



FEATURES:

- **Repairs Narrow Cracks**
  Fills cracks up to 1/2” (12 mm) wide and 1/4” (6 mm) deep.
- **Ready-to-Use**
  No mixing required - just shake, pour, and let it cure.
- **Self-Leveling Formula**
  Provides easy precison tooling for narrow crack line applications.
- **Weather-Resistant Seal**
  Resists cracking, shrinking, and water penetration.
- **Natural Concrete Finish**
  Dries to a light gray color that blends with most concrete.
- **Quick Set Time**
  Withstands light foot traffic in under an hour after application.
- **Superior Adhesion**
  Forms a strong, durable bond to cementitious building materials.

INTERIOR/ EXTERIOR

TACK FREE IN UNDER 1 HOUR

EASY WATER CLEAN-UP

LOW ODOR & LOW VOC

MADE IN THE USA

www.reddevil.com
Customer Service: 1-800-423-3845

Red Devil, Inc.
4175 Webb Street
Pryor, OK 74361

TECHNICAL DATA SHEET

CONCRETE CRACK FILLER

PART#	COLOR	PACKAGE	UPC #	CASE QTY.
0649	Gray	32 fl. oz Bottle	0-75339-04360-8	6

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 11.2
Total Non-Volatile % Solids (Weight): 75%
Viscosity: 30,000 cps
Consistency/Appearance: Gray Liquid Material
Odor: Mild
Base Polymer: Copolymer Emulsion
pH: 8 to 9
Elongation At Break: 50%
Tensile Strength: 8 lbs.
Dry Application Adhesive Strength: 16 lbs.
Wet Application Adhesive Strength: 5.5 lbs
Shore A Hardness: 85
Tack Free Time: 50 Minutes
Rain Ready Time: 24 Hours
Full Cure: 24 Hours
Application Temperature: 45°F to 100°F (7°C to 37°C)
Service Temperature: -30°F to 150°F (-34°C to 65°C)
Coverage: 38 linear feet at 1/4" deep x 1/2" wide
Shelf Life: Expect 1 Year @ 72°F

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	Yes (See MSDS)
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazzard	None
DOT UN/NA Number	None
Packing Group	None
VOC Content	35.7 g/L

LIMITED WARRANTY:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

APPLICATION:

1. Remove all loose dirt and debris, oil, grease, and other foreign materials that may interfere with adhesion or performance. Ensuring the application area is completely clean and structurally sound.
2. For cracks deeper than ¼" (6 mm), use clean fine sand or backer rod to fill the crack up to 1/4" (6 mm) below the surface.
3. Shake the bottle thoroughly before each use to ensure a consistent mixture.
4. Remove the cap, cut the tip of spout to a size slighty smaller than the crack.
5. Squeeze the Concrete Crack Filler directly into the crack, filling the crack up to or just above the surface. Smooth or tool the surface as needed for a uniform, level finish.
6. Protect new surfaces from heavy traffic and moisture exposure for 24 hours after application.

FOR BEST RESULTS:

- Apply when temperatures are above 45°F (7°C) and rain is not expected within 24 hours of application.
- Do not apply in cracks wider than ½" (12 mm).
- Ensure the application surface is clean and dry.
- Do not apply to concrete that has cured for less than 7 days.
- Store product in original container at 40°F(4°C) to 80°F(26°C) and protect from freezing.

CLEAN-UP:

Clean up excess wet material with a damp rag or sponge. Remove uncured material from skin and tools with soap and water immediately after use. Dried material must be mechanically removed.

LIMITATIONS:

- Deep cracks may require additional ¼" layers, allowing at least 24 hours between applications.
- Full cure of the product is dependent on temperature, humidity, and depth of repair. Cooler temperatures, higher humidity, & greater depth of repair will delay curing process.

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. (See SDS for additional safety information)
⚠ WARNING: Reproductive Harm Risk From Ethanediol & Cancer Risk From Titanium Dioxide Exposure - www.P65Warnings.ca.gov